

EMFA



Saturn
Downlight

SATURN LED DOWNLIGHT

Class II IP20

Available in any
of these RAL colors



The Saturn LED Downlight is specially designed to provide highest energy efficiency in general lighting applications. Using latest LED technology in combination with special plastic moulding and paint application allows for around 90lm/W lighting output. The highly efficient diffuser provides a completely homogenous light output.

Body

Die cast aluminium

Paint

Electrostatic powder paint RAL 9016 (available in other RAL colors)

Springs

Steel for mounting in ceilings of 1-25mm thickness

Gear

Non-Dimmable electronic LED driver (1-10V Dimmable and DALI drivers available on request)

Cable

0.5m exiting from top of fixture



COB LED

Led : 180mA 6W / 250mA 8W COB LED


Reflector : 10° / 38° / 60°

Gear : 240V Non-Dimmable Driver

(1-10V Dimmable Driver and DALI Driver available on request)


Cable : 0.5 m 2x0,75 mm H03 VV-F

FIXED




Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°,38°,60°	528004
6W LED	3000 K	570 lm	10°,38°,60°	528001
6W LED	4000 K	581 lm	10°,38°,60°	528002
6W LED	6000 K	593 lm	10°,38°,60°	528003
8W LED	2700 K	760 lm	10°,38°,60°	528014
8W LED	3000 K	760 lm	10°,38°,60°	528011
8W LED	4000 K	774 lm	10°,38°,60°	528012
8W LED	6000 K	790 lm	10°,38°,60°	528013

ADJUSTABLE



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°,38°,60°	528104
6W LED	3000 K	570 lm	10°,38°,60°	528101
6W LED	4000 K	581 lm	10°,38°,60°	528102
6W LED	6000 K	593 lm	10°,38°,60°	528103
8W LED	2700 K	760 lm	10°,38°,60°	528114
8W LED	3000 K	760 lm	10°,38°,60°	528111
8W LED	4000 K	774 lm	10°,38°,60°	528112
8W LED	6000 K	790 lm	10°,38°,60°	528113



Honeycomb
Code No: 953956