ASSOS 4 RECESSED DRIVE OVER FIXTURES Load 15 kN | Class I IP67 IK10

Available in any of these RAL colors









EMFA's Assos 4 series is specially designed to light facades, columns, monuments and trees. The fixture can be equipped with metal halide, halogen or fluorescent lamps. The fixture has 3 different options of cover: 316 stainless steel, die cast aluminium or bronze in combination with the die cast aluminium body which allows for IP67 and IK10 and a load of 15kN. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete. A louvre can be ordered separately to reduce the glare of the lamps. An anti-slip glass is available upon request.

Cover

Die cast aluminium / 316L Stainless Steel

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box. Gaskets

Silicone


Diffusers


15 mm Tempered Glass Screws 316L Stainless steel

Glands 2 x PG 13.5

Recessing Tube Polyamide 6











Lampholder: G12 Fixed or Adjustable ± 20°

Reflector : 30°, 42° Diffuser : Clear Glass : 35W - 99°C Temp 70W - 144°C

Alum.

150W - 238°C

METAL HALIDE 35W / 70W / 150W

Accessories:



Louvre To avoid glare.

Can be applied to all lamp types except Halogen PAR 30

and 38

Code No 955105


Caution:

The louvre and filter cannot be applied to the standard fixture. These options should be mentioned when ordering.



Anti-slip Glass

Please contact for this option.



206241

Code No

