


 Drive Over



EMFA

MILET ANI

RECESSED DRIVE OVER FIXTURES

Load 8 kN | Class I IP67 IK10

EMFA's Ani step mounted series is specially designed to deliver low-glare lighting to facades, columns, monuments, and trees with minimal installation depth and narrow trim. The fixture is made of a combination of 316L stainless steel and die cast aluminium. The tilted design reduces the glare of the LED's. The Linear LEDs with special lenses gives excellent wallwashing effect. An anti-slip glass is available upon request.

Cover

316L Stainless steel

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

8 mm Tempered Glass


Screws

316L Stainless Steel




"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, and 2 wattages, and available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



Symmetrical



Galvanized
Recessing Box


LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Asymmetrical



Asym. Glass




Trenched Glass




Milky Glass





Clear Glass






Led : Linear LEDs
Voltage : 240 VAC with integrated driver
 (12-24 VDC on request)
Diffuser : 8mm Tempered Glass
Beam Angle : 45° / 60° / 90°
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F

ANI 1






Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
6W	2700 K	570 lm	450003	450503
6W	3000 K	570 lm	450001	450501
6W	4000 K	690 lm	450002	450502
12W	2700 K	1140 lm	450013	450513
12W	3000 K	1140 lm	450011	450511
12W	4000 K	1195 lm	450012	450512

ANI 2




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
12W	2700 K	1140 lm	450013	450603
12W	3000 K	1140 lm	450101	450601
12W	4000 K	1254 lm	450102	450602
24W	2700 K	2280 lm	450113	450613
24W	3000 K	2280 lm	450111	450611
24W	4000 K	2320 lm	450112	450612

ANI 3



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
18W	2700 K	1710 lm	450203	450703
18W	3000 K	1710 lm	450201	450701
18W	4000 K	1790 lm	450202	450702
36W	2700 K	3420 lm	450213	450713
36W	3000 K	3420 lm	450211	450711
36W	4000 K	3520 lm	450212	450712

ANI 4



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
24W	2700 K	2280 lm	450303	450803
24W	3000 K	2280 lm	450301	450801
24W	4000 K	2320 lm	450302	450802
36W	2700 K	3420 lm	450313	450813
36W	3000 K	3420 lm	450311	450811
36W	4000 K	3520 lm	450312	450812



Galvanized Recessing Box

KNIDOS

RECESSED DRIVE OVER FIXTURES

Load 20 kN | Class I IP67 IK10

EMFA's Knidos series consists of a range of LED, metal halide, and fluorescent sources to deliver the desired light effect to facades, columns, monuments and trees. The fixture is made of a combination of 316L stainless steel and glass reinforced polyester, which makes it completely resistant to corrosion. The sturdy fixture allows loads up to 20kN and IK 10. The LEDs used come in 3 different tones of white, as well as blue, red, green, and amber. An anti-slip glass is available upon request.

Adjustable Asymmetrical LEDs

In this series EMFA is introducing its first adjustable asymmetric LED unit. The LEDs can be internally adjusted up to 40 degree to give the desired light output to facades, columns, monuments, and trees without losing light to the sky. The Knidos is large enough, and has enough surface area so that at an ambient temperature of 50° C, 9 LEDs can be operated at 350 mA (9W).

Cover

316L Stainless steel

Body

Glass reinforced polyester

Gaskets

Silicone

Diffusers

12 mm Tempered Glass

Screws



316L Stainless Steel

"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Accessories:



Anti-slip Glass

Please contact for this option.

MILET ANI

RECESSED DRIVE OVER FIXTURES

Load 8 kN | Class I IP67 IK10



Voltage : 240V A.C with integrated driver
(24V AC or DC on request)


Diffuser : 12 mm Clear Glass (Frosted Glass on request)

Mac Adam : 3

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

LED




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Flush Mounted	Step Mounted
9W	2700 K	810 lm	10°, 25°, 40°	258003	258013
9W	3000 K	810 lm	10°, 25°, 40°	258001	258011
9W	4000 K	891lm	10°, 25°, 40°	258002	258012
18W	2700 K	1620 lm	10°, 25°, 40°	258021	258031
18W	3000 K	1620 lm	10°, 25°, 40°	258022	258032
18W	4000 K	1782 lm	10°, 25°, 40°	258023	258033

METAL HALIDE SPOT




Power	Lampholder	Reflector	Code No	
			Flush Mounted	Step Mounted
CDMR-111 35W	Gx8,5	10°, 40°	254301	254311
CDMR-111 70W	Gx8,5	10°, 40°	254401	254411

METAL HALIDE WALLWASHER




Power	Lampholder	Reflector	Code No	
			Flush Mounted	Step Mounted
35W	Rx 7s	Asym. 50°	251101	251201
150W	Rx 7s-24	Asym. 50°	251111	251211

METAL HALIDE



Power	Lampholder	Reflector	Code No	
			Flush Mounted	Step Mounted
35W	G12	30°, 42°	257001	257101
70W	G12	30°, 42°	257011	257111



Special Vantilation System
for Cooling



SANTOS 4

RECESSED DRIVE OVER FIXTURES

Load 10 kN | Class I IP67 IK10

EMFA's Santos flush mounted series is specially designed to deliver low-glare lighting to facades, columns, monuments and trees with minimal installation depth and narrow trim. The fixture is made of a combination of 316L stainless steel and die cast aluminium. A shield above the lamp reduces the glare of the metal halide lamps. A mirror finish reflector allows for a narrow to wide beam light output. An anti-slip glass is available upon request.

Cover

316L Stainless steel

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box

Gaskets

Silicone

Diffusers

8 mm Tempered Glass

Screws

316L Stainless steel


Glands

2 x PG 13.5


Recessing Tube

Polyamide 6


Mounting Feature



Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture. To make the fixture drive over, the recessing tube should be mounted flush to the ground.



Correct



Incorrect




This fixture is also available with 2 screws instead of 4. For this option, please contact us.




Anti-slip Glass

Please contact for this option.



Fixed

Adjustable



SANTOS 4

RECESSED DRIVE OVER FIXTURES Load 10 kN | Class I IP67 IK10



Voltage : 240V A.C with integrated driver
(24V AC or DC on request)


Diffuser : Clear Tempered Glass (Frosted Glass on request)

Mac Adam : 3

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

LED




Power	Kelvin	Real Lumen Output	Lens	Code No
9W	2700 K	855 lm	10°, 23°, 36°	550211
9W	3000 K	855 lm	10°, 23°, 36°	550212
9W	4000 K	872 lm	10°, 23°, 36°	550213
18W	2700 K	1710 lm	10°, 23°, 36°	550203
18W	3000 K	1710 lm	10°, 23°, 36°	550201
18W	4000 K	1744 lm	10°, 23°, 36°	550202

HALOGEN




Power	Lampholder	Reflector	Code No
PAR30 75W	E27 Adjustable	38°	550101

METAL HALIDE



Power	Lampholder	Reflector	Code No
20W	G 8.5 Fixed	12°, 36°	550111
35W	G 8.5 Fixed	12°, 36°	550121
70W	G 8.5 Fixed	12°, 36°	550131

METAL HALIDE



Power	Lampholder	Reflector	Code No
35W	Gx8,5 Adjustable	10°, 40°	550151
70W	Gx8,5 Adjustable	10°, 40°	550161

SANTOS 5

RECESSED DRIVE OVER FIXTURES

Load 6 kN | Class I IP67 IK10

EMFA's Santos step mounted series is specially designed to deliver low-glare lighting to facades, columns, monuments and trees with minimal installation depth and narrow trim. The fixture is made of a combination of 316L stainless steel and die cast aluminium. A shield above the lamp reduces the glare of the metal halide lamps. A mirror finish reflector allows for a narrow to wide beam light output. An anti-slip glass is available upon request.

Cover

316L Stainless steel

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box

Gaskets

Silicone

Diffusers

8 mm Tempered Glass

Screws

316L Stainless steel


Glands

2 x PG 13.5


Recessing Tube

Polyamide 6


Mounting Feature



Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture. To make the fixture drive over, the recessing tube should be mounted flush to the ground.



Correct



Incorrect

When mounting the fixture on uneven surfaces, place so that the water does not accumulate on the surface of the fixture.





This fixture is also available with 2 screws instead of 4. For this option, please contact us.




Anti-slip Glass

Please contact for this option.



Fixed

Adjustable



SANTOS 5

RECESSED DRIVE OVER FIXTURES Load 10 kN | Class I IP67 IK10



Voltage : 240V A.C with integrated driver
(24V AC or DC on request)


Diffuser : 12 mm Clear Glass (Frosted Glass on request)

Mac Adam : 3

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

LED




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W	2700 K	855 lm	10°, 23°, 36°	551321	551331
9W	3000 K	855 lm	10°, 23°, 36°	551322	551332
9W	4000 K	872 lm	10°, 23°, 36°	551323	551333
18W	2700 K	1710 lm	10°, 23°, 36°	551303	551313
18W	3000 K	1710 lm	10°, 23°, 36°	551301	551311
18W	4000 K	1744 lm	10°, 23°, 36°	551302	551312

HALOGEN




Power	Lampholder	Reflector	Code No	
			Round	Square
PAR30 75W	E27 Adjustable	38°	551101	551201

METAL HALIDE



Power	Lampholder	Reflector	Code No	
			Round	Square
20W	G 8.5 Fixed	12°, 36°	551111	551211
35W	G 8.5 Fixed	12°, 36°	551121	551221
70W	G 8.5 Fixed	12°, 36°	551131	551231

METAL HALIDE SPOT



Power	Lampholder	Reflector	Code No	
			Round	Square
35W	Gx8,5 Adjustable	10°, 40°	551151	551251
70W	Gx8,5 Adjustable	10°, 40°	551161	551261




EMFA

TEOS 3 RECESSED DRIVE OVER FIXTURES

Load 50 kN | Class I IP67 IK10

Available in any
of these RAL colors



EMFA's Teos 3 Recessed Drive Over LED Fixture is specially designed to deliver high output LED light to ground surfaces of roads, carparks and pathways. This heavy duty fixture is designed to withstand the weight of large vehicles. Its robust construction allows for a maximum static load of 5000kg. The body and head of the fixture are made of die cast aluminium, while the recessing tube is made of steel to withstand the repeated impact of driving vehicles' tires. The high power LEDs are positioned and angled to provide maximum light output. The electronic LED driver is housed in the base of the fixture. The fixture comes with 2 x PG13.5 cable glands and 0.5m cable.

Cover

Die cast aluminium

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

Polycarbonate

Screws

316L Stainless steel

Glands

2 x PG 13.5

Cable

0.5m 3x0,75 mm H05VV-F


Recessing Tube

Electrostatic powder paint

Coated steel




Mounting Feature




Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture.

To make the fixture drive over, the recessing tube should be mounted flush to the ground.



Correct



Incorrect

When mounting the fixture on uneven surfaces, place so that the water does not accumulate on the surface of the fixture.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.



Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

TEOS 3 RECESSED DRIVE OVER FIXTURES

Load 50 kN | Class I IP67 IK10


Available in any of these RAL colors



- Led** : Linear LEDs
- Voltage** : 240 VAC with integrated driver (12-24 VDC on request)
- Diffuser** : Polycarbonate
- CRI** : >80 or >90
- Cable** : Potted 1m 3x1 H03 VV-F




Mono



Power	Kelvin	Real Lumen Output	Code No
1x 4W	2700 K	1x 380 lm	180103
1x 4W	3000 K	1x 380 lm	180101
1x 4W	4000 K	1x 418 lm	180102




Duo 1-way



Power	Kelvin	Real Lumen Output	Code No
2x 4W	2700 K	2x 380 lm	180113
2x 4W	3000 K	2x 380 lm	180111
2x 4W	4000 K	2x 392 lm	180112




Duo 2-way




Power	Kelvin	Real Lumen Output	Code No
2x 4W	2700 K	2x 380 lm	180123
2x 4W	3000 K	2x 380 lm	180121
2x 4W	4000 K	2x 392 lm	180122




Trio




Power	Kelvin	Real Lumen Output	Code No
3x 4W	2700 K	3x 380 lm	180133
3x 4W	3000 K	3x 380 lm	180131
3x 4W	4000 K	3x 392 lm	180132



Quad



Power	Kelvin	Real Lumen Output	Code No
4x 4W	2700 K	4x 380 lm	180143
4x 4W	3000 K	4x 380 lm	180141
4x 4W	4000 K	4x 392 lm	180142



Lux levels for one aperture at 3000K

MIRA

RECESSED DRIVE OVER FIXTURES

Load 20 kN | Class I IP67 IK10

The Mira series consists of a range of LED and fluorescent sources to deliver the desired light effect to facades, columns, bridges, monuments, and signs. The series is made of a die cast aluminium body with electrostatic powder paint finished with a 316L stainless steel cover. The recessed versions are for drive over up to 20 kN including a stainless steel recessing box. The surface mounted versions come with a heavy-duty 316L stainless steel bracket. The fixtures come with integrated electronic ballasts and a specially developed potted power cable to effectively bond with the cast resin and stop any water ingress. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Cover

316L Stainless steel

Body

Die cast aluminium

Diffusers

12 mm Tempered Glass

Gaskets


Silicone

Screws

316L Stainless steel

Recessing Box

Stainless steel



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

MIRA


RECESSED DRIVE OVER FIXTURES

Load 20 kN | Class I IP67 IK10




Led : Power LEDs
Voltage : 240 VAC with integrated driver (12-24 VDC on request)
Diffuser : 12mm Tempered Glass
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F
 Single color LED options upon request are ;
 Blue Amber Green Red

MIRA 1 LED





Power	Kelvin	Real Lumen Output	Lens	Code No	
				Symmetrical	Asymmetrical
12W	2700 K	1140 lm	10°, 25°, 40°	430118	430513
12W	3000 K	1140 lm	10°, 25°, 40°	430111	450501
12W	4000 K	1160 lm	10°, 25°, 40°	430116	450502
12W	6000 K	1185 lm	10°, 25°, 40°	430117	450512
27W	RGB	Red Green Blue	25°, 40°	430161	430361

MIRA 2 LED




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Symmetrical	Asymmetrical
36W	2700 K	3420 lm	10°, 25°, 40°	430614	430608
36W	3000 K	3420 lm	10°, 25°, 40°	430611	430601
36W	4000 K	3488 lm	10°, 25°, 40°	430612	430606
36W	6000 K	3557 lm	10°, 25°, 40°	430613	430607
81W	RGB	Red Green Blue	25°, 40°	430621	430631

MIRA 2 LED



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
12W	2700 K	1140 lm	430723	
12W	3000 K	1140 lm	430721	
12W	4000 K	1160 lm	430722	
12W	6000 K	1185 lm	430724	

MIRA 2 METAL HALIDE




Power	Lampholder	Code No	
		Symmetrical	Asymmetrical
70W	G 8,5 METAL HALIDE	430711	

ASSOS 2

RECESSED DRIVE OVER FIXTURES

Load 15 kN | Class I IP67 IK10

Available in any
of these RAL colors



EMFA's Assos 2 series is specially designed to light facades, columns, monuments and trees with a die cast aluminium grill protecting the glass. The fixture can be equipped with metal halide, halogen or fluorescent lamps. The fixture is made completely of die cast aluminium body, which allows for IP67 and IK10 and a load of 15kN. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete. A louvre can be ordered separately to reduce the glare of the lamps.

Cover

Die cast aluminium

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Gaskets

Silicone

Diffusers

8 mm Tempered Glass

Screws

316L Stainless steel


Glands

2 x PG 13.5

Recessing Tube

Polyamide 6


Mounting Feature




Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture. To make the fixture drive over, the recessing tube should be mounted flush to the ground.



This fixture is suitable for helicopter landing pads due to its heavy duty aluminium cover.




HALOGEN



Power	Lampholder	Reflector	Code No
PAR30 75W	E27	38°	201131

METAL HALIDE




Power	Lampholder	Reflector	Code No
35W	G 12 Adjustable	30°, 42°	201141
70W	G 12 Adjustable	30°, 42°	201151
150W	G 12 Adjustable	30°, 42°	201161

ASSOS 3

RECESSED DRIVE OVER FIXTURES

Load 15 kN | Class I IP67 IK10

Available in any
of these RAL colors



EMFA's Assos 3 series is specially designed to light pathways, roads, and gardens. The fixture can be equipped with LED, halogen or fluorescent lamps. The fixture has 3 different options of cover: Multi, Mono, Dual, and Wall to give different lighting effects. In combination with the die cast aluminium body, the fixture allows for IP67 and IK10 and a load of 15kN. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete.

Cover

Die cast aluminium

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Gaskets

Silicone

Diffusers

Tempered press glass or polycarbonate

Screws

316L Stainless steel

Glands


2 x PG 13.5

Recessing Tube

Polyamide 6



Mounting Feature



Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture.

To make the fixture drive over, the recessing tube should be mounted flush to the ground.

LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.





Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

ASSOS 3

RECESSED DRIVE OVER FIXTURES Load 15 kN | Class I IP67 IK10


Available in any
of these RAL colors



Voltage : 240 VAC with integrated driver
(12-24 VDC on request)
Diffuser : Polycarbonate
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F




Mono



Power	Kelvin	Real Lumen Output	Code No
1x 4W LED	2700 K	1x 380 lm	203142
1x 4W LED	3000 K	1x 380 lm	203141
1x 4W LED	4000 K	1x 387 lm	203143
1x 4W LED	6000 K	1x 395 lm	203144
HALOGEN 25-40W		G 9	203101




Dual




Power	Kelvin	Real Lumen Output	Code No
2x 4W LED	2700 K	2x 380 lm	204142
2x 4W LED	3000 K	2x 380 lm	204141
2x 4W LED	4000 K	2x 387 lm	204143
2x 4W LED	6000 K	2x 395 lm	204144
HALOGEN 25-40W		G 9	204101




Multi



Power	Kelvin	Real Lumen Output	Code No
1x 11W LED	2700 K	1045 lm	202142
1x 11W LED	3000 K	1045 lm	202141
1x 11W LED	4000 K	1065 lm	202143
1x 11W LED	6000 K	1087 lm	202144
HALOGEN 25-40W		G 9	202101



Wall



Power	Kelvin	Real Lumen Output	Code No
2x 4W LED	2700 K	2x 380 lm	205142
2x 4W LED	3000 K	2x 380 lm	205141
2x 4W LED	4000 K	2x 387 lm	205143
2x 4W LED	6000 K	2x 395 lm	205144
HALOGEN 25-40W		G 9	205101



ASSOS RECESSED DRIVE OVER FIXTURES

Load 15 kN | Class I IP67 IK10

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

EMFA's Assos series is specially designed to light facades, columns, monuments and trees. The fixture can be equipped with metal halide, halogen or fluorescent lamps. The fixture has 3 different options of cover: 316 stainless steel, die cast aluminium or bronze in combination with the die cast aluminium body which allows for IP67 and IK10 and a load of 15kN. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete. A louvre can be ordered separately to reduce the glare of the lamps. An anti-slip glass is available upon request.

Cover

Die cast aluminium / 316L Stainless Steel

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Gaskets

Silicone

Diffusers

15 mm Tempered Glass

Screws

316L Stainless steel

Glands


2 x PG 13.5

Recessing Tube


Polyamide 6




Mounting Feature



Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture. To make the fixture drive over, the recessing tube should be mounted flush to the ground.




Correct



Incorrect

When mounting the fixture on uneven surfaces, place so that the water does not accumulate on the surface of the fixture.



Louvre

To avoid glare. Can be applied to all lamp types except Halogen PAR 30 and 38 Code No 955105



Dichroic Color Glass Filter

Can be applied to all lamp types except Halogen PAR 38.

Code No 955101 - Blue
Code No 955102 - Red
Code No 955103 - Yellow
Code No 955104 - Green

Caution:

The louvre and filter cannot be applied to the standard fixture. These options should be mentioned when ordering.




Anti-slip Glass

Please contact for this option.

ASSOS RECESSED DRIVE OVER FIXTURES

Load 15 kN | Class I IP67 IK10

Available in any
of these RAL colors




Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Diffuser : 12 mm Clear Glass (Frosted Glass on request)


Cable : Potted 1m 3x1 H03 VV-F

ASSOS 4 HALOGEN




Power	Lampholder	Reflector	Code No	
			Alum	Inox
PAR30 75W	E27 Adjustable	38°	221311	221321

ASSOS 4 METAL HALIDE




Power	Lampholder	Reflector	Code No	
			Alum	Inox
35W M.H.	Gx8.5 Adjustable	12°, 36°	206271	207271
70W M.H.	Gx8.5 Adjustable	12°, 36°	551121	551221
35W M.H.	G 12 Adjustable	30°, 42°	206241	207241
70W M.H.	G 12 Adjustable	30°, 42°	206251	207251
150W M.H.	G 12 Adjustable	30°, 42°	206261	207261

ASSOS 4 HALOGEN



Power	Lampholder	Reflector	Code No	
			Alum	Inox
PAR30 75W	E27 Adjustable	38°	221391	
HALOGEN RJ111 50W	G 53	38°		212291

ASSOS 4 HALOGEN



Power	Lampholder	Reflector	Code No	
			Alum	Inox
35W M.H.	Gx8.5 Adjustable	12°, 36°	212271	
35W M.H.	G 12 Adjustable	30°, 42°	212241	
70W M.H.	Gx8.5 Adjustable	12°, 36°	212201	
70W M.H.	G 12 Adjustable	30°, 42°	212211	
150W M.H.	G 12 Adjustable	30°, 42°	212221	

 Walk Over



 EMFA

MIRA 5

RECESSED WALK OVER FIXTURES

Load 2 kN | Class I IP67 IK10

The Mira series consists of a range of LED sources to deliver the desired light effect to facades, columns, bridges, monuments, and signs. The series is made of a die cast aluminium body with electrostatic powder paint finished with a 316L stainless steel cover. The recessed versions are for Walk over up to 20 kN including a stainless steel recessing box. The surface mounted versions come with a heavy-duty 316L stainless steel bracket. The fixtures come with integrated electronic ballasts and a specially developed potted power cable to effectively bond with the cast resin and stop any water ingress. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Cover

316L Stainless steel

Body

Die cast aluminium

Diffusers

12 mm Tempered Glass

Gaskets

Silicone

Screws

316L Stainless Steel

Recessing Box

Steel



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finished of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

MIRA 5

RECESSED WALK OVER FIXTURES


Load 2 kN | Class I IP67 IK10



Led : Power LEDs
Voltage : 240 VAC with integrated driver (12-24 VDC on request)
Diffuser : 12mm Tempered Glass
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F
 Single color LED options upon request are ;
 Blue Amber Green Red




340mm




Power	Kelvin	Real Lumen Output	Lens	Code No
9W	2700 K	855 lm	10°, 25°, 40°	441005
9W	3000 K	855 lm	10°, 25°, 40°	441001
9W	4000 K	872 lm	10°, 25°, 40°	441002
9W	6000 K	890 lm	10°, 25°, 40°	441003
27W	RGB	Red Green Blue	25°, 40°	441004

644mm




Power	Kelvin	Real Lumen Output	Lens	Code No
18W	2700 K	1710 lm	10°, 25°, 40°	441105
18W	3000 K	1710 lm	10°, 25°, 40°	441101
18W	4000 K	1744 lm	10°, 25°, 40°	441102
18W	6000 K	1779 lm	10°, 25°, 40°	441103
54W	RGB	Red Green Blue	25°, 40°	441104

1040mm





Power	Kelvin	Real Lumen Output	Lens	Code No
36W	2700 K	3420 lm	10°, 25°, 40°	441205
36W	3000 K	3420 lm	10°, 25°, 40°	441201
36W	4000 K	3488 lm	10°, 25°, 40°	441202
36W	6000 K	3558 lm	10°, 25°, 40°	441203
81W	RGB	Red Green Blue	25°, 40°	441204

1275mm



Power	Kelvin	Real Lumen Output	Lens	Code No
45W	2700 K	4275 lm	10°, 25°, 40°	441304
45W	3000 K	4275 lm	10°, 25°, 40°	441301
45W	4000 K	4360 lm	10°, 25°, 40°	441302
45W	6000 K	4360 lm	10°, 25°, 40°	441303





MILET ANI

RECESSED WALK OVER FIXTURES

Load 2 kN | Class I IP67 IK10

EMFA's Ani step mounted series is specially designed to deliver low-glare lighting to facades, columns, monuments, and trees with minimal installation depth and narrow trim. The fixture is made of a combination of 316L stainless steel and die cast aluminium. The tilted design reduces the glare of the LED's. The Linear LEDs with special lenses gives excellent wallwashing effect. An anti-slip glass is available upon request.

Cover

316L Stainless steel

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

8 mm Tempered Glass


Screws

316L Stainless Steel




"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, and 2 wattages, and available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



Symmetrical




Galvanized
Recessing Box


LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 100lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Asymmetrical



Asym. Glass




Trenched Glass



Milky Glass




Clear Glass



MILET ANI


RECESSED WALK OVER FIXTURES

Load 2 kN | Class I IP67 IK10





Led : Linear LEDs
Voltage : 240 VAC with integrated driver
 (12-24 VDC on request)
Diffuser : 8mm Tempered Glass
Beam Angle : 45° / 60° / 90°
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F

ANI 1





Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
6W	2700 K	570 lm	451003	451503
6W	3000 K	570 lm	451001	451501
6W	4000 K	690 lm	451002	451502
12W	2700 K	1140 lm	451013	451513
12W	3000 K	1140 lm	451011	451511
12W	4000 K	1195 lm	451012	451512

ANI 2





Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
12W	2700 K	1140 lm	451103	451603
12W	3000 K	1140 lm	451101	451601
12W	4000 K	1254 lm	451102	451602
24W	2700 K	2280 lm	451113	451613
24W	3000 K	2280 lm	451111	451611
24W	4000 K	2320 lm	451112	451612

ANI 3



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
18W	2700 K	1710 lm	451203	451703
18W	3000 K	1710 lm	451201	451701
18W	4000 K	1790 lm	451202	451702
36W	2700 K	3420 lm	451213	451713
36W	3000 K	3420 lm	451211	451711
36W	4000 K	3520 lm	451212	451712

ANI 4



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
24W	2700 K	2280 lm	451321	451821
36W	2700 K	3420 lm	451331	451831
24W	3000 K	2280 lm	451301	451801
36W	3000 K	3420 lm	451311	451811
24W	4000 K	2320 lm	451302	451802
36W	4000 K	3520 lm	451312	451812



Galvanized Recessing Box

ASSOS 6

RECESSED WALK OVER FIXTURES

Class I IP67 IK10

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

EMFA's Assos 6 Alum series is specially designed to light trees and bushes where drive over is not required. The fixture can be equipped with metal halide, halogen or fluorescent lamps. The fixture is made of die cast aluminium and allows for allows for IP67 and IK10. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete. A louvre can be ordered separately to reduce the glare of the lamps. An anti-slip glass is available upon request.

Cover

Die cast aluminium

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Gaskets

Silicone

Diffusers

15 mm Tempered Glass (Aluminium Cover)

Screws

316L Stainless steel


Glands

2 x PG 13.5

Recessing Tube

Polyamide 6

Mounting Features




Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture.

To make the fixture drive over, the recessing tube should be mounted flush to the ground.




HALOGEN



Power	Lampholder	Reflector	Code No Inox
PAR30 75W	E27 Adjustable	38°	211361
RJ 111 50W	G 53	38°	221561

METAL HALIDE



Power	Lampholder	Reflector	Code No Inox
35W M.H.	Gx8.5 Adjustable	12°, 36°	211271
35W M.H.	G 12 Adjustable	30°, 42°	211241
70W M.H.	Gx8.5 Adjustable	12°, 36°	211201
70W M.H.	G 12 Adjustable	30°, 42°	211211
70W M.H.	G 12 Adjustable	30°, 42°	211221

MILET

RECESSED WALK OVER FIXTURES

Load 7.5 kN | IP67 IK10

The Milet Recessed series consists of a range of LED and halogen sources to deliver the desired light effect to facades, columns, bridges, monuments, and trees. The fixtures are made of a combination of a 316L stainless steel cover and die cast aluminium body painted with electrostatic powder paint. Tempered glass, silicone gaskets and cast resin complete the fixture to make it IP67 IK10 and withstand rough environments. For the LED versions, a specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. For the halogen versions, a PG9 cable gland allows for a secure connection of the on-site cable. A polycarbonate recessing box is included for installation into concrete or the ground. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired light effect.

Asymmetric LEDs

In this catalogue EMFA is introducing the tilted LED fixtures. These fixtures give an asymmetrical light output to facades, columns, bridges, monuments, and trees without losing light to the sky. The die cast aluminium body has a fixed built in tilt to allow for proper heat dissipation of the LEDs that can run up to 350mA.

Cover

316L Stainless Steel

Body

Die cast aluminium

Recessing Box

Polycarbonate

Glands

1 x PG 9

Gaskets

Silicone

Diffusers

12 mm Tempered Glass


Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted to the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

AntiSteft Screws



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

MILET

RECESSED WALK OVER FIXTURES

Load 7.5 kN | IP67 IK10



Voltage : 240 VAC with integrated driver
(12-24 VDC on request)

Diffuser : 8mm Tempered Glass (Frosted Glass)


Mac Adam : 3

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Single color LED options upon request are ;
 Blue  Amber  Green  Red

LED




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
4W	2700 K	380 lm	10°, 25°, 40°	425202	425212
4W	3000 K	380 lm	10°, 25°, 40°	425201	425211
4W	4000 K	387 lm	10°, 25°, 40°	425206	425216
4W	6000 K	395 lm	10°, 25°, 40°	425207	425217

HALOGEN



Power	Lampholder	Reflector	Code No	
			Round	Square
35W HALOGEN	Gu5,3 12V	10°, 38°	317111	316111
40W HALOGEN	G 9	10°, 38°	317121	316121
50W HALOGEN	Gu10	10°, 38°	317131	316131

HALOGEN



Power	Lampholder	Reflector	Code No	
			Step	Flush
35W HALOGEN	Gu4 12V	10°, 38°	319101	319201

BIRGI

RECESSED WALK OVER FIXTURES

Class I IP67 IK08

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

EMFA's Birgi series is specially designed to light pathways, roads, and gardens. The fixture can be equipped with LED. The fixture has 3 different options of cover: Multi, Mono, Dual, and Wall to give different lighting effects. In combination with the die cast aluminium body, the fixture allows for IP67 and IK08. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete.

Cover

Die cast aluminium

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Gaskets

Silicone

Diffusers

Tempered press glass or polycarbonate

Screws

316L Stainless steel


Recessing Tube

Aluminium










LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Mounting Feature



Provide at least 30 cm of drainage gravel to avoid the accumulation of water under the fixture. To make the fixture drive over, the recessing tube should be mounted flush to the ground.






Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

BIRGI 1 RECESSED WALK OVER FIXTURES

Class I IP67 IK08

Available in any
of these RAL colors



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Polycarbonate


CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

Mono




Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	471004
1W LED	3000 K	95 lm	471001
1W LED	4000 K	97 lm	471002
1W LED	6000 K	99 lm	471003
3W LED	2700 K	380 lm	471014
3W LED	3000 K	380 lm	471011
3W LED	4000 K	387 lm	471012
3W LED	6000 K	395 lm	471013

Dual



Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	471104
1W LED	3000 K	95 lm	471101
1W LED	4000 K	97 lm	471102
1W LED	6000 K	99 lm	471103
3W LED	2700 K	380 lm	471114
3W LED	3000 K	380 lm	471111
3W LED	4000 K	387 lm	471112
3W LED	6000 K	395 lm	471113

Multi





Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	471204
1W LED	3000 K	95 lm	471201
1W LED	4000 K	97 lm	471202
1W LED	6000 K	99 lm	471203
3W LED	2700 K	380 lm	471214
3W LED	3000 K	380 lm	471211
3W LED	4000 K	387 lm	471212
3W LED	6000 K	395 lm	471213

BIRGI 1 RECESSED WALK OVER FIXTURES

Class I IP67 IK08

Available in any
of these RAL colors



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Polycarbonate


CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

Mono




Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	470004
1W LED	3000 K	95 lm	470001
1W LED	4000 K	97 lm	470002
1W LED	6000 K	99 lm	470003
3W LED	2700 K	380 lm	470014
3W LED	3000 K	380 lm	470011
3W LED	4000 K	387 lm	470012
3W LED	6000 K	395 lm	470013

Dual



Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	470104
1W LED	3000 K	95 lm	470101
1W LED	4000 K	97 lm	470102
1W LED	6000 K	99 lm	470103
3W LED	2700 K	380 lm	470114
3W LED	3000 K	380 lm	470111
3W LED	4000 K	387 lm	470112
3W LED	6000 K	395 lm	470113

Quad






Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	470204
1W LED	3000 K	95 lm	470201
1W LED	4000 K	97 lm	470202
1W LED	6000 K	99 lm	470203
3W LED	2700 K	380 lm	470214
3W LED	3000 K	380 lm	470211
3W LED	4000 K	387 lm	470212
3W LED	6000 K	395 lm	470213

BIRGI 2 RECESSED WALK OVER FIXTURES

Class I IP67 IK08

Available in any
of these RAL colors



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Polycarbonate


CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

Mono





Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	480004
1W LED	3000 K	95 lm	480001
1W LED	4000 K	97 lm	480002
1W LED	6000 K	99 lm	480003
3W LED	2700 K	380 lm	480014
3W LED	3000 K	380 lm	480011
3W LED	4000 K	387 lm	480012
3W LED	6000 K	395 lm	480013

Dual



Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	480104
1W LED	3000 K	95 lm	480101
1W LED	4000 K	97 lm	480102
1W LED	6000 K	99 lm	480103
3W LED	2700 K	380 lm	480114
3W LED	3000 K	380 lm	480111
3W LED	4000 K	387 lm	480112
3W LED	6000 K	395 lm	480113

Multi



Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	480204
1W LED	3000 K	95 lm	480201
1W LED	4000 K	97 lm	480202
1W LED	6000 K	99 lm	480203
3W LED	2700 K	380 lm	480214
3W LED	3000 K	380 lm	480211
3W LED	4000 K	387 lm	480212
3W LED	6000 K	395 lm	480213

BIRGI 3 RECESSED WALK OVER FIXTURES

Class I IP67 IK08

Available in any of these RAL colors

7004


7016

9005

9016



6002

1015





- Voltage** : 240 VAC with integrated driver (12-24 VDC on request)
 - Diffuser** : Polycarbonate
 - CRI** : >80 or >90
 - Cable** : Potted 1m 3x1 H03 VV-F
- Single color LED options upon request are ;
- Blue
Amber
Green
Red

Mono





Power	Kelvin	Real Lumen Output	Code No	
			Round	Square
1W LED	2700 K	1x 95 lm	491004	490004
1W LED	3000 K	1x 95 lm	491001	490001
1W LED	4000 K	1x 97 lm	491002	490002
1W LED	6000 K	1x 99 lm	491003	490003
3W LED	2700 K	1x 380 lm	491014	490014
3W LED	3000 K	1x 380 lm	491011	490011
3W LED	4000 K	1x 387 lm	491012	490012
3W LED	6000 K	1x 395 lm	491013	490013

Dual



Power	Kelvin	Real Lumen Output	Code No	
			Round	Square
2W LED	2700 K	2x 95 lm	491104	490104
2W LED	3000 K	2x 95 lm	491101	490101
2W LED	4000 K	2x 97 lm	491102	490102
2W LED	6000 K	2x 99 lm	491103	490103
6W LED	2700 K	2x 380 lm	491114	490114
6W LED	3000 K	2x 380 lm	491111	490111
6W LED	4000 K	2x 387 lm	491112	490112
6W LED	6000 K	2x 395 lm	491113	490113

Quad



Power	Kelvin	Real Lumen Output	Code No	
			Round	Square
4W LED	2700 K	4x 95 lm	491204	490204
4W LED	3000 K	4x 95 lm	491201	490201
1W LED	4000 K	4x 97 lm	491202	490202
4W LED	6000 K	4x 99 lm	491203	490203
12W LED	2700 K	4x 380 lm	491214	490214
12W LED	3000 K	4x 380 lm	491211	490211
12W LED	4000 K	4x 387 lm	491212	490212
12W LED	6000 K	4x 395 lm	491213	490213

Kaman Adjustable Recessed



403

KAMAN

ADJUSTABLE LED RECESSED FIXTURES IP67 IK10

The Kaman Recessed series consists of a range of LED light sources to deliver the desired light effect to facades, columns, bridges, monuments, and trees. The fixtures are made of a combination of a 316L stainless steel cover and die cast aluminium body painted with electrostatic powder paint. Tempered glass, silicone gaskets and cast resin complete the fixture to make it IP67 IK10 and withstand rough environments. A specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The fixtures come with an aluminium recessing tube for easy mounting in the ground or concrete. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired light effect.

Asymmetrical LEDs

These fixtures give an asymmetrical light output to facades, columns, bridges, monuments, and trees without losing light to the sky. The die cast aluminium body has a fixed built in tilt to allow for proper heat dissipation of the LEDs that can run up to 700mA.

Cover

316L Stainless steel

Body

Die cast aluminium

Recessing Box

Aluminium

Gaskets

Silicone

Diffusers


Tempered Glass

Screws

316L Stainless steel

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.




Adjustable



LEDs


Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.



KAMAN 3

ADJUSTABLE LED RECESSED FIXTURES

IP67 IK10



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)


CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

Fix to Recessing Tube with Silicone





Power	Color	Real Lumen Output	Lens	Code Round	Code No Square
6W LED	2700 K	570 lm	10°,20°30°	240003	240103
6W LED	3000 K	570 lm	10°,20°30°	240001	240101
6W LED	4000 K	580 lm	10°,20°30°	240002	240102
6W LED	6000 K	592 lm	10°,20°30°	240004	240104
11W LED	2700 K	1045 lm	10°,20°30°	240013	240113
11W LED	3000 K	1045 lm	10°,20°30°	240011	240111
11W LED	4000 K	1065 lm	10°,20°30°	240012	240112
11W LED	6000 K	1088 lm	10°,20°30°	240014	240114

Fix to Recessing Tube with Screws



Power	Color	Real Lumen Output	Lens	Code Round	Code No Square
6W LED	2700 K	570 lm	10°,20°30°	241003	241103
6W LED	3000 K	570 lm	10°,20°30°	241001	241101
6W LED	4000 K	580 lm	10°,20°30°	241002	241102
6W LED	6000 K	592 lm	10°,20°30°	241004	241104
11W LED	2700 K	1045 lm	10°,20°30°	241013	241113
11W LED	3000 K	1045 lm	10°,20°30°	241011	241111
11W LED	4000 K	1065 lm	10°,20°30°	241012	241112
11W LED	6000 K	1088 lm	10°,20°30°	241014	241114



Honeycomb
Code No: 953511

BELKIS

RECESSED FIXTURES

IP67 IK10

The Belkis Recessed series consists of a range of LED, fluorescent and halogen sources to deliver the desired light effect to facades, columns, bridges, monuments, and trees. The fixtures are made of a combination of a 316L stainless steel cover and die cast aluminium body painted with electrostatic powder paint. Tempered glass, silicone gaskets and cast resin complete the fixture to make it IP67 IK10 and withstand rough environments. A specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The fixtures come with an aluminium recessing tube for easy mounting in the ground or concrete. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired light effect.

Asymmetrical LEDs

These fixtures give an asymmetrical light output to facades, columns, bridges, monuments, and trees without losing light to the sky. The die cast aluminium body has a fixed built in tilt to allow for proper heat dissipation of the LEDs that can run up to 700mA.

Cover

316L Stainless steel

Body

Die cast aluminium

Recessing Box

Aluminium

Gaskets



Silicone

Diffusers

Tempered Glass

Screws


316L Stainless steel



Honeycomb

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

BELKIS MINI RECESSED WALK OVER FIXTURES

Class I IP67 IK08



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 4 mm (Frosted Glass on request)


CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

Symmetrical





Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	391004
1W LED	3000 K	95 lm	10°, 25°, 40°	391001
1W LED	4000 K	97 lm	10°, 25°, 40°	391002
1W LED	6000 K	99 lm	10°, 25°, 40°	391003
3W LED	2700 K	380 lm	10°, 25°, 40°	391104
3W LED	3000 K	380 lm	10°, 25°, 40°	391101
3W LED	4000 K	387 lm	10°, 25°, 40°	391102
3W LED	6000 K	395 lm	10°, 25°, 40°	391103

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	391201
1W LED	3000 K	95 lm	10°, 25°, 40°	391202
1W LED	4000 K	97 lm	10°, 25°, 40°	391203
1W LED	6000 K	99 lm	10°, 25°, 40°	391204
3W LED	2700 K	380 lm	10°, 25°, 40°	391211
3W LED	3000 K	380 lm	10°, 25°, 40°	391212
3W LED	4000 K	387 lm	10°, 25°, 40°	391213
3W LED	6000 K	395 lm	10°, 25°, 40°	391214

Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	391301
1W LED	3000 K	95 lm	10°, 25°, 40°	391302
1W LED	4000 K	97 lm	10°, 25°, 40°	391303
1W LED	6000 K	99 lm	10°, 25°, 40°	391304
3W LED	2700 K	380 lm	10°, 25°, 40°	391311
3W LED	3000 K	380 lm	10°, 25°, 40°	391312
3W LED	4000 K	387 lm	10°, 25°, 40°	391313
3W LED	6000 K	395 lm	10°, 25°, 40°	391314




Honeycomb
Code No: 953714



BELKIS 1

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red

Fix to Recessing Tube with Silicone

Symmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	425192	425292
1W LED	3000 K	95 lm	10°, 25°, 40°	425191	425291
1W LED	4000 K	97 lm	10°, 25°, 40°	425196	425296
1W LED	6000 K	99 lm	10°, 25°, 40°	425197	425297
3W LED	2700 K	380 lm	10°, 25°, 40°	405504	405514
3W LED	3000 K	380 lm	10°, 25°, 40°	405501	405511
3W LED	4000 K	387 lm	10°, 25°, 40°	405502	405512
3W LED	6000 K	395 lm	10°, 25°, 40°	405503	405513

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	405544	405554
1W LED	3000 K	95 lm	10°, 25°, 40°	405541	405551
1W LED	4000 K	97 lm	10°, 25°, 40°	405542	405552
1W LED	6000 K	99 lm	10°, 25°, 40°	405543	405553
3W LED	2700 K	380 lm	10°, 25°, 40°	405584	405594
3W LED	3000 K	380 lm	10°, 25°, 40°	405581	405591
3W LED	4000 K	387 lm	10°, 25°, 40°	405582	405592
3W LED	6000 K	395 lm	10°, 25°, 40°	405583	405593

Halogen



Power	Lampholder	Reflector	Code No	
			Round	Square
HALOGEN 12V 20W	95 lm	10°-38°	320101	320201




Honeycomb
Code No: 953521

BELKIS 1

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	425182	425282
1W LED	3000 K	95 lm	10°, 25°, 40°	425181	425281
1W LED	4000 K	97 lm	10°, 25°, 40°	425186	425286
1W LED	6000 K	99 lm	10°, 25°, 40°	425187	425287
3W LED	2700 K	380 lm	10°, 25°, 40°	405524	405534
3W LED	3000 K	380 lm	10°, 25°, 40°	405521	405531
3W LED	4000 K	387 lm	10°, 25°, 40°	405522	405532
3W LED	6000 K	395 lm	10°, 25°, 40°	405523	405533

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	405564	405574
1W LED	3000 K	95 lm	10°, 25°, 40°	405561	405571
1W LED	4000 K	97 lm	10°, 25°, 40°	405562	405572
1W LED	6000 K	99 lm	10°, 25°, 40°	405563	405573
3W LED	2700 K	380 lm	10°, 25°, 40°	405604	405614
3W LED	3000 K	380 lm	10°, 25°, 40°	405601	405611
3W LED	4000 K	387 lm	10°, 25°, 40°	405602	405612
3W LED	6000 K	395 lm	10°, 25°, 40°	405603	405613

Halogen



Power	Lampholder	Reflector	Code No	
			Round	Square
HALOGEN 12V 20W	95 lm	10°-38°	320111	320211



Honeycomb
Code No: 953521



BELKIS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	422102	422112
3W LED	3000 K	285 lm	10°, 25°, 40°	422101	422111
3W LED	4000 K	290 lm	10°, 25°, 40°	422106	422116
3W LED	6000 K	296 lm	10°, 25°, 40°	422107	422117
9W LED	2700 K	855 lm	10°, 25°, 40°	418334	418344
9W LED	3000 K	855 lm	10°, 25°, 40°	418331	418341
9W LED	4000 K	872 lm	10°, 25°, 40°	418332	418342
9W LED	6000 K	890 lm	10°, 25°, 40°	418333	418343
9W LED	RGB	Blue, Green, Red	25°, 40°	418371	418381

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	439001	439101
3W LED	3000 K	285 lm	10°, 25°, 40°	439002	439102
3W LED	4000 K	290 lm	10°, 25°, 40°	439003	439103
3W LED	6000 K	296 lm	10°, 25°, 40°	439004	439104
9W LED	2700 K	855 lm	10°, 25°, 40°	439011	439111
9W LED	3000 K	855 lm	10°, 25°, 40°	439012	439112
9W LED	4000 K	872 lm	10°, 25°, 40°	439013	439113
9W LED	6000 K	890 lm	10°, 25°, 40°	439014	439114
9W LED	RGB	Blue, Green, Red	25°, 40°	439015	439115

Wallwasher



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	326004	326014
1W LED	3000 K	95 lm	10°, 25°, 40°	326001	326001
1W LED	4000 K	97 lm	10°, 25°, 40°	326002	326002
1W LED	6000 K	99 lm	10°, 25°, 40°	326003	326003
3W LED	2700 K	285 lm	10°, 25°, 40°	326044	326054
3W LED	3000 K	285 lm	10°, 25°, 40°	326041	326051
3W LED	4000 K	290 lm	10°, 25°, 40°	326042	326052
3W LED	6000 K	296 lm	10°, 25°, 40°	326043	326053




Honeycomb
Code No: 953522

BELKIS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	418394	418404
3W LED	3000 K	285 lm	10°, 25°, 40°	418391	418401
3W LED	4000 K	290 lm	10°, 25°, 40°	418392	418402
3W LED	6000 K	296 lm	10°, 25°, 40°	418393	418403
9W LED	2700 K	855 lm	10°, 25°, 40°	418434	418444
9W LED	3000 K	855 lm	10°, 25°, 40°	418431	418441
9W LED	4000 K	872 lm	10°, 25°, 40°	418432	418442
9W LED	6000 K	890 lm	10°, 25°, 40°	418433	418443
9W LED	RGB	RGB	25°, 40°	418471	418481

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	418514	418524
3W LED	3000 K	285 lm	10°, 25°, 40°	418511	418521
3W LED	4000 K	290 lm	10°, 25°, 40°	418512	418522
3W LED	6000 K	296 lm	10°, 25°, 40°	418513	418523
9W LED	2700 K	855 lm	10°, 25°, 40°	418554	418564
9W LED	3000 K	855 lm	10°, 25°, 40°	418551	418561
9W LED	4000 K	872 lm	10°, 25°, 40°	418552	418562
9W LED	6000 K	890 lm	10°, 25°, 40°	418553	418563
9W LED	RGB	RGB	25°, 40°	418591	418601

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	418634	418644
3W LED	3000 K	285 lm	10°, 25°, 40°	418631	418641
3W LED	4000 K	290 lm	10°, 25°, 40°	418632	418642
3W LED	6000 K	296 lm	10°, 25°, 40°	418633	418643
9W LED	2700 K	855 lm	10°, 25°, 40°	418674	418684
9W LED	3000 K	855 lm	10°, 25°, 40°	418671	418681
9W LED	4000 K	872 lm	10°, 25°, 40°	418672	418682
9W LED	6000 K	890 lm	10°, 25°, 40°	418673	418683
9W LED	RGB	RGB	25°, 40°	418711	418721




Honeycomb
Code No: 953522

BELKIS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	425162	425262
3W LED	3000 K	285 lm	10°, 25°, 40°	425161	425261
3W LED	4000 K	290 lm	10°, 25°, 40°	425166	425266
3W LED	6000 K	296 lm	10°, 25°, 40°	425167	425267
9W LED	2700 K	855 lm	10°, 25°, 40°	418354	418364
9W LED	3000 K	855 lm	10°, 25°, 40°	418351	418361
9W LED	4000 K	872 lm	10°, 25°, 40°	418352	418362
9W LED	6000 K	890 lm	10°, 25°, 40°	418353	418363
9W LED	RGB	RGB	25°, 40°	425411	425421

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	442001	442101
3W LED	3000 K	285 lm	10°, 25°, 40°	442002	442102
3W LED	4000 K	290 lm	10°, 25°, 40°	442003	442103
3W LED	6000 K	296 lm	10°, 25°, 40°	442004	442104
9W LED	2700 K	855 lm	10°, 25°, 40°	442011	442111
9W LED	3000 K	855 lm	10°, 25°, 40°	442012	442112
9W LED	4000 K	872 lm	10°, 25°, 40°	442013	442113
9W LED	6000 K	890 lm	10°, 25°, 40°	442014	442114
9W LED	RGB	RGB	25°, 40°	442015	442115

Wallwasher



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	326024	326034
1W LED	3000 K	95 lm	10°, 25°, 40°	326021	326031
1W LED	4000 K	97 lm	10°, 25°, 40°	326022	326032
1W LED	6000 K	99 lm	10°, 25°, 40°	326023	326033
3W LED	2700 K	285 lm	10°, 25°, 40°	326064	326074
3W LED	3000 K	285 lm	10°, 25°, 40°	326061	326071
3W LED	4000 K	290 lm	10°, 25°, 40°	326062	326072
3W LED	6000 K	296 lm	10°, 25°, 40°	326063	326073



Honeycomb
Code No: 953522

BELKIS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	418414	418424
3W LED	3000 K	285 lm	10°, 25°, 40°	418411	418421
3W LED	4000 K	290 lm	10°, 25°, 40°	418412	418422
3W LED	6000 K	296 lm	10°, 25°, 40°	418413	418423
9W LED	2700 K	855 lm	10°, 25°, 40°	418454	418464
9W LED	3000 K	855 lm	10°, 25°, 40°	418451	418461
9W LED	4000 K	872 lm	10°, 25°, 40°	418452	418462
9W LED	6000 K	890 lm	10°, 25°, 40°	418453	418463
9W LED	RGB	RGB	25°, 40°	418491	418501

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	418534	418544
3W LED	3000 K	285 lm	10°, 25°, 40°	418531	418541
3W LED	4000 K	290 lm	10°, 25°, 40°	418532	418542
3W LED	6000 K	296 lm	10°, 25°, 40°	418533	418543
9W LED	2700 K	855 lm	10°, 25°, 40°	418874	418584
9W LED	3000 K	855 lm	10°, 25°, 40°	418571	418581
9W LED	4000 K	872 lm	10°, 25°, 40°	418572	418582
9W LED	6000 K	890 lm	10°, 25°, 40°	418573	418583
9W LED	RGB	RGB	25°, 40°	418611	418621

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	418654	418664
3W LED	3000 K	285 lm	10°, 25°, 40°	418651	418661
3W LED	4000 K	290 lm	10°, 25°, 40°	418652	418662
3W LED	6000 K	296 lm	10°, 25°, 40°	418653	418663
9W LED	2700 K	855 lm	10°, 25°, 40°	418694	418704
9W LED	3000 K	855 lm	10°, 25°, 40°	418691	418701
9W LED	4000 K	872 lm	10°, 25°, 40°	418692	418702
9W LED	6000 K	890 lm	10°, 25°, 40°	418693	418703
9W LED	RGB	RGB	25°, 40°	418731	418741




Honeycomb
Code No: 953522

BELKIS 2

RECESSED WALK OVER WITH TIR LENS FIXTURES

Class I IP67 IK08



COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)


Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 20°, 30°	119003	119013
6W LED	3000 K	570 lm	10°, 20°, 30°	119001	119011
6W LED	4000 K	581 lm	10°, 20°, 30°	119002	119012
6W LED	6000 K	593 lm	10°, 20°, 30°	119004	119014
11W LED	2700 K	1045 lm	10°, 20°, 30°	119023	119033
11W LED	3000 K	1045 lm	10°, 20°, 30°	119021	119031
11W LED	4000 K	1065 lm	10°, 20°, 30°	119022	119032
11W LED	6000 K	1087 lm	10°, 20°, 30°	119024	119034

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 20°, 30°	122001	122101
6W LED	3000 K	570 lm	10°, 20°, 30°	122002	122102
6W LED	4000 K	581 lm	10°, 20°, 30°	122003	122103
6W LED	6000 K	593 lm	10°, 20°, 30°	122004	122104
11W LED	2700 K	1045 lm	10°, 20°, 30°	122011	122111
11W LED	3000 K	1045 lm	10°, 20°, 30°	122012	122112
11W LED	4000 K	1065 lm	10°, 20°, 30°	122013	122113
11W LED	6000 K	1087 lm	10°, 20°, 30°	122014	122114

Halogen




Power	Lampholder	Reflector	Code No	
			Round	Square
HALOGEN 35W	Gu10	10°, 38°	322101	322201



Honeycomb
Code No: 953522

BELKIS 2 RECESSED WALK OVER WITH TIR LENS FIXTURES

Class I IP67 IK08



COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)



Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Fix to Recessing Tube with Silicone

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	139001	139101
6W LED	3000 K	570 lm	10°, 25°, 40°	139002	139102
6W LED	4000 K	581 lm	10°, 25°, 40°	139003	139104
6W LED	6000 K	593 lm	10°, 25°, 40°	139004	139104
11W LED	2700 K	1045 lm	10°, 25°, 40°	139011	139111
11W LED	3000 K	1045 lm	10°, 25°, 40°	139012	139112
11W LED	4000 K	1065 lm	10°, 25°, 40°	139013	139113
11W LED	6000 K	1087 lm	10°, 25°, 40°	139014	139114

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	119203	119213
6W LED	3000 K	570 lm	10°, 25°, 40°	119201	119211
6W LED	4000 K	581 lm	10°, 25°, 40°	119202	119212
6W LED	6000 K	593 lm	10°, 25°, 40°	119204	119214
11W LED	2700 K	1045 lm	10°, 25°, 40°	119223	119233
11W LED	3000 K	1045 lm	10°, 25°, 40°	119221	119231
11W LED	4000 K	1065 lm	10°, 25°, 40°	119222	119232
11W LED	6000 K	1087 lm	10°, 25°, 40°	119224	119234

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	119403	119413
6W LED	3000 K	570 lm	10°, 25°, 40°	119401	119411
6W LED	4000 K	581 lm	10°, 25°, 40°	119402	119412
6W LED	6000 K	593 lm	10°, 25°, 40°	119404	119414
11W LED	2700 K	1045 lm	10°, 25°, 40°	119423	119433
11W LED	3000 K	1045 lm	10°, 25°, 40°	119421	119431
11W LED	4000 K	1065 lm	10°, 25°, 40°	119422	119432
11W LED	6000 K	1087 lm	10°, 25°, 40°	119424	119434




Honeycomb
Code No: 953522



BELKIS 2

RECESSED WALK OVER WITH TIR LENS FIXTURES

Class I IP67 IK08



COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)


Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 20°, 30°	119003	119013
6W LED	3000 K	570 lm	10°, 20°, 30°	119001	119011
6W LED	4000 K	581 lm	10°, 20°, 30°	119002	119012
6W LED	6000 K	593 lm	10°, 20°, 30°	119004	119014
11W LED	2700 K	1045 lm	10°, 20°, 30°	119023	119033
11W LED	3000 K	1045 lm	10°, 20°, 30°	119021	119031
11W LED	4000 K	1065 lm	10°, 20°, 30°	119022	119032
11W LED	6000 K	1087 lm	10°, 20°, 30°	119024	119034

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 20°, 30°	140001	140101
6W LED	3000 K	570 lm	10°, 20°, 30°	140002	140102
6W LED	4000 K	581 lm	10°, 20°, 30°	140003	140103
6W LED	6000 K	593 lm	10°, 20°, 30°	140004	140104
11W LED	2700 K	1045 lm	10°, 20°, 30°	140011	140111
11W LED	3000 K	1045 lm	10°, 20°, 30°	140012	140112
11W LED	4000 K	1065 lm	10°, 20°, 30°	140013	140113
11W LED	6000 K	1087 lm	10°, 20°, 30°	140014	140114

Halogen



Power	Lampholder	Reflector	Code No	
			Round	Square
HALOGEN 35W	Gu10	10°, 38°	322101	322201



Honeycomb
Code No: 953522

BELKIS 2

RECESSED WALK OVER WITH TIR LENS FIXTURES

Class I IP67 IK08



COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)


Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Fix to Recessing Tube with Screws

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 20°, 30°	141001	141001
6W LED	3000 K	570 lm	10°, 20°, 30°	141002	141102
6W LED	4000 K	581 lm	10°, 20°, 30°	141003	141103
6W LED	6000 K	593 lm	10°, 20°, 30°	141004	141104
11W LED	2700 K	1045 lm	10°, 20°, 30°	141011	141111
11W LED	3000 K	1045 lm	10°, 20°, 30°	141012	141112
11W LED	4000 K	1065 lm	10°, 20°, 30°	141013	141113
11W LED	6000 K	1087 lm	10°, 20°, 30°	141014	141114

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 20°, 30°	119304	119313
6W LED	3000 K	570 lm	10°, 20°, 30°	119301	119311
6W LED	4000 K	581 lm	10°, 20°, 30°	119302	119312
6W LED	6000 K	593 lm	10°, 20°, 30°	119305	119314
11W LED	2700 K	1045 lm	10°, 20°, 30°	119323	119333
11W LED	3000 K	1045 lm	10°, 20°, 30°	119321	119331
11W LED	4000 K	1065 lm	10°, 20°, 30°	119322	119332
11W LED	6000 K	1087 lm	10°, 20°, 30°	119324	119334

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 20°, 30°	119503	119513
6W LED	3000 K	570 lm	10°, 20°, 30°	119501	119511
6W LED	4000 K	581 lm	10°, 20°, 30°	119502	119512
6W LED	6000 K	593 lm	10°, 20°, 30°	119504	119514
11W LED	2700 K	1045 lm	10°, 20°, 30°	119523	119533
11W LED	3000 K	1045 lm	10°, 20°, 30°	119521	119531
11W LED	4000 K	1065 lm	10°, 20°, 30°	119522	119532
11W LED	6000 K	1087 lm	10°, 20°, 30°	119524	119534




Honeycomb
Code No: 953522

BELKIS 3

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	422204	422212
6W LED	3000 K	570 lm	10°, 25°, 40°	422201	422211
6W LED	4000 K	581 lm	10°, 25°, 40°	422202	422216
6W LED	6000 K	593 lm	10°, 25°, 40°	422203	422217
18W LED	RGB	Red Green Blue	25°, 40°	422261	422271

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	326104	326114
6W LED	3000 K	570 lm	10°, 25°, 40°	326101	326111
6W LED	4000 K	581 lm	10°, 25°, 40°	326102	326112
6W LED	6000 K	593 lm	10°, 25°, 40°	326103	326113
18W LED	RGB	Red Green Blue	25°, 40°	326141	326151

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	423104	423114
6W LED	3000 K	570 lm	10°, 25°, 40°	423101	423111
6W LED	4000 K	581 lm	10°, 25°, 40°	423102	423112
6W LED	6000 K	593 lm	10°, 25°, 40°	423103	423113
18W LED	RGB	Red Green Blue	25°, 40°	423141	423151

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	423184	423194
6W LED	3000 K	570 lm	10°, 25°, 40°	423181	423191
6W LED	4000 K	581 lm	10°, 25°, 40°	423182	423192
6W LED	6000 K	593 lm	10°, 25°, 40°	423183	423193
18W LED	RGB	Red Green Blue	25°, 40°	423221	423231




Honeycomb
Code No: 953523



BELKIS 3

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	422222	422232
6W LED	3000 K	570 lm	10°, 25°, 40°	422221	422231
6W LED	4000 K	581 lm	10°, 25°, 40°	422226	422236
6W LED	6000 K	593 lm	10°, 25°, 40°	422227	422237
18W LED	RGB	Red Green Blue	25°, 40°	422251	422251

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	326124	326134
6W LED	3000 K	570 lm	10°, 25°, 40°	326121	326131
6W LED	4000 K	581 lm	10°, 25°, 40°	326122	326132
6W LED	6000 K	593 lm	10°, 25°, 40°	326123	326133
18W LED	RGB	Red Green Blue	25°, 40°	326401	326411

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	423124	423134
6W LED	3000 K	570 lm	10°, 25°, 40°	423121	423131
6W LED	4000 K	581 lm	10°, 25°, 40°	423122	423132
6W LED	6000 K	593 lm	10°, 25°, 40°	423123	423133
18W LED	RGB	Red Green Blue	25°, 40°	423161	423171

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	423204	423214
6W LED	3000 K	570 lm	10°, 25°, 40°	423201	423211
6W LED	4000 K	581 lm	10°, 25°, 40°	423202	423212
6W LED	6000 K	593 lm	10°, 25°, 40°	423203	423213
18W LED	RGB	Red Green Blue	25°, 40°	423241	423251



Honeycomb
Code No: 953523

BELKIS 3 RECESSED WALK OVER WITH TIR LENS FIXTURES

Class I IP67 IK08



COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)


Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	1045 lm	10°, 20°, 30°	119603	119613
6W LED	3000 K	1045 lm	10°, 20°, 30°	119601	119611
6W LED	4000 K	1065 lm	10°, 20°, 30°	119602	119612
6W LED	6000 K	1087 lm	10°, 20°, 30°	119604	119614

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
11W LED	2700 K	1045 lm	10°, 20°, 30°	120801	120811
11W LED	3000 K	1045 lm	10°, 20°, 30°	120802	120812
11W LED	4000 K	1065 lm	10°, 20°, 30°	120803	120813
11W LED	6000 K	1087 lm	10°, 20°, 30°	120804	120814

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
11W LED	2700 K	1045 lm	10°, 20°, 30°	119803	119813
11W LED	3000 K	1045 lm	10°, 20°, 30°	119801	119811
11W LED	4000 K	1065 lm	10°, 20°, 30°	119802	119812
11W LED	6000 K	1087 lm	10°, 20°, 30°	119804	119814

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
11W LED	2700 K	1045 lm	10°, 20°, 30°	120003	120013
11W LED	3000 K	1045 lm	10°, 20°, 30°	120001	120011
11W LED	4000 K	1065 lm	10°, 20°, 30°	120002	120012
11W LED	6000 K	1087 lm	10°, 20°, 30°	120004	120014



Honeycomb
Code No: 953523

BELKIS 3 RECESSED WALK OVER WITH TIR LENS FIXTURES

Class I IP67 IK08



COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)


Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
11W LED	2700 K	1045 lm	10°, 20°, 30°	119703	119713
11W LED	3000 K	1045 lm	10°, 20°, 30°	119701	119711
11W LED	4000 K	1065 lm	10°, 20°, 30°	119702	119712
11W LED	6000 K	1087 lm	10°, 20°, 30°	119704	119714

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
11W LED	2700 K	1045 lm	10°, 20°, 30°	120901	120911
11W LED	3000 K	1045 lm	10°, 20°, 30°	120902	120912
11W LED	4000 K	1065 lm	10°, 20°, 30°	120903	120913
11W LED	6000 K	1087 lm	10°, 20°, 30°	120904	120914

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
11W LED	2700 K	1045 lm	10°, 20°, 30°	119903	119913
11W LED	3000 K	1045 lm	10°, 20°, 30°	119901	119911
11W LED	4000 K	1065 lm	10°, 20°, 30°	119902	119912
11W LED	6000 K	1087 lm	10°, 20°, 30°	119904	119914

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
11W LED	2700 K	1045 lm	10°, 20°, 30°	121003	121013
11W LED	3000 K	1045 lm	10°, 20°, 30°	121001	121011
11W LED	4000 K	1065 lm	10°, 20°, 30°	121002	121012
11W LED	6000 K	1087 lm	10°, 20°, 30°	121004	121014




Honeycomb
Code No: 953523



BELKIS 4

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	422302	422312
9W LED	3000 K	855 lm	10°, 25°, 40°	422301	422311
9W LED	4000 K	872 lm	10°, 25°, 40°	422306	422316
9W LED	6000 K	890 lm	10°, 25°, 40°	422307	422317

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	326204	326214
9W LED	3000 K	855 lm	10°, 25°, 40°	326201	326211
9W LED	4000 K	872 lm	10°, 25°, 40°	326202	326212
9W LED	6000 K	890 lm	10°, 25°, 40°	326203	326213

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
18W COB LED	2700 K	1710 lm	10°, 20°, 30°	120203	120213
18W COB LED	3000 K	1710 lm	10°, 20°, 30°	120201	120211
18W COB LED	4000 K	1744 lm	10°, 20°, 30°	120202	120212
18W COB LED	6000 K	1779 lm	10°, 20°, 30°	120204	120214

Symmetrical Deep



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
13W COB LED	2700 K	1235 lm	24°, 38°	326303	326313
13W COB LED	3000 K	1235 lm	24°, 38°	326301	326311
13W COB LED	4000 K	1259 lm	24°, 38°	326302	326312
13W COB LED	6000 K	1259 lm	24°, 38°	326304	326314




Honeycomb
Code No: 953524

BELKIS 4

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	422322	422332
9W LED	3000 K	855 lm	10°, 25°, 40°	422321	422331
9W LED	4000 K	872 lm	10°, 25°, 40°	422326	422336
9W LED	6000 K	890 lm	10°, 25°, 40°	422327	422337

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	326224	326234
9W LED	3000 K	855 lm	10°, 25°, 40°	326221	326231
9W LED	4000 K	872 lm	10°, 25°, 40°	326222	326232
9W LED	6000 K	890 lm	10°, 25°, 40°	326223	326233

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
18W COB LED	2700 K	1710 lm	10°, 20°, 30°	120303	120313
18W COB LED	3000 K	1710 lm	10°, 20°, 30°	120301	120311
18W COB LED	4000 K	1744 lm	10°, 20°, 30°	120302	120312
18W COB LED	6000 K	1779 lm	10°, 20°, 30°	120304	120314

Symmetrical Deep



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
13W COB LED	2700 K	1235 lm	24°, 38°	326323	326333
13W COB LED	3000 K	1235 lm	24°, 38°	326321	326331
13W COB LED	4000 K	1259 lm	24°, 38°	326322	326332
13W COB LED	6000 K	1259 lm	24°, 38°	326324	326334



Honeycomb
Code No: 953524

BELKIS 5

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	423704	423314
27W LED	3000 K	2560 lm	10°, 25°, 40°	423301	423311
27W LED	4000 K	2610 lm	10°, 25°, 40°	423302	423312
27W LED	6000 K	2670 lm	10°, 25°, 40°	423303	423313
27W LED	RGB		25°, 40°	423341	423351

Symmetrical Halogen




Power	Lampholder	Reflector	Code No	
			Round	Square
PAR30 75W HALOGEN	E27	10°, 38°	324111	324211

Wallwasher




Power	Kelvin	Real Lumen Output	Reflector	Code No	
				Round	Square
13W COB LED	2700 K	1235 lm	Asymmetrical	423704	423714
13W COB LED	3000 K	1235 lm	Asymmetrical	423701	423711
13W COB LED	4000 K	1259 lm	Asymmetrical	423702	423712
13W COB LED	6000 K	1284 lm	Asymmetrical	723703	423713

60° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	24°, 38°	423564	423574
6W LED	3000 K	570 lm	24°, 38°	423561	423571
6W LED	4000 K	581 lm	24°, 38°	423562	423572
6W LED	6000 K	593 lm	24°, 38°	423563	423573



Honeycomb
Code No: 953525

BELKIS 5

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Round	Code No Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	423604	423614
27W LED	3000 K	2560 lm	10°, 25°, 40°	423601	423611
27W LED	4000 K	2610 lm	10°, 25°, 40°	423602	423612
27W LED	6000 K	2670 lm	10°, 25°, 40°	423603	423613
27W LED	RGB		25°, 40°	423401	423411

25° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Round	Code No Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	423644	423654
27W LED	3000 K	2560 lm	10°, 25°, 40°	423641	423651
27W LED	4000 K	2610 lm	10°, 25°, 40°	423642	423652
27W LED	6000 K	2670 lm	10°, 25°, 40°	423643	423653
27W LED	RGB		25°, 40°	423481	423491

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Round	Code No Square
25W COB LED	2700 K	2375 lm	10°, 20°, 30°	120403	120413
25W COB LED	3000 K	2375 lm	10°, 20°, 30°	120401	120411
25W COB LED	4000 K	2422 lm	10°, 20°, 30°	120402	120412
25W COB LED	6000 K	2470 lm	10°, 20°, 30°	120404	120414

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No Round	Code No Square
25W COB LED	2700 K	2375 lm	10°, 20°, 30°	120603	120613
25W COB LED	3000 K	2375 lm	10°, 20°, 30°	120601	120611
25W COB LED	4000 K	2422 lm	10°, 20°, 30°	120602	120612
25W COB LED	6000 K	2470 lm	10°, 20°, 30°	120604	120614



Honeycomb
Code No: 953525

BELKIS 5

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	423324	423334
27W LED	3000 K	2560 lm	10°, 25°, 40°	423321	423331
27W LED	4000 K	2610 lm	10°, 25°, 40°	423322	423332
27W LED	6000 K	2670 lm	10°, 25°, 40°	423323	423333
27W LED	RGB		25°, 40°	422381	422491

Symmetrical Halogen




Power	Lampholder	Reflector	Code No	
			Round	Square
PAR30 75W HALOGEN	E27	10°, 38°	324121	324221

Wallwasher




Power	Kelvin	Real Lumen Output	Reflector	Code No	
				Round	Square
13W COB LED	2700 K	1235 lm	Asymmetrical	423724	423734
13W COB LED	3000 K	1235 lm	Asymmetrical	423721	423731
13W COB LED	4000 K	1259 lm	Asymmetrical	423722	423732
13W COB LED	6000 K	1284 lm	Asymmetrical	723723	423733

60° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	24°, 38°	423584	423594
6W LED	3000 K	570 lm	24°, 38°	423581	423591
6W LED	4000 K	581 lm	24°, 38°	423582	423592
6W LED	6000 K	593 lm	24°, 38°	423583	423593



Honeycomb
Code No: 953525

BELKIS 5

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	423624	423634
27W LED	3000 K	2560 lm	10°, 25°, 40°	423621	423631
27W LED	4000 K	2610 lm	10°, 25°, 40°	423622	423632
27W LED	6000 K	2670 lm	10°, 25°, 40°	423623	423633
27W LED	RGB	Blue, Amber, Green, Red	25°, 40°	423421	423431

25° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	423664	423674
27W LED	3000 K	2560 lm	10°, 25°, 40°	423661	423671
27W LED	4000 K	2610 lm	10°, 25°, 40°	423662	423672
27W LED	6000 K	2670 lm	10°, 25°, 40°	423663	423673
27W LED	RGB	Blue, Amber, Green, Red	25°, 40°	423501	423511

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
25W COB LED	2700 K	2375 lm	10°, 20°, 30°	120503	120513
25W COB LED	3000 K	2375 lm	10°, 20°, 30°	120501	120511
25W COB LED	4000 K	2422 lm	10°, 20°, 30°	120502	120512
25W COB LED	6000 K	2470 lm	10°, 20°, 30°	120504	120514

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
25W COB LED	2700 K	2375 lm	10°, 20°, 30°	120703	120713
25W COB LED	3000 K	2375 lm	10°, 20°, 30°	120701	120711
25W COB LED	4000 K	2422 lm	10°, 20°, 30°	120702	120712
25W COB LED	6000 K	2470 lm	10°, 20°, 30°	120704	120714



Honeycomb
Code No: 953525



PATNOS

RECESSED FIXTURES IP67 IK10

The Patnos series is an adaption of the Belkis Recessed series using less or no visible screws. No screws are visible on the cover if silicone is used to glue the fixture to the recessing tube. The series is designed to light walls, facades, columns, monuments, and trees. The fixtures are made of a combination of a 316L stainless steel cover and die cast aluminium body painted with electrostatic powder paint. Tempered glass, silicone gaskets and cast resin complete the fixture to make it IP67 IK10 and withstand rough environments. A specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The fixtures come with an aluminium recessing tube for easy mounting in the ground or concrete. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired light effect.

Asymmetrical LEDs

In this catalogue EMFA is introducing the tilted LED fixtures. These fixtures give an asymmetrical light output to facades, columns, bridges, monuments, and trees without losing light to the sky. The die cast aluminium body has a fixed built in tilt to allow for proper heat dissipation of the LEDs that can run up to 700mA.

Cover

316L Stainless steel

Body

Die cast aluminium

Recessing Box

Aluminium

Gaskets


Silicone

Diffusers

Tempered Glass

Screws

316L Stainless steel




Symmetrical

Symmetrical Deep

15° Asymmetrical


25° Asymmetrical



Honeycomb

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

PATNOS 1

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	160004	160014
1W LED	3000 K	95 lm	10°, 25°, 40°	160001	160011
1W LED	4000 K	97 lm	10°, 25°, 40°	160002	160012
1W LED	6000 K	99 lm	10°, 25°, 40°	160003	160013
3W LED	2700 K	380 lm	10°, 25°, 40°	160044	160054
3W LED	3000 K	380 lm	10°, 25°, 40°	160041	160051
3W LED	4000 K	387 lm	10°, 25°, 40°	160042	160052
3W LED	6000 K	395 lm	10°, 25°, 40°	160043	160053

7° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	160204	160214
1W LED	3000 K	95 lm	10°, 25°, 40°	160201	160211
1W LED	4000 K	97 lm	10°, 25°, 40°	160202	160212
1W LED	6000 K	99 lm	10°, 25°, 40°	160203	160213
3W LED	2700 K	380 lm	10°, 25°, 40°	160244	160254
3W LED	3000 K	380 lm	10°, 25°, 40°	160241	160251
3W LED	4000 K	387 lm	10°, 25°, 40°	160242	160252
3W LED	6000 K	395 lm	10°, 25°, 40°	160243	160253




Honeycomb
Code No: 953521

PATNOS 1

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	160024	160034
1W LED	3000 K	95 lm	10°, 25°, 40°	160021	160031
1W LED	4000 K	97 lm	10°, 25°, 40°	160022	160032
1W LED	6000 K	99 lm	10°, 25°, 40°	160023	160033
3W LED	2700 K	380 lm	10°, 25°, 40°	160064	160074
3W LED	3000 K	380 lm	10°, 25°, 40°	160061	160071
3W LED	4000 K	387 lm	10°, 25°, 40°	160062	160072
3W LED	6000 K	395 lm	10°, 25°, 40°	160063	160073

7° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	160224	160234
1W LED	3000 K	95 lm	10°, 25°, 40°	160221	160231
1W LED	4000 K	97 lm	10°, 25°, 40°	160222	160232
1W LED	6000 K	99 lm	10°, 25°, 40°	160223	160233
3W LED	2700 K	380 lm	10°, 25°, 40°	160264	160274
3W LED	3000 K	380 lm	10°, 25°, 40°	160261	160271
3W LED	4000 K	387 lm	10°, 25°, 40°	160262	160272
3W LED	6000 K	395 lm	10°, 25°, 40°	160263	160273




Honeycomb
Code No: 953521

PATNOS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161004	161014
3W LED	3000 K	285 lm	10°, 25°, 40°	161001	161011
3W LED	4000 K	290 lm	10°, 25°, 40°	161002	161012
3W LED	6000 K	296 lm	10°, 25°, 40°	161003	161013
9W LED	2700 K	855 lm	10°, 25°, 40°	161044	161054
9W LED	3000 K	855 lm	10°, 25°, 40°	161041	161051
9W LED	4000 K	872 lm	10°, 25°, 40°	161042	161052
9W LED	6000 K	890 lm	10°, 25°, 40°	161043	161053
9W LED	RGB	RGB	25°, 40°	161081	161091

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	165001	165101
3W LED	3000 K	285 lm	10°, 25°, 40°	165002	165102
3W LED	4000 K	290 lm	10°, 25°, 40°	165003	165103
3W LED	6000 K	296 lm	10°, 25°, 40°	165004	165104
9W LED	2700 K	855 lm	10°, 25°, 40°	165011	165111
9W LED	3000 K	855 lm	10°, 25°, 40°	165012	165112
9W LED	4000 K	872 lm	10°, 25°, 40°	165013	165113
9W LED	6000 K	890 lm	10°, 25°, 40°	165014	165114
9W LED	RGB	RGB	25°, 40°	165015	165115

Wallwasher



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	161604	161614
1W LED	3000 K	95 lm	10°, 25°, 40°	161001	161611
1W LED	4000 K	97 lm	10°, 25°, 40°	161602	161612
1W LED	6000 K	99 lm	10°, 25°, 40°	161603	161613
3W LED	2700 K	285 lm	10°, 25°, 40°	161644	161654
3W LED	3000 K	285 lm	10°, 25°, 40°	161641	161651
3W LED	4000 K	290 lm	10°, 25°, 40°	161642	161652
3W LED	6000 K	296 lm	10°, 25°, 40°	161643	161653




Honeycomb
Code No: 953522



PATNOS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161204	161214
3W LED	3000 K	285 lm	10°, 25°, 40°	161201	161211
3W LED	4000 K	290 lm	10°, 25°, 40°	161202	161212
3W LED	6000 K	296 lm	10°, 25°, 40°	161203	161213
9W LED	2700 K	855 lm	10°, 25°, 40°	161244	161254
9W LED	3000 K	855 lm	10°, 25°, 40°	161241	161251
9W LED	4000 K	872 lm	10°, 25°, 40°	161242	161252
9W LED	6000 K	890 lm	10°, 25°, 40°	161243	161253
9W LED	RGB	RGB	25°, 40°	161281	161291

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161324	161334
3W LED	3000 K	285 lm	10°, 25°, 40°	161321	161331
3W LED	4000 K	290 lm	10°, 25°, 40°	161322	161332
3W LED	6000 K	296 lm	10°, 25°, 40°	161323	161333
9W LED	2700 K	855 lm	10°, 25°, 40°	161364	161374
9W LED	3000 K	855 lm	10°, 25°, 40°	161361	161371
9W LED	4000 K	872 lm	10°, 25°, 40°	161362	161372
9W LED	6000 K	890 lm	10°, 25°, 40°	161363	161373
9W LED	RGB	RGB	25°, 40°	161401	161411

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161444	161454
3W LED	3000 K	285 lm	10°, 25°, 40°	161441	161451
3W LED	4000 K	290 lm	10°, 25°, 40°	161442	161452
3W LED	6000 K	296 lm	10°, 25°, 40°	161443	161453
9W LED	2700 K	855 lm	10°, 25°, 40°	161484	161494
9W LED	3000 K	855 lm	10°, 25°, 40°	161481	161491
9W LED	4000 K	872 lm	10°, 25°, 40°	161482	161492
9W LED	6000 K	890 lm	10°, 25°, 40°	161483	161493
9W LED	RGB	RGB	25°, 40°	161521	161531



Honeycomb
Code No: 953522

PATNOS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161024	161034
3W LED	3000 K	285 lm	10°, 25°, 40°	161021	161031
3W LED	4000 K	290 lm	10°, 25°, 40°	161022	161032
3W LED	6000 K	296 lm	10°, 25°, 40°	161023	161033
9W LED	2700 K	855 lm	10°, 25°, 40°	161064	161074
9W LED	3000 K	855 lm	10°, 25°, 40°	161061	161071
9W LED	4000 K	872 lm	10°, 25°, 40°	161062	161072
9W LED	6000 K	890 lm	10°, 25°, 40°	161063	161073
9W LED	RGB	RGB	25°, 40°	161101	161111

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161701	161801
3W LED	3000 K	285 lm	10°, 25°, 40°	161702	161802
3W LED	4000 K	290 lm	10°, 25°, 40°	161703	161803
3W LED	6000 K	296 lm	10°, 25°, 40°	161704	161804
9W LED	2700 K	855 lm	10°, 25°, 40°	161711	161811
9W LED	3000 K	855 lm	10°, 25°, 40°	161712	161812
9W LED	4000 K	872 lm	10°, 25°, 40°	161713	161813
9W LED	6000 K	890 lm	10°, 25°, 40°	161714	161814
9W LED	RGB	RGB	25°, 40°	161715	161815

Wallwasher



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	161624	161634
1W LED	3000 K	95 lm	10°, 25°, 40°	161621	161631
1W LED	4000 K	97 lm	10°, 25°, 40°	161622	161632
1W LED	6000 K	99 lm	10°, 25°, 40°	161623	161633
3W LED	2700 K	285 lm	10°, 25°, 40°	161664	161674
3W LED	3000 K	285 lm	10°, 25°, 40°	161661	161671
3W LED	4000 K	290 lm	10°, 25°, 40°	161662	161672
3W LED	6000 K	296 lm	10°, 25°, 40°	161663	161673




Honeycomb
Code No: 953522

PATNOS 2

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161224	161234
3W LED	3000 K	285 lm	10°, 25°, 40°	161221	161231
3W LED	4000 K	290 lm	10°, 25°, 40°	161222	161232
3W LED	6000 K	296 lm	10°, 25°, 40°	161223	161233
9W LED	2700 K	855 lm	10°, 25°, 40°	161264	161274
9W LED	3000 K	855 lm	10°, 25°, 40°	161261	161271
9W LED	4000 K	872 lm	10°, 25°, 40°	161262	161272
9W LED	6000 K	890 lm	10°, 25°, 40°	161263	161273
9W LED	RGB	RGB	25°, 40°	161301	161311

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161344	161654
3W LED	3000 K	285 lm	10°, 25°, 40°	161341	161351
3W LED	4000 K	290 lm	10°, 25°, 40°	161342	161352
3W LED	6000 K	296 lm	10°, 25°, 40°	161343	161353
9W LED	2700 K	855 lm	10°, 25°, 40°	161384	161394
9W LED	3000 K	855 lm	10°, 25°, 40°	161381	161391
9W LED	4000 K	872 lm	10°, 25°, 40°	161382	161392
9W LED	6000 K	890 lm	10°, 25°, 40°	161383	161393
9W LED	RGB	RGB	25°, 40°	161421	161431

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	161464	161474
3W LED	3000 K	285 lm	10°, 25°, 40°	161461	161471
3W LED	4000 K	290 lm	10°, 25°, 40°	161462	161472
3W LED	6000 K	296 lm	10°, 25°, 40°	161463	161473
9W LED	2700 K	855 lm	10°, 25°, 40°	161504	161514
9W LED	3000 K	855 lm	10°, 25°, 40°	161501	161511
9W LED	4000 K	872 lm	10°, 25°, 40°	161502	161512
9W LED	6000 K	890 lm	10°, 25°, 40°	161503	161513
9W LED	RGB	RGB	25°, 40°	161541	161551



Honeycomb
Code No: 953522



PATNOS 3

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162004	162014
6W LED	3000 K	570 lm	10°, 25°, 40°	162001	162011
6W LED	4000 K	581 lm	10°, 25°, 40°	162002	162012
6W LED	6000 K	593 lm	10°, 25°, 40°	162003	162013
18W LED	RGB	Red Green Blue	25°, 40°	162041	162051

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162404	162414
6W LED	3000 K	570 lm	10°, 25°, 40°	162401	162411
6W LED	4000 K	581 lm	10°, 25°, 40°	162402	162412
6W LED	6000 K	593 lm	10°, 25°, 40°	162403	162413
18W LED	RGB	Red Green Blue	25°, 40°	162501	162511

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162204	162214
6W LED	3000 K	570 lm	10°, 25°, 40°	162201	162211
6W LED	4000 K	581 lm	10°, 25°, 40°	162202	162212
6W LED	6000 K	593 lm	10°, 25°, 40°	162203	162213
18W LED	RGB	Red Green Blue	25°, 40°	162241	162251

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162284	162294
6W LED	3000 K	570 lm	10°, 25°, 40°	162281	162291
6W LED	4000 K	581 lm	10°, 25°, 40°	162282	162292
6W LED	6000 K	593 lm	10°, 25°, 40°	162283	162293
18W LED	RGB	Red Green Blue	25°, 40°	162321	162331



Honeycomb
Code No: 953523

PATNOS 3

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162024	162034
6W LED	3000 K	570 lm	10°, 25°, 40°	162021	162031
6W LED	4000 K	581 lm	10°, 25°, 40°	162022	162032
6W LED	6000 K	593 lm	10°, 25°, 40°	162023	162033
18W LED	RGB	Red Green Blue	25°, 40°	162061	162071

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162424	162434
6W LED	3000 K	570 lm	10°, 25°, 40°	162421	162431
6W LED	4000 K	581 lm	10°, 25°, 40°	162422	162432
6W LED	6000 K	593 lm	10°, 25°, 40°	162423	162433
18W LED	RGB	Red Green Blue	25°, 40°	162601	162611

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162224	162234
6W LED	3000 K	570 lm	10°, 25°, 40°	162221	162231
6W LED	4000 K	581 lm	10°, 25°, 40°	162222	162232
6W LED	6000 K	593 lm	10°, 25°, 40°	162223	162233
18W LED	RGB	Red Green Blue	25°, 40°	162261	162271

25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
6W LED	2700 K	570 lm	10°, 25°, 40°	162304	162314
6W LED	3000 K	570 lm	10°, 25°, 40°	162301	162311
6W LED	4000 K	581 lm	10°, 25°, 40°	162302	162312
6W LED	6000 K	593 lm	10°, 25°, 40°	162303	162313
18W LED	RGB	Red Green Blue	25°, 40°	162341	162351




Honeycomb
Code No: 953523



PATNOS 4

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	163004	163014
9W LED	3000 K	855 lm	10°, 25°, 40°	163001	163011
9W LED	4000 K	872 lm	10°, 25°, 40°	163002	163012
9W LED	6000 K	890 lm	10°, 25°, 40°	163003	163013

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	163104	163114
9W LED	3000 K	855 lm	10°, 25°, 40°	163101	163111
9W LED	4000 K	872 lm	10°, 25°, 40°	163102	163112
9W LED	6000 K	890 lm	10°, 25°, 40°	163103	163113

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
18W COB LED	2700 K	1710 lm	10°, 20°, 30°	163201	163211
18W COB LED	3000 K	1710 lm	10°, 20°, 30°	163202	163212
18W COB LED	4000 K	1744 lm	10°, 20°, 30°	163203	163213
18W COB LED	6000 K	1779 lm	10°, 20°, 30°	163204	163214

Symmetrical Deep



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
13W COB LED	2700 K	1235 lm	24°, 38°	163143	163153
13W COB LED	3000 K	1235 lm	24°, 38°	163141	163151
13W COB LED	4000 K	1259 lm	24°, 38°	163142	163152
13W COB LED	6000 K	1259 lm	24°, 38°	163144	163154




Honeycomb
Code No: 953524

PATNOS 4

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED or COB LED

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	163024	163034
9W LED	3000 K	855 lm	10°, 25°, 40°	163021	163031
9W LED	4000 K	872 lm	10°, 25°, 40°	163022	163032
9W LED	6000 K	890 lm	10°, 25°, 40°	163023	163033

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	163124	163134
9W LED	3000 K	855 lm	10°, 25°, 40°	163121	163131
9W LED	4000 K	872 lm	10°, 25°, 40°	163122	163132
9W LED	6000 K	890 lm	10°, 25°, 40°	163123	163133

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
18W COB LED	2700 K	1710 lm	10°, 20°, 30°	163301	163311
18W COB LED	3000 K	1710 lm	10°, 20°, 30°	163302	163312
18W COB LED	4000 K	1744 lm	10°, 20°, 30°	163303	163313
18W COB LED	6000 K	1779 lm	10°, 20°, 30°	163304	163314

Symmetrical Deep



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
13W COB LED	2700 K	1235 lm	24°, 38°	163163	163173
13W COB LED	3000 K	1235 lm	24°, 38°	163161	163171
13W COB LED	4000 K	1259 lm	24°, 38°	163162	163172
13W COB LED	6000 K	1259 lm	24°, 38°	163164	163174




Honeycomb
Code No: 953524



PATNOS 5

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Silicone

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Round	Code No Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	164044	164054
27W LED	3000 K	2560 lm	10°, 25°, 40°	164041	164051
27W LED	4000 K	2610 lm	10°, 25°, 40°	164042	164052
27W LED	6000 K	2670 lm	10°, 25°, 40°	164043	164053
27W LED	RGB		25°, 40°	164081	164091

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Round	Code No Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	164704	164714
27W LED	3000 K	2560 lm	10°, 25°, 40°	164701	164711
27W LED	4000 K	2610 lm	10°, 25°, 40°	164702	164712
27W LED	6000 K	2670 lm	10°, 25°, 40°	164703	164713
27W LED	RGB		25°, 40°	164241	164251

25° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Round	Code No Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	164744	164754
27W LED	3000 K	2560 lm	10°, 25°, 40°	164741	164751
27W LED	4000 K	2610 lm	10°, 25°, 40°	164742	164752
27W LED	6000 K	2670 lm	10°, 25°, 40°	164743	164753
27W LED	RGB		25°, 40°	164321	164331

Wallwasher



Power	Kelvin	Real Lumen Output	Reflector	Code No Round	Code No Square
13W COB LED	2700 K	1235 lm	Asymmetrical	164804	164814
13W COB LED	3000 K	1235 lm	Asymmetrical	164801	164811
13W COB LED	4000 K	1259 lm	Asymmetrical	164802	164812
13W COB LED	6000 K	1284 lm	Asymmetrical	164803	164813




Honeycomb
Code No: 953525

PATNOS 5

RECESSED WALK OVER FIXTURES

Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red


Fix to Recessing Tube with Screws

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	164064	164074
27W LED	3000 K	2560 lm	10°, 25°, 40°	164061	164071
27W LED	4000 K	2610 lm	10°, 25°, 40°	164062	164072
27W LED	6000 K	2670 lm	10°, 25°, 40°	164063	164073
27W LED	RGB	Blue, Amber, Green, Red	25°, 40°	164101	164111

15° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	164724	164734
27W LED	3000 K	2560 lm	10°, 25°, 40°	164721	164731
27W LED	4000 K	2610 lm	10°, 25°, 40°	164722	164732
27W LED	6000 K	2670 lm	10°, 25°, 40°	164723	164733
27W LED	RGB	Blue, Amber, Green, Red	25°, 40°	164261	164271

25° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
27W LED	2700 K	2560 lm	10°, 25°, 40°	164764	164774
27W LED	3000 K	2560 lm	10°, 25°, 40°	164761	164771
27W LED	4000 K	2610 lm	10°, 25°, 40°	164762	164772
27W LED	6000 K	2670 lm	10°, 25°, 40°	164763	164773
27W LED	RGB	Blue, Amber, Green, Red	25°, 40°	164341	164351

Wallwasher



Power	Kelvin	Real Lumen Output	Reflector	Code No	
				Round	Square
13W COB LED	2700 K	1235 lm	Asymmetrical	164824	164834
13W COB LED	3000 K	1235 lm	Asymmetrical	164821	164831
13W COB LED	4000 K	1259 lm	Asymmetrical	164822	164832
13W COB LED	6000 K	1284 lm	Asymmetrical	164823	164833



Honeycomb
Code No: 953525

GORDION

RECESSED LED FIXTURES

Load 5 kN | Class I IP67 IK08

The Gordion series is an adaption of the Belkis Recessed series without the stainless steel cover. Merely a painted glass finishes the look of the fixture. Once placed inside the stainless steel tube, the fixture can only be removed with a special tool. The Gordion series is designed to light walls, facades, columns, monuments, and trees. The fixtures are made of die cast aluminium body painted with electrostatic powder paint. Tempered glass, silicone gaskets and cast resin complete the fixture to make it IP67 IK10 and withstand rough environments. A specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired light effect.

Body

Die cast aluminium

Recessing Tube

316L Stainless steel

Gaskets

Silicone



Diffusers

Tempered Glass with painted circumference



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



Honeycomb

LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

GORDION

RECESSED LED FIXTURES

Load 5 kN | Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;


Blue Amber Green Red

Gordion 1

Symmetrical



7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Symmetrical	7°Asymmetrical
1W LED	2700 K	95 lm	10°,25°,40°	170004	170014
1W LED	3000 K	95 lm	10°,25°,40°	170001	170011
1W LED	4000 K	97 lm	10°,25°,40°	170002	170012
1W LED	6000 K	99 lm	10°,25°,40°	170003	170013

Gordion 2

Symmetrical



7° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Symmetrical	Asymmetrical
3W LED	2700 K	285 lm	10°,25°,40°	170104	170114
3W LED	3000 K	285 lm	10°,25°,40°	170101	170111
3W LED	4000 K	290 lm	10°,25°,40°	170102	170112
3W LED	6000 K	296 lm	10°,25°,40°	170103	170113

Gordion 2


15° Asymmetrical



25° Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No	
				15° Asymmetrical	25° Asymmetrical
9W LED	2700 K	855 lm	10°,25°,40°	170144	170154
9W LED	3000 K	855 lm	10°,25°,40°	170141	170151
9W LED	4000 K	872 lm	10°,25°,40°	170142	170152
9W LED	6000 K	890 lm	10°,25°,40°	170143	170153



Honeycomb
Gordion 1: 953521
Gordion 2: 953522

GORDION

RECESSED LED FIXTURES Load 5 kN | Class I IP67 IK08



POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red

Gordion 3

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Symmetrical
6W LED	2700 K	570 lm	10°,25°,40°	170204
6W LED	3000 K	570 lm	10°,25°,40°	170201
6W LED	4000 K	581 lm	10°,25°,40°	170202
6W LED	6000 K	593 lm	10°,25°,40°	170203

Gordion 3

15° Asymmetrical


25° Asymmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No 15° Asymmetrical	Code No 25° Asymmetrical
6W LED	2700 K	570 lm	10°,25°,40°	170214	170224
6W LED	3000 K	570 lm	10°,25°,40°	170211	170221
6W LED	4000 K	581 lm	10°,25°,40°	170212	170222
6W LED	6000 K	593 lm	10°,25°,40°	170213	170223

Gordion 4

Symmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No Symmetrical
9W LED	2700 K	855 lm	10°,25°,40°	170304
9W LED	3000 K	855 lm	10°,25°,40°	170301
9W LED	4000 K	872 lm	10°,25°,40°	170302
9W LED	6000 K	890 lm	10°,25°,40°	170303



Honeycomb
Gordion 3: 953523
Gordion 4: 953524

GORDION


RECESSED LED FIXTURES
 Load 5 kN | Class I IP67 IK08



POWER LED (COB LED options available)
 Voltage : 240 VAC with integrated driver (12-24 VDC on request)
 Diffuser : Clear Glass 8 mm (Frosted Glass on request)
 CRI : >80 or >90
 Cable : Potted 1m 3x1 H03 VV-F
 Single color Power LED options upon request are ;
 Blue Amber Green Red

Gordion 5

Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No Symmetrical
9W LED	2700 K	95 lm	10°,25°,40°	170404
9W LED	3000 K	95 lm	10°,25°,40°	170401
9W LED	4000 K	97 lm	10°,25°,40°	170402
9W LED	6000 K	99 lm	10°,25°,40°	170403


Gordion 5

15°Asymmetrical

25°Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No 15° Asymmetrical	Code No 25° Asymmetrical
9W LED	2700 K	855 lm	10°,25°,40°	170414	170424
9W LED	3000 K	855 lm	10°,25°,40°	170411	170421
9W LED	4000 K	872 lm	10°,25°,40°	170412	170422
9W LED	6000 K	890 lm	10°,25°,40°	170413	170423



Honeycomb

Gordion 5: 953525

 Wall Recessed



EMFA

MILET ANI

WALL RECESSED

Class I IP67 IK08

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

EMFA's Ani wall recessed series is specially designed to deliver low-glare lighting to facades, walkways, pathways and driveways with minimal installation depth and narrow trim. The fixture is made of a combination of 316L stainless steel and die cast aluminium. The tilted design reduces the glare of the LED's. The Linear LEDs with special lenses gives excellent wallwashing effect. An anti-slip glass is available upon request.

Cover

316L Stainless steel or Aluminium

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

4 mm Tempered Glass

Screws


316L Stainless Steel

Glands


PG 11

"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, and 2 wattages, and available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



Symmetrical



Galvanized
Recessing Box




end of the code
number "s" add
for Screw
mounting option for


LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Asymmetrical



Asym. Glass




Trenched Glass





Milky Glass




Clear Glass






Led : Linear LEDs
Voltage : 240 VAC with integrated driver
 (12-24 VDC on request)
Diffuser : 8mm Tempered Glass
Beam Angle : 45° / 60° / 90°
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F

ANI 1




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
6W	2700 K	570 lm	456003	456503
12W	2700 K	1140 lm	456013	456513
6W	3000 K	570 lm	456001	456501
12W	3000 K	1140 lm	456011	456511
6W	4000 K	690 lm	456002	456502
12W	4000 K	1195 lm	456012	456512

ANI 2




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
12W	2700 K	1140 lm	456103	456603
24W	2700 K	2280 lm	456113	456613
12W	3000 K	1140 lm	456101	456601
24W	3000 K	2280 lm	456111	456611
12W	4000 K	1254 lm	456102	456602
24W	4000 K	2320 lm	456112	456612

ANI 3



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
18W	2700 K	1710 lm	456203	456703
36W	2700 K	3420 lm	456213	456713
18W	3000 K	1710 lm	456201	456701
36W	3000 K	3420 lm	456211	456711
18W	4000 K	1790 lm	456202	456702
36W	4000 K	3520 lm	456212	456712

ANI 4



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
24W	2700 K	2280 lm	456303	456803
36W	2700 K	3420 lm	456313	456813
24W	3000 K	2280 lm	456301	456801
36W	3000 K	3420 lm	456311	456811
24W	4000 K	2320 lm	456302	456802
36W	4000 K	3520 lm	456312	456812




Galvanized
Recessing Box



MILET ANI


WALL RECESSED

Class I IP67 IK08




Led : Linear LEDs
Voltage : 240 VAC with integrated driver
 (12-24 VDC on request)
Diffuser : 8mm Tempered Glass
Beam Angle : 45° / 60° / 90°
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F

ANI 1




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
6W	2700 K	570 lm	455003	455503
12W	2700 K	1140 lm	455013	455513
6W	3000 K	570 lm	455001	455501
12W	3000 K	1140 lm	455011	455511
6W	4000 K	690 lm	455002	455502
12W	4000 K	1195 lm	455012	455512

ANI 2




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
12W	2700 K	1140 lm	455103	455603
24W	2700 K	2280 lm	455113	455613
12W	3000 K	1140 lm	455101	455601
24W	3000 K	2280 lm	455111	455611
12W	4000 K	1254 lm	455102	455602
24W	4000 K	2320 lm	455112	455612

ANI 3




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
18W	2700 K	1710 lm	455203	455703
36W	2700 K	3420 lm	455213	455713
18W	3000 K	1710 lm	455201	455701
36W	3000 K	3420 lm	455211	455711
18W	4000 K	1790 lm	455202	455702
36W	4000 K	3520 lm	455212	455712

ANI 4



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
24W	2700 K	2280 lm	455303	455803
36W	2700 K	3420 lm	455313	455813
24W	3000 K	2280 lm	455301	455801
36W	3000 K	3420 lm	455311	455811
24W	4000 K	2320 lm	455302	455802
36W	4000 K	3520 lm	455312	455812



Galvanized Recessing Box

SANTOS 6

WALL RECESSED FIXTURES

Class I IP67 IK10

EMFA's Santos 6 Wall Recessed Fixture is specially designed to deliver glare-free lighting in open areas and pathways. The combination of the ribbed glass, which creates a horizontal elliptical light output and the lamp cover, which hides the source of light, allows for an unobtrusive comfortable lighting effect. The fixture is made of a combination of 316L stainless steel and aluminium. The narrow depth of 159 mm allows the fixture to be installed in most walls. The electronic ballast is housed in the thermally separated base of the fixture.

Cover

316L Stainless steel

Body

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Gaskets

Silicone

Diffusers

5 mm ribbed tempered Glass

Screws

316L Stainless steel

Glands

2 x PG 13.5

Recessing Tube

Polyamide 6



Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Diffuser : 12 mm Clear Glass (Frosted Glass on request)



Mac Adam : 3

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F



Adjustable



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W	2700 K	855 lm	10°, 23°, 36°	552301	552401
18W	2700 K	1710 lm	10°, 23°, 36°	552311	552411
9W	3000 K	855 lm	10°, 23°, 36°	552302	552402
18W	3000 K	1710 lm	10°, 23°, 36°	552121	552221
9W	4000 K	872 lm	10°, 23°, 36°	552303	552403
18W	4000 K	1744 lm	10°, 23°, 36°	552122	552222

MIRA

WALL RECESSED FIXTURE

Class I IP67 IK10

The Mira series consists of a range of LED and fluorescent sources to deliver the desired light effect to facades, columns, bridges, monuments, and signs. The series is made of a die cast aluminium body with electrostatic powder paint finished with a 316L stainless steel cover. The recessed versions are for drive over up to 20 kN including a stainless steel recessing box. The surface mounted versions come with a heavy-duty 316L stainless steel bracket. The fixtures come with integrated electronic ballasts and a specially developed potted power cable to effectively bond with the cast resin and stop any water ingress. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Cover

316L Stainless steel

Body

Die cast aluminium

Diffusers

12 mm Tempered Glass

Gaskets

Silicone

Screws

316L Stainless steel

Recessing Box

Stainless steel

Led : Power LEDs

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : 12mm Tempered Glass



Mac Adam : 3

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red



Asymmetrical



Power	Kelvin	Lumen Output	Lens	Code No
12W	2700 K	1140 lm	10°, 25°, 40°	430371
12W	3000 K	1140 lm	10°, 25°, 40°	430371
12W	4000 K	1160 lm	10°, 25°, 40°	430372
12W	6000 K	1185 lm	10°, 25°, 40°	430372
27W	RGB	Red, Green, Blue	25°, 40°	430381



BELKIS WALL RECESSED FIXTURE

Class I IP65 IK08



COB LED




Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90



Cable : Potted 1m 3x1 H03 VV-F

Belkis 3 Fix to Recessing Tube with Silicone





Power	Kelvin	Real Lumen Output	Code No	
			Round	Square
7W LED	2700 K	665 lm	423261	423281
7W LED	3000 K	665 lm	423261	423281
7W LED	4000 K	678 lm	423262	423282
7W LED	6000 K	690 lm	423264	423284

Belkis 3 Fix to Recessing Tube with Screws






Power	Kelvin	Real Lumen Output	Code No	
			Round	Square
7W LED	2700 K	665 lm	423271	423291
7W LED	3000 K	665 lm	423271	423291
7W LED	4000 K	678 lm	423272	423292
7W LED	6000 K	690 lm	423374	423294

Belkis 4 Fix to Recessing Tube with Silicone



Power	Kelvin	Real Lumen Output	Code No	
			Round	Square
11W LED	2700 K	1045 lm	423901	423921
11W LED	3000 K	1045 lm	423901	423921
11W LED	4000 K	1065 lm	423902	423922
11W LED	6000 K	1087 lm	423904	423924

Belkis 4 Fix to Recessing Tube with Screws



Power	Kelvin	Real Lumen Output	Code No	
			Round	Square
11W LED	2700 K	1045 lm	423911	423931
11W LED	3000 K	1045 lm	423911	423931
11W LED	4000 K	1065 lm	423912	423932
11W LED	6000 K	1087 lm	423914	423934

MILET WALL RECESSED FIXTURES

IP65 IK08

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

Cover

Die cast aluminium / Inox (Stainless steel)

Paint

Black or grey electrostatic powder

Body

Die cast aluminium

Recessing Box

Polycarbonate

Glands

1 X PG 9

Gaskets


Silicone

Diffusers

4 mm Tempered Glass





Symmetrical Inox





Power	Lampholder	Reflector	Code No	
			Round	Square
35W HALOGEN	Gu5,3 12V	10°, 38°	308111	306111
40W HALOGEN	G 9		308121	306121
50W HALOGEN	Gu10	10°, 38°	308131	306131

Symmetrical Aluminium





Power	Lampholder	Reflector	Code No	
			Round	Square
35W HALOGEN	Gu5,3 12V	10°, 38°	304111	302111
40W HALOGEN	G 9		304121	302121
50W HALOGEN	Gu10	10°, 38°	304131	302131

Asymmetrical Inox



Power	Lampholder	Reflector	Code No	
			Round	Square
35W HALOGEN	Gu5,3 12V	10°, 38°	303111	305111
40W HALOGEN	G 9		303121	305121
50W HALOGEN	Gu10	10°, 38°	303131	305131

Asymmetrical Aluminium




Power	Lampholder	Reflector	Code No	
			Round	Square
35W HALOGEN	Gu5,3 12V	10°, 38°	307111	301111
40W HALOGEN	G 9		307121	301121
50W HALOGEN	Gu10	10°, 38°	307131	301131

BELKIS MINI WALL RECESSED FIXTURES

Class I IP65 IK08

Available in any
of these RAL colors



Cover
316L Stainless steel or Aluminium

Body
Die cast aluminium

Recessing Box
Aluminium

Gaskets
Silicone

Diffusers
Tempered Glass

Screws
316L Stainless steel

Voltage : 240 VAC with integrated driver
(12-24 VDC on request)

Diffuser : Clear Glass 4 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red




Symmetrical




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	309001
1W LED	3000 K	95 lm	10°, 25°, 40°	309002
1W LED	4000 K	97 lm	10°, 25°, 40°	309003
1W LED	6000 K	99 lm	10°, 25°, 40°	309004
3W LED	2700 K	380 lm	10°, 25°, 40°	309011
3W LED	3000 K	380 lm	10°, 25°, 40°	309012
3W LED	4000 K	387 lm	10°, 25°, 40°	309013
3W LED	6000 K	395 lm	10°, 25°, 40°	309014

Symmetrical Deep




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	309101
1W LED	3000 K	95 lm	10°, 25°, 40°	309102
1W LED	4000 K	97 lm	10°, 25°, 40°	309103
1W LED	6000 K	99 lm	10°, 25°, 40°	309104
3W LED	2700 K	380 lm	10°, 25°, 40°	309111
3W LED	3000 K	380 lm	10°, 25°, 40°	309112
3W LED	4000 K	387 lm	10°, 25°, 40°	309113
3W LED	6000 K	395 lm	10°, 25°, 40°	309114

Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	309201
1W LED	3000 K	95 lm	10°, 25°, 40°	309202
1W LED	4000 K	97 lm	10°, 25°, 40°	309203
1W LED	6000 K	99 lm	10°, 25°, 40°	309204
3W LED	2700 K	380 lm	10°, 25°, 40°	309211
3W LED	3000 K	380 lm	10°, 25°, 40°	309212
3W LED	4000 K	387 lm	10°, 25°, 40°	309213
3W LED	6000 K	395 lm	10°, 25°, 40°	309214



Honeycomb
Code No: 953714

BELKIS 1 LL WALL RECESSED FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Diffusers

Tempered Glass

Gaskets

Silicone

Led : Linear LEDs



Voltage : 240 VAC with integrated driver
(12-24 VDC on request)

Diffuser : 4mm Tempered Clear Glass or Milky Glass


Mac Adam : 3

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F




Asymmetrical




Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	424101
3W	3000 K	285 lm	424101
3W	4000 K	290 lm	424102
3W	6000 K	296 lm	424104

Symmetrical



Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	424111
3W	3000 K	285 lm	424111
3W	4000 K	290 lm	424112
3W	6000 K	296 lm	424114

Symmetrical




Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	424121
3W	3000 K	285 lm	424121
3W	4000 K	290 lm	424122
3W	6000 K	296 lm	424124



SATURN WALL RECESSED FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Diffusers

Tempered Glass

Gaskets

Silicone

Led

:COB LEDs

Voltage

: 240 VAC with integrated driver
(12-24 VDC on request)

Diffuser

: 4mm Tempered Clear Glass or Frosted Glass

Mac Adam



: 3

CRI


: >80 or >90

Cable

: Potted 1m 3x1 H03 VV-F




Asymmetrical





Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	527003
3W	3000 K	285 lm	527001
3W	4000 K	290 lm	527002
3W	6000 K	296 lm	527004

Symmetrical



Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	527103
3W	3000 K	285 lm	527101
3W	4000 K	290 lm	527102
3W	6000 K	296 lm	527104

Symmetrical




Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	527203
3W	3000 K	285 lm	527201
3W	4000 K	290 lm	527202
3W	6000 K	296 lm	527204



BERGAMA WALL RECESSED FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Steel or Inox (Stainless Steel)

Paint

Electrostatic powder

Reflector

Anodized aluminium

Recessing Box

Galvanized steel
(only for in wall series)

Diffuser

4 mm Clear Glass



Led : Linear LEDs

Voltage : 240 VAC with integrated driver
(12-24 VDC on request)

Diffuser : 4mm Tempered Clear Glass or Frosted Glass


Mac Adam : 3

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F




140x70



Power	Kelvin	Real Lumen Output	Code No	
			Steel	Inox
1W	2700 K	95 lm	349002	349012
1W	3000 K	95 lm	349001	349011
1W	4000 K	97 lm	349003	349013
1W	6000 K	99 lm	349004	349014

70x140



Power	Kelvin	Real Lumen Output	Code No	
			Steel	Inox
3W	2700 K	285 lm	349101	349111
3W	3000 K	285 lm	527101	527101
3W	4000 K	290 lm	527102	527102
3W	6000 K	296 lm	349104	349114

PYRAMID

WALL RECESSED FIXTURES

IP65 IK08

Available in any
of these RAL colors



Cover & Body

Glass reinforced polyester

Screws

Inox

Gasket

Silicone

Glass

Tempered

Recessing Box

Galvanized steel

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Cable : Potted 1 m 3x1 H03 VV-F


Symmetrical



Asymmetrical




Symmetrical



Power	Lampholder	Kelvin	Code No
6W	LED	2700 K	502001
6W	LED	3000 K	502002
6W	LED	4000 K	502003
6W	LED	6000 K	502004
2x 18W FLUO. G24 d-2			502111
2x 26W FLUO. G24 d-3			502121

Asymmetrical



Power	Lampholder	Kelvin	Code No
6W	LED	2700 K	501001
6W	LED	3000 K	501002
6W	LED	4000 K	501003
6W	LED	6000 K	501004
1x 18W FLUO. G24 d-2			501011
1x 26W FLUO. G24 d-3			501121

SLIM PYRAMID WALL RECESSED FIXTURES


IP65 IK08

Available in any
of these RAL colors




Cover & Body
Glass reinforced polyester
Screws
Inox
Gasket
Silicone
Glass
Tempered
Recessing Box
Galvanized steel

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)
Cable : Potted 1 m 3x1 H03 VV-F




Symmetrical




Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	503001
9W	LED	3000 K	503002
9W	LED	4000 K	503003
9W	LED	6000 K	503004
1x 18W FLUO. G24 d-2			503011
1x 26W FLUO. G24 d-3			503021

Asymmetrical



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	503101
9W	LED	3000 K	503102
9W	LED	4000 K	503103
9W	LED	6000 K	503104
1x 18W FLUO. G24 d-2			503111
1x 26W FLUO. G24 d-3			503121

Asymmetrical




Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	503201
9W	LED	3000 K	503202
9W	LED	4000 K	503203
9W	LED	6000 K	503204
1x 18W FLUO. G24 d-2			503211
1x 26W FLUO. G24 d-3			503221

SIDE WALL RECESSED FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die Cast Aluminium

Cover

Die Cast Aluminium

Paint




Electrostatic powder paint

Diffuser


Polycarbonate

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Cable : Potted 1 m 3x1 H03 VV-F




Side 4




Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	510001
9W	LED	3000 K	510002
9W	LED	4000 K	510003
9W	LED	6000 K	510004
75W HALOGEN	E27		510201
1x 26W FLUO.	G24 d-3		510221

Side 5



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	511001
9W	LED	3000 K	511002
9W	LED	4000 K	511003
9W	LED	6000 K	511004
75W HALOGEN	E27		511201
1x 26W FLUO.	G24 d-3		511221

Side 6



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	512001
9W	LED	3000 K	512002
9W	LED	4000 K	512003
9W	LED	6000 K	512004
75W HALOGEN	E27		512201
1x 26W FLUO.	G24 d-3		512221

PERGE WALL RECESSED FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die Cast Aluminium

Cover

Die Cast Aluminium

Paint

Electrostatic powder paint

Diffuser

Polycarbonate



Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Cable : Potted 1 m 3x1 H03 VV-F


Symmetrical



Asymmetrical




Perge 4




Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	520001
9W	LED	3000 K	520002
9W	LED	4000 K	520003
9W	LED	6000 K	520004
75W HALOGEN	E27		520201
1x 26W FLUO.	G24 d-3		520221

Perge 5



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	521001
9W	LED	3000 K	521002
9W	LED	4000 K	521003
9W	LED	6000 K	521004
75W HALOGEN	E27		521201
1x 26W FLUO.	G24 d-3		521221

Perge 6



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	522001
9W	LED	3000 K	522002
9W	LED	4000 K	522003
9W	LED	6000 K	522004
75W HALOGEN	E27		522201
1x 26W FLUO.	G24 d-3		522221

 Surface Mounted



EMFA 

KNIDOS

SURFACE MOUNTED FIXTURES

IP67 IK10

Available in any
of these RAL colors



Cover

316L Stainless steel

Outer Body

316L Stainless steel

Inner Body

Glass reinforced polyester

Diffusers

12 mm Tempered Glass

Gaskets

Silicone

Screws

316L Stainless Steel



Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Diffuser : 12 mm Clear Glass (Frosted Glass on request)

Mac Adam : 3

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red




Symmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No
9W	2700 K	810 lm	10°, 25°, 40°	257244
18W	2700 K	1620 lm	10°, 25°, 40°	257251
9W	3000 K	810 lm	10°, 25°, 40°	257241
18W	3000 K	1620 lm	10°, 25°, 40°	257252
9W	4000 K	891lm	10°, 25°, 40°	257242
18W	4000 K	1782 lm	10°, 25°, 40°	257253
9W	6000 K	898lm	10°, 25°, 40°	257243
18W	6000 K	1795 lm	10°, 25°, 40°	257254
CDMR-111 35W		Gx8,5	10°, 40°	257211
CDMR-111 70W		Gx8,5	10°, 40°	257231

Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No
9W	2700 K	810 lm	10°, 25°, 40°	256304
18W	2700 K	1620 lm	10°, 25°, 40°	256331
9W	3000 K	810 lm	10°, 25°, 40°	256301
18W	3000 K	1620 lm	10°, 25°, 40°	256332
9W	4000 K	891lm	10°, 25°, 40°	256302
18W	4000 K	1782 lm	10°, 25°, 40°	256333
9W	6000 K	898lm	10°, 25°, 40°	256303
18W	6000 K	1795 lm	10°, 25°, 40°	256334
CDMR-111 35W		Gx8,5	10°, 40°	256311
CDMR-111 70W		Gx8,5	10°, 40°	256321

NEPTUN 3 SURFACE MOUNTED FIXTURES

IP65 IK10

Available in any
of these RAL colors



The Neptun Surface Mounted Uplighter, completely made of aluminium steel is ideal for areas where corrosive agents such as salt water or fertilizers would harm aluminium fixtures. The fixture can be mounted without harm to any surface and therefore is ideal for protected and historical sites where mounting recessed fixtures is not permitted.

Body

Die cast aluminium

Diffusers

4 mm Tempered Glass

Paint

Electrostatic powder

Gaskets

Silicone

Screws

316L Stainless Steel

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Diffuser : 12 mm Clear Glass (Frosted Glass on request)

Mac Adam : 3



CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F


Single color LED options upon request are ;

Blue Amber Green Red


Asymmetrical



Asymmetrical



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	259005
6W LED	3000 K	570 lm	10°, 25°, 40°	259001
6W LED	4000 K	580 lm	10°, 25°, 40°	259002
6W LED	6000 K	592 lm	10°, 25°, 40°	259003
18W LED	RGB	Red Green Blue	25°, 40°	259004



Honeycomb
Code No: 953523

BELKIS 5

SURFACE MOUNTED FIXTURES

IP65 IK10

Available in any
of these RAL colors



The Belkis Surface Mounted Uplighter, completely made of 316L stainless steel is ideal for areas where corrosive agents such as salt water or fertilizers would harm aluminium fixtures. The fixture can be mounted without harm to any surface and therefore is ideal for protected and historical sites where mounting recessed fixtures is not permitted.

Cover

316L Stainless steel

Outer Body

316L Stainless steel

Inner Body

Die cast aluminium

Diffusers

8 mm Tempered Glass

Gaskets

Silicone


Screws

316L Stainless Steel




- Voltage** : 240V A.C with integrated driver
(24V AC or DC on request)
- Diffuser** : 12 mm Clear Glass (Frosted Glass on request)
- Mac Adam** : 3
- CRI** : >80 or >90
- Cable** : Potted 1m 3x1 H03 VV-F

Wallwasher



Power	Kelvin	Real Lumen Output	Lens	Code No
13W COB LED	2700 K	1235 lm	Asymmetrical	333004
13W COB LED	3000 K	1235 lm	Asymmetrical	333001
13W COB LED	4000 K	1259 lm	Asymmetrical	333002
13W COB LED	6000 K	1284 lm	Asymmetrical	333003




Honeycomb
Code No: 953525

TEOS 3

SURFACE DRIVE OVER FIXTURES

Load 50 kN | Class I IP67 IK10

Available in any
of these RAL colors



EMFA's Teos 3 Surface Drive Over LED Fixture is specially designed to deliver high output LED light to ground surfaces of roads, carparks and pathways. This heavy duty fixture is designed to withstand the weight of large vehicles. Its robust construction allows for a maximum static load of 5000kg. The body and head of the fixture are made of die cast aluminium, while the recessing tube is made of steel to withstand the repeated impact of driving vehicles' tires. The high power LEDs are positioned and angled to provide maximum light output. The electronic LED driver is housed in the base of the fixture. The fixture comes with 2 x PG13.5 cable glands and 0.5m cable.

Cover

Die cast aluminium

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

Polycarbonate

Screws


316L Stainless steel

Glands

2 x PG 13.5

Cable

0.5m 3x0,75 mm H05VV-F




LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management



All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.



TEOS 3 SURFACE DRIVE OVER FIXTURES

Load 50 kN | Class I IP67 IK10


Available in any
of these RAL colors



- Led** : Linear LEDs
- Voltage** : 240 VAC with integrated driver (12-24 VDC on request)
- Diffuser** : Polycarbonate
- CRI** : >80 or >90
- Cable** : Potted 1m 3x1 H03 VV-F




Mono



Power	Kelvin	Real Lumen Output	Code No
1x 4W	2700 K	1x 380 lm	180203
1x 4W	3000 K	1x 380 lm	180201
1x 4W	4000 K	1x 418 lm	180202




Duo 1-way



Power	Kelvin	Real Lumen Output	Code No
2x 4W	2700 K	2x 380 lm	180213
2x 4W	3000 K	2x 380 lm	180211
2x 4W	4000 K	2x 392 lm	180212




Duo 2-way



Power	Kelvin	Real Lumen Output	Code No
2x 4W	2700 K	2x 380 lm	180223
2x 4W	3000 K	2x 380 lm	180221
2x 4W	4000 K	2x 392 lm	180222




Trio




Power	Kelvin	Real Lumen Output	Code No
3x 4W	2700 K	3x 380 lm	180233
3x 4W	3000 K	3x 380 lm	180231
3x 4W	4000 K	3x 392 lm	180232



Quad



Power	Kelvin	Real Lumen Output	Code No
4x 4W	2700 K	3x 380 lm	180243
4x 4W	3000 K	3x 380 lm	180241
4x 4W	4000 K	3x 392 lm	180242



Lux levels for one aperture at 3000K




EMFA

MIRA

SURFACE MOUNTED FIXTURES

Class I IP67 IK10

Available in any
of these RAL colors



The Mira series consists of a range of LED, fluorescent and metal halide sources to deliver the desired light effect to facades, columns, bridges, monuments, and signs. The series is made of a die cast aluminium body with electrostatic powder paint finished with a 316L stainless steel cover. The recessed versions are for drive over up to 20 kN including a stainless steel recessing box. The surface mounted versions come with a heavy-duty 316L stainless steel bracket. The fixtures come with integrated electronic ballasts and a specially developed potted power cable to effectively bond with the cast resin and stop any water ingress. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Cover

316L Stainless steel

Body

Die cast aluminium

Diffusers

12 mm Tempered Glass

Gaskets

Silicone

Screws

316L Stainless steel

Recessing Box

Stainless steel



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.




LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

Available in any
of these RAL colors




- Led** : Power LEDs
- Voltage** : 240 VAC with integrated driver (12-24 VDC on request)
- Diffuser** : 12mm Tempered Glass
- Mac Adam** : 3
- CRI** : >80 or >90
- Cable** : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


Bu sayfa bir önceki pdf'e koyulmamış
dolayısıyla yeni kodları verilecek.

MIRA 1 Short Bracket




Power	Kelvin	Real Lumen Output	Lens	Code No
12W	2700 K	1140 lm	10°, 25°, 40°	430202
12W	3000 K	1140 lm	10°, 25°, 40°	430201
12W	4000 K	1160 lm	10°, 25°, 40°	430206
12W	6000 K	1185 lm	10°, 25°, 40°	430207
27W	RGB	Red, Green, Blue	25°, 40°	430241

MIRA 1 Long Bracket




Power	Kelvin	Real Lumen Output	Lens	Code No
12W	2700 K	1140 lm	10°, 25°, 40°	430312
12W	3000 K	1140 lm	10°, 25°, 40°	430311
12W	4000 K	1160 lm	10°, 25°, 40°	430316
12W	6000 K	1185 lm	10°, 25°, 40°	430317
27W	RGB	Red, Green, Blue	25°, 40°	430341

MIRA 2 Short Bracket



Power	Kelvin	Real Lumen Output	Lens	Code No
36W	2700 K	3420 lm	10°, 25°, 40°	430802
36W	3000 K	3420 lm	10°, 25°, 40°	430801
36W	4000 K	3488 lm	10°, 25°, 40°	430806
36W	6000 K	3557 lm	10°, 25°, 40°	430807
81W	RGB	Red, Green, Blue	25°, 40°	430821
70W	METAL HALIDE G12			430841

MIRA 2 Long Bracket



Power	Kelvin	Real Lumen Output	Lens	Code No
36W	2700 K	3420 lm	10°, 25°, 40°	430902
36W	3000 K	3420 lm	10°, 25°, 40°	430901
36W	4000 K	3488 lm	10°, 25°, 40°	430906
36W	6000 K	3557 lm	10°, 25°, 40°	430907
81W	RGB	Red, Green, Blue	25°, 40°	430921
70W	METAL HALIDE G12			430941

KARIA

SURFACE MOUNTED FIXTURES

Class I IP67 IK10

Available in these 2 colors



Grey

Black

The Karia series consists of a range of LED and fluorescent sources to deliver the desired light effect to facades, columns, bridges, monuments, and signs. The series is made of an anodized extrusion aluminium body with polyamid side covers. Polyamid brackets are used to mount the fixtures. Stainless steel brackets are also available to increase the distance from the mounting surface if necessary. The fixtures come with integrated electronic ballasts and LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired light effect.

Body

Anodized Aluminium profile with polyamid 66 side covers

Mounting Brackets

Polyamide 66 (Stainless Steel on request)

Screws

Stainless steel

Diffusers

4 mm Tempered Glass

Gaskets

Silicone

Gland

2 cable Gland for 5-8 mm Ø cable



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



Thermal Management


All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

MIRA 5

RECESSED WALK OVER FIXTURES


Load 2 kN | Class I IP67 IK10

Available in these 2 colors




Led : Power LEDs
Voltage : 240 VAC with integrated driver (12-24 VDC on request)
Diffuser : 8mm Tempered Glass
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F
 Single color LED options upon request are ;
 Blue Amber Green Red

Karia 1 400mm




Power	Kelvin	Real Lumen Output	Lens	Code No
12W	2700 K	1140 lm	10°, 25°, 40°	431102
12W	3000 K	1140 lm	10°, 25°, 40°	431101
12W	4000 K	1162 lm	10°, 25°, 40°	431106
12W	6000 K	1186 lm	10°, 25°, 40°	431107
27W	RGB		25°, 40°	431601

Karia 2 750mm



Power	Kelvin	Real Lumen Output	Lens	Code No
24W	2700 K	2280 lm	10°, 25°, 40°	431212
24W	3000 K	2280 lm	10°, 25°, 40°	431211
24W	4000 K	2325 lm	10°, 25°, 40°	431216
24W	6000 K	2372 lm	10°, 25°, 40°	431217

Karia 3 1050mm




Power	Kelvin	Real Lumen Output	Lens	Code No
36W	2700 K	3420 lm	10°, 25°, 40°	431244
36W	3000 K	3420 lm	10°, 25°, 40°	431241
36W	4000 K	3488 lm	10°, 25°, 40°	431242
36W	6000 K	3558 lm	10°, 25°, 40°	431243
81W	RGB		25°, 40°	431251

SLIM PYRAMID WALL SURFACE FIXTURES

IP65 IK08

Available in any
of these RAL colors



Cover & Body

Glass reinforced polyester

Screws

Inox

Gasket

Silicone

Glass

Tempered

Recessing Box

Galvanized steel


Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Cable : Potted 1 m 3x1 H03 VV-F

Asymmetrical



Asymmetrical



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	503603
9W	LED	3000 K	503601
9W	LED	4000 K	503602
9W	LED	6000 K	503604
1x 9W FLUO.	G24 d-1		503501

SIDE WALL SURFACE FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die Cast Aluminium

Cover

Die Cast Aluminium

Paint

Electrostatic powder paint


Diffuser

Polycarbonate


Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Cable : Potted 1 m 3x1 H03 VV-F


Symmetrical



Asymmetrical




Side 1




Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	505211
9W	LED	3000 K	505212
9W	LED	4000 K	505213
9W	LED	6000 K	505214
75W HALOGEN	E27		505201
1x 26W FLUO.	G24 d-3		505221

Side 2



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	507211
9W	LED	3000 K	507212
9W	LED	4000 K	507213
9W	LED	6000 K	507214
75W HALOGEN	E27		507201
1x 26W FLUO.	G24 d-3		507221

Side 3



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	506211
9W	LED	3000 K	506212
9W	LED	4000 K	506213
9W	LED	6000 K	506214
75W HALOGEN	E27		506201
1x 26W FLUO.	G24 d-3		506221

PERGE WALL SURFACE FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die Cast Aluminium

Cover

Die Cast Aluminium

Paint

Electrostatic powder paint

Diffuser

Polycarbonate

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Cable : Potted 1 m 3x1 H03 VV-F


Symmetrical



Asymmetrical




Perge 1




Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	515211
9W	LED	3000 K	515212
9W	LED	4000 K	515213
9W	LED	6000 K	515214
75W HALOGEN	E27		515201
1x 26W FLUO.	G24 d-3		515221

Perge 2



Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	517211
9W	LED	3000 K	517212
9W	LED	4000 K	517213
9W	LED	6000 K	517214
75W HALOGEN	E27		517201
1x 26W FLUO.	G24 d-3		517221

Perge 3




Power	Lampholder	Kelvin	Code No
9W	LED	2700 K	516211
9W	LED	3000 K	516212
9W	LED	4000 K	516213
9W	LED	6000 K	516214
75W HALOGEN	E27		516201
1x 26W FLUO.	G24 d-3		516221

MILET

WALL SURFACE FIXTURES

IP65 IK08

Available in any
of these RAL colors



Cover

Die cast aluminium / Inox (Stainless steel)

Paint

Black or grey electrostatic powder

Body

Die cast aluminium

Connection


Sealed crimp splices

Gaskets

Silicone


Diffusers

4 mm Tempered Glass




The Milet Surface Mounted Series is specially designed to deliver low glare halogen lighting to steps, open areas, corridors and pathways. The fixture has a die cast aluminium body painted with electrostatic powder paint. The slated or open covers come in an aluminium or aluminium / stainless steel finish. The cable on site can be securely connected to the fixture via a sealed crimp splice.

Symmetrical



Power	Lampholder	Reflector	Code No	
			Alum.	Inox
40W HALOGEN	G 9	-	312111	314111

Asymmetrical



Power	Lampholder	Reflector	Code No	
			Alum.	Inox
40W HALOGEN	G 9	-	310111	311111





The Milet Indirect series consists of an on-wall fixture and a bollard using LED, halogen or fluorescent. The fixtures are made of a combination of a die cast aluminium head and an aluminium pipe painted with electrostatic powder paint. The wall fixture allows for a custom made sign showing room numbers or names. For the LED versions, a specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. For the halogen and fluorescent versions, an IP connection box is provided to allow for a secure connection of the on-site cable.

Cover

Die cast aluminium

Paint

Black or grey electrostatic powder

Body

Die cast aluminium

Connection


IP connection box

Gaskets

Silicone

Diffusers


Polycarbonate



Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Diffuser : Polycarbonate

Cable : Potted 1 m 3x1 H03 VV-F



Power	Lampholder	Kelvin	Code No
11W	LED	2700 K	290102
11W	LED	3000 K	290101
11W	LED	4000 K	290103
11W	LED	6000 K	290104
40W HALOGEN	G 9		290201



Special Application

For room numbers, names, signs etc.
The acrylic part inside can be colour
of choice.




CODE NO 295115
ELECTR. CIR. FLUO. 6W

SQUARE MINI

LED APPLIQUES LED DRIVER IN HADE Class I IP65 IK10

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Gaskets

Silicone

Diffusers

Tempered Glass

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

POWER LED (COB LED options available)

Voltage : 240 VAC with integrated driver (12-24 VDC on request)



Diffuser : Clear Glass 8 mm (Frosted Glass on request)

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red




Honeycomb
Code No: 953541

240V Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	298004
1W LED	3000 K	95 lm	10°, 25°, 40°	298001
1W LED	4000 K	97 lm	10°, 25°, 40°	298002
1W LED	6000 K	99 lm	10°, 25°, 40°	298003
3W LED	2700 K	380 lm	10°, 25°, 40°	298014
3W LED	3000 K	380 lm	10°, 25°, 40°	298011
3W LED	4000 K	387 lm	10°, 25°, 40°	298012
3W LED	6000 K	395 lm	10°, 25°, 40°	298013
12-24V Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	298024
6W LED	3000 K	570 lm	10°, 25°, 40°	298021
6W LED	4000 K	585 lm	10°, 25°, 40°	298022
6W LED	6000 K	592 lm	10°, 25°, 40°	298023

BELKIS 1 LL WALL SURFACE FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Diffusers

Tempered Glass 4 mm

Gaskets

Silicone




The Belkis 1 LLS is specially designed to deliver low glare LED lighting to steps, open areas, corridors and pathways where recessing the fixture is not possible. The fixture has a die cast aluminium body painted with electrostatic powder paint. The narrow depth of 39mm, which also includes the LED driver, allows the fixture to be installed in any wall. A plastic recessing box is included for installation into concrete. A specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The linear LED used comes in 2 different tones of white, 3000K and 4000K.




- Led** : Linear LEDs
- Voltage** : 240 VAC with integrated driver
(12-24 VDC on request)
- Diffuser** : 4mm Tempered Clear Glass or Milky Glass
- Mac Adam** : 3
- CRI** : >80 or >90
- Cable** : Potted 1m 3x1 H03 VV-F

Asymmetrical



Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	424143
3W	3000 K	285 lm	424141
3W	4000 K	290 lm	424142
3W	6000 K	296 lm	424144

Symmetrical



Power	Kelvin	Real Lumen Output	Code No	
			Milky Glass	Clear Glass
3W	2700 K	285 lm	424153	424163
3W	3000 K	285 lm	424151	424161
3W	4000 K	290 lm	424152	424162
3W	6000 K	296 lm	424154	424164




SATURN LL

WALL SURFACE FIXTURES

IP65 IK08

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Diffusers

Tempered Glass 4 mm

Gaskets

Silicone




The Saturn 1 LLS is specially designed to deliver low glare LED lighting to steps, open areas, corridors and pathways where recessing the fixture is not possible. The fixture has a die cast aluminium body painted with electrostatic powder paint. The narrow depth of 39mm, which also includes the LED driver, allows the fixture to be installed in any wall. A plastic recessing box is included for installation into concrete. A specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The linear LED used comes in 2 different tones of white, 3000K and 4000K.




- Led** : COB LEDs
- Voltage** : 240 VAC with integrated driver
(12-24 VDC on request)
- Diffuser** : 4mm Tempered Clear Glass or Milky Glass
- Mac Adam** : 3
- CRI** : >80 or >90
- Cable** : Potted 1m 3x1 H03 VV-F

Asymmetrical



Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	526003
3W	3000 K	285 lm	526001
3W	4000 K	290 lm	526002
3W	6000 K	296 lm	526004

Symmetrical



Power	Kelvin	Real Output	Code No		Lumen
			Milky Glass	Clear Glass	
3W	2700 K	285 lm	526203		526103
3W	3000 K	285 lm	526201		526101
3W	4000 K	290 lm	526202		526101
3W	6000 K	296 lm	526204		526104





Body

Die cast aluminium

Paint

Electrostatic powder

Diffusers

Tempered Glass 4 mm

Gaskets

Silicone

The LYKIA LL is specially designed to deliver low glare LED lighting to steps, open areas, corridors and pathways where recessing the fixture is not possible. The fixture has a die cast aluminium body painted with electrostatic powder paint. The narrow depth of 39mm, which also includes the LED driver, allows the fixture to be installed in any wall. A plastic recessing box is included for installation into concrete. A specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The linear LED used comes in 2 different tones of white, 3000K and 4000K.

Led : Linear LEDs



Voltage : 240 VAC with integrated driver
(12-24 VDC on request)

Diffuser : 4mm Tempered Clear Glass or Milky Glass


Mac Adam : 3

CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F



Asymmetrical



Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	285 lm	424202
3W	3000 K	285 lm	424201
3W	4000 K	290 lm	424203
3W	6000 K	296 lm	424204





EMFA

MILET ANI

WALL SURFACE

Class I IP67 IK08

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

EMFA's Ani wall recessed series is specially designed to deliver low-glare lighting to facades, walkways, pathways and driveways with minimal installation depth and narrow trim. The fixture is made of a combination of 316L stainless steel and die cast aluminium. The tilted design reduces the glare of the LED's. The Linear LEDs with special lenses gives excellent wallwashing effect. An anti-slip glass is available upon request.

Cover

316L Stainless steel or Aluminium

Body

Die cast aluminium

Gaskets

Silicone

Diffusers


4 mm Tempered Glass

Screws

316L Stainless Steel

Glands


PG 11



"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, and 2 wattages, and available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

Symmetrical



Galvanized Surface Box




end of the code number "s" add for screw mounting option for


LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Asymmetrical



Asym. Glass



Trenched Glass




Milky Glass



Clear Glass




Available in any
of these RAL colors




Led : Linear LEDs
Voltage : 240 VAC with integrated driver
 (12-24 VDC on request)
Diffuser : 8mm Tempered Glass
Beam Angle : 45° / 60° / 90°
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F

ANI 1




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
6W	2700 K	570 lm	457003	457503
12W	2700 K	1140 lm	457013	457513
6W	3000 K	570 lm	457001	457501
12W	3000 K	1140 lm	457011	457511
6W	4000 K	690 lm	457002	457502
12W	4000 K	1195 lm	457012	457512

ANI 2




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
12W	2700 K	1140 lm	457103	457603
24W	2700 K	2280 lm	457113	457613
12W	3000 K	1140 lm	457101	457601
24W	3000 K	2280 lm	457111	457611
12W	4000 K	1254 lm	457102	457602
24W	4000 K	2320 lm	457112	457612

ANI 3




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
18W	2700 K	1710 lm	457203	457703
36W	2700 K	3420 lm	457213	457713
18W	3000 K	1710 lm	457201	457701
36W	3000 K	3420 lm	457211	457711
18W	4000 K	1790 lm	457202	457702
36W	4000 K	3520 lm	457212	457712

ANI 4




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
24W	2700 K	2280 lm	457303	457803
36W	2700 K	3420 lm	457313	457813
24W	3000 K	2280 lm	457301	457801
36W	3000 K	3420 lm	457311	457811
24W	4000 K	2320 lm	457302	457802
36W	4000 K	3520 lm	457312	457812




Galvanized
Surface Box

Available in any
of these RAL colors




Led : Linear LEDs
Voltage : 240 VAC with integrated driver
(12-24 VDC on request)
Diffuser : 8mm Tempered Glass
Beam Angle : 45° / 60° / 90°
Mac Adam : 3
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F

ANI 1




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
6W	2700 K	570 lm	454003	454503
12W	2700 K	1140 lm	454013	454513
6W	3000 K	570 lm	454001	454501
12W	3000 K	1140 lm	454011	454511
6W	4000 K	690 lm	454002	454502
12W	4000 K	1195 lm	454012	454512

ANI 2




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
12W	2700 K	1140 lm	454103	454603
24W	2700 K	2280 lm	454113	454613
12W	3000 K	1140 lm	454101	454601
24W	3000 K	2280 lm	454111	454611
12W	4000 K	1254 lm	454102	454602
24W	4000 K	2320 lm	454112	454612

ANI 3




Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
18W	2700 K	1710 lm	454203	454703
36W	2700 K	3420 lm	454213	454713
18W	3000 K	1710 lm	454201	454701
36W	3000 K	3420 lm	454211	454711
18W	4000 K	1790 lm	454202	454702
36W	4000 K	3520 lm	454212	454712

ANI 4



Power	Kelvin	Real Lumen Output	Code No	
			Symmetrical	Asymmetrical
24W	2700 K	2280 lm	454303	454803
36W	2700 K	3420 lm	454313	454813
24W	3000 K	2280 lm	454301	454801
36W	3000 K	3420 lm	454311	454811
24W	4000 K	2320 lm	454302	454802
36W	4000 K	3520 lm	454312	454812





Galvanized
Surface Box

TAROS 2

SURFACE LED FIXTURES


Class I IP55 IK08

Available in any
of these RAL colors




Led : Power LEDs
Voltage : 240 VAC with integrated driver
 (12-24 VDC on request)
Diffuser : Polycarbonate
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F
 Single color LED options upon request are ;
 Blue Amber Green Red

Mono




Power	Kelvin	Real Lumen Output	Code No
1x 4W	2700 K	1x 380 lm	443001
1x 4W	3000 K	1x 380 lm	443002
1x 4W	4000 K	1x 418 lm	443003
1x 4W	6000 K	1x 418 lm	443004

Dual




Power	Kelvin	Real Lumen Output	Code No
2x 4W	2700 K	2x 380 lm	443101
2x 4W	3000 K	2x 380 lm	443102
2x 4W	4000 K	2x 392 lm	443103
2x 4W	6000 K	2x 392 lm	443104

Trio




Power	Kelvin	Real Lumen Output	Code No
3x 4W	2700 K	2x 380 lm	443201
3x 4W	3000 K	2x 380 lm	443202
3x 4W	4000 K	2x 392 lm	443203
3x 4W	6000 K	2x 392 lm	443204

Quad



Power	Kelvin	Real Lumen Output	Code No
4x 4W	2700 K	3x 380 lm	443301
4x 4W	3000 K	3x 380 lm	443302
4x 4W	4000 K	3x 392 lm	443303
4x 4W	6000 K	3x 392 lm	443304

 Selge Applique




403

EMFA 

SELGE ADJUSTABLE TWO WAY LED APPLIQUES

Class I IP65

Available in any
of these RAL colors



The Selge Adjustable Applique series consists of a range of LED light sources to deliver the desired light effect to facades and columns. The series is made of die cast aluminium and extrusion aluminium painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Outer Body

Extruded aluminium

Body

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium



Diffuser

Tempered Glass or acrylic


"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

Adjustable



- Led** : Linear LEDs
- Voltage** : 240 VAC with integrated driver
(12-24 VDC on request)
- Diffuser** : 3mm Tempered Clear Glass or Milky Glass
- Mac Adam** : 3
- CRI** : >80 or >90



Power	Kelvin	Real Lumen Output	Code No
2x 3W	2700 K	2x 285 lm	108004
2x 3W	3000 K	2x 285 lm	108001
2x 3W	4000 K	2x 290 lm	108002
2x 3W	6000 K	2x 296 lm	108003

Silyon Wall Surface



SILYON LED SURFACE MOUNTED

Class I IP65

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

The Silyon Surface Mount series consists of a range of LED light sources to deliver the desired light effect to facades and columns. The series is made of die cast aluminium and painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Body

Die cast aluminium

Paint

Electrostatic powder

Base

316L Stainless Steel

Diffuser

Tempered Glass or acrylic

Led : Power LEDs

Voltage : 240 VAC with integrated driver
(12-24 VDC on request)



Diffuser : Polycarbonate

CRI : >80 or >90



Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red



	Kelvin	Real Lumen Output		Code No	
		1W	3W	1W	3W
LED	2700 K	95 lm	285 lm	109011	109004
LED	3000 K	95 lm	285 lm	109012	109001
LED	4000 K	97 lm	290 lm	109013	109002
LED	6000 K	99 lm	296 lm	109014	109003




	Kelvin	Real Lumen Output		Code No	
		1W	3W	1W	3W
LED	2700 K	95 lm	285 lm	109111	109104
LED	3000 K	95 lm	285 lm	109112	109101
LED	4000 K	97 lm	290 lm	109113	109102
LED	6000 K	99 lm	296 lm	109114	109103

LEON LED SURFACE MOUNTED

Class I IP65

Available in any
of these RAL colors



EMFA's Leon combines a die-cast aluminium head housing an LED unit with an extrusion aluminium pipe. The bollard is designed to light pathways, landscapes and open spaces. The Leon bollard gives light only in the downward direction. This avoids any kind of glare and light pollution. The head and pipe are connected by a hidden screw within the pipe. The head contains LEDs that can be powered up to 12W. An optional galvanized steel anchorage kit is available for mounting into concrete. An alternative option is sleeve anchors for mounting onto existing concrete or a picket to mount into the earth.

Head

Die cast aluminium

Diffusers

Frosted polyamide 6.6

Pipe




Extrusion aluminium

Paint

Electrostatic powder



- Led** : Circular LEDs (6W or 12W)
- Voltage** : 240 VAC with integrated driver
(12-24 VDC on request)
- Diffuser** : Polyamide
- CRI** : >80
- Cable** : Potted 1m 3x1 H03 VV-F



	Kelvin	Real Lumen Output		Code No	
		6W	12W	6W	12W
LED	2700 K	570 lm	1140 lm	179001	179011
LED	3000 K	570 lm	1140 lm	179002	179012
LED	4000 K	582lm	1162 lm	179003	179013
LED	6000 K	591 lm	1185 lm	179004	179014



Ceramus Mini Applique

Ø43mm




EMFA

CERAMUS MINI

LED APPLIQUES

Class I IP65

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffuser

Tempered Glass or acrylic

Gaskets

Silicon

Power LEDs

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)


Lens : 10°, 20° or 30°

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;

Blue Amber Green Red




One - Way




	Kelvin	Real Lumen Output		Lens	Code No	
		1W	3W		1W	3W
LED	2700 K	95 lm	285 lm	10°, 25°, 40°	463004	463014
LED	3000 K	95 lm	285 lm	10°, 25°, 40°	463001	463011
LED	4000 K	97 lm	290 lm	10°, 25°, 40°	463002	463012
LED	6000 K	99 lm	296 lm	10°, 25°, 40°	463003	463013

Two - Way



	Kelvin	Real Lumen Output		Lens	Code No	
		2x 1W	2x 3W		1W	3W
LED	2700 K	95 lm	285 lm	10°, 25°, 40°	463104	463114
LED	3000 K	95 lm	285 lm	10°, 25°, 40°	463101	463111
LED	4000 K	97 lm	290 lm	10°, 25°, 40°	463102	463112
LED	6000 K	99 lm	296 lm	10°, 25°, 40°	463103	463113



Honeycomb
Code No: 953511

Ceramus 2 Applique

Ø80mm



EMFA

CERAMUS 2 LED APPLIQUES






Class I IP65

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

- Body**
Die cast aluminium
- Paint**
Electrostatic powder
- Bracket**
Die cast aluminium
- Diffuser**
Tempered Glass or acrylic
- Gaskets**
Silicon
- COB LED**

- Voltage** : 240 VAC with integrated driver (12-24 VDC on request)
- Diffuser** : Clear Glass 8 mm (Frosted Glass on request)
- Lens** : 10°, 20° or 30°
- CRI** : >80 or >90
- Cable** : Potted 1m 3x1 H03 VV-F



Honeycomb
Code No: 953522

	Kelvin	Real Lumen Output		Lens	Code No	
		6W	12W		6W	12W
LED	2700 K	570 lm	1140 lm	10°,20°,30°	464004	464014
LED	3000 K	570 lm	1140 lm	10°,20°,30°	464001	464011
LED	4000 K	582lm	1162 lm	10°,20°,30°	464002	464012
LED	6000 K	591 lm	1185 lm	10°,20°,30°	464003	464013

	Kelvin	Real Lumen Output		Lens	Code No	
		2x 6W	2x 12W		6W	12W
LED	2700 K	570 lm	1140 lm	10°,20°,30°	464104	464114
LED	3000 K	570 lm	1140 lm	10°,20°,30°	464101	464111
LED	4000 K	582lm	1162 lm	10°,20°,30°	464102	464112
LED	6000 K	591 lm	1185 lm	10°,20°,30°	464103	464113




BELKIS

APPLIQUES

Class I IP55 IK08

Available in any
of these RAL colors



The Belkis Applique series consists of a range of LED, metal halide and halogen sources to deliver the desired light effect to facades and columns. The series is made of die cast aluminium and extrusion aluminium painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Body

Aluminium Profile

Cover

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffusers

Tempered Glass

Gaskets

Silicone

Connection

IP connection box




“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

One Way



Two Way



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

BELKIS APPLIQUES

Class I IP55 IK08

Available in any
of these RAL colors



Power LEDs

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)


CRI : >80 or >90

Cable : Potted 1m 3x1 H03 VV-F

Single color Power LED options upon request are ;


Blue Amber Green Red

BELKIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No	
				One Way	Two Way
1W	2700 K	95 lm	10°, 25°, 40°	425102	425112
1W	3000 K	95 lm	10°, 25°, 40°	425101	425111
1W	4000 K	97 lm	10°, 25°, 40°	425106	425116
1W	6000 K	99 lm	10°, 25°, 40°	425107	425117
25W	HALOGEN	G9		340101	343101

BELKIS 2




Power	Kelvin	Real Lumen Output	Lens	Code No	
				One Way	Two Way
3W	2700 K	95 lm	10°, 25°, 40°	425122	425152
3W	3000 K	95 lm	10°, 25°, 40°	425121	425131
3W	4000 K	97 lm	10°, 25°, 40°	425126	425136
3W	6000 K	99 lm	10°, 25°, 40°	425127	425137
35W	HALOGEN	Gu10		341111	344111

BELKIS 5




Power	Kelvin	Real Lumen Output	Lens	Code No	
				One Way	Two Way
9W	2700 K	95 lm	10°, 25°, 40°	425142	425152
9W	3000 K	95 lm	10°, 25°, 40°	425141	425151
9W	4000 K	97 lm	10°, 25°, 40°	425146	425156
9W	6000 K	99 lm	10°, 25°, 40°	425147	425157
75W	HALOGEN	E27		342111	345111

BELKIS 5 M.H.



Power	Lampholder	Code No	
		One Way	Two Way
35W METAL HALIDE	G12	346401	346501
70W METAL HALIDE	G12	346411	346511



Honeycomb

Belkis 1: 953521

Belkis 2: 953522



Belkis 5: 953525



BELKIS 1 ACRYLIC APPLIQUES

Class I IP55 IK08

Available in any
of these RAL colors




Voltage : 240V A.C with integrated driver

Diffuser : Acrylic Pipe

Transformer : Electronic


Cable : Potted 1 m 3x1 H03 VV-F

One Way




Power	Lampholder	Code No
COMPACT FLUO. 13W	G24 q - 1	293301

Two Way




Power	Lampholder	Code No
COMPACT FLUO. 2x 13W	2x G24 q - 1	293401

Torch Acrylic



Power	Lampholder	Code No
COMPACT FLUO. 13W	G24 q - 1	293201

Torch Acrylic




Power	Lampholder	Code No
50W HALOGEN	Gu 5,3	293251



SQUARE APPLIQUES

Class I IP65 IK08

Available in any
of these RAL colors



The Square Applique series consists of a range of LED, metal halide and halogen sources to deliver the desired light effect to facades and columns. The series is made of die cast aluminium and extrusion aluminium painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Body

Die cast aluminium

Cover

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffusers

Tempered Glass

Gaskets

Silicone

Connection

IP connection box



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

One Way



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

SQUARE APPLIQUES

Class I IP65 IK08

Available in any
of these RAL colors



Power LEDs

Voltage : 240 VAC with integrated driver (12-24 VDC on request)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)


CRI : >80 or >90

Cable : -

Single color Power LED options upon request are ;


Blue Amber Green Red

Clear Glass with Lens




Power	Kelvin	Real Lumen Output	Lens	Code No
6W	2700 K	570 lm	10°, 25°, 40°	434024
6W	3000 K	570 lm	10°, 25°, 40°	434021
6W	4000 K	582lm	10°, 25°, 40°	434022
6W	6000 K	591 lm	10°, 25°, 40°	434023

Frosted Glass




Power	Kelvin	Real Lumen Output	Code No
6W	2700 K	570 lm	434013
6W	3000 K	570 lm	434011
6W	4000 K	582lm	434012
6W	6000 K	591 lm	434014

Dot




Power	Kelvin	Real Lumen Output	Code No
6W	2700 K	570 lm	434003
6W	3000 K	570 lm	434001
6W	4000 K	582lm	434002
6W	6000 K	591 lm	434004



Honeycomb
Code No: 953523

Available in any
of these RAL colors



Body

Aluminium profile

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffusers

Acrylic

Gaskets

Silicone

Connection

IP connection box

Aluminium



Acrylic



COB LED


Voltage : 240 VAC with integrated driver
(12-24 VDC on request)

Diffuser : Acrylic

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Round




Power	Kelvin	Lumen Output	Code	
			Aluminium	Acrylic
11W	2700 K	1045 lm	504003	504023
11W	3000 K	1045 lm	504001	504021
11W	4000 K	1065 lm	504002	504022
11W	6000 K	1089 lm	504004	504024

Round



Power	Kelvin	Real Lumen Output	Code	
			Aluminium	Acrylic
11W	2700 K	1045 lm	504013	504033
11W	3000 K	1045 lm	504011	504031
11W	4000 K	1065 lm	504012	504032
11W	6000 K	1089 lm	504014	504034

Square




Power	Kelvin	Real Lumen Output	Code
			Aluminium
11W	2700 K	1045 lm	504043
11W	3000 K	1045 lm	504041
11W	4000 K	1065 lm	504042
11W	6000 K	1089 lm	504044

SATURN

APPLIQUES


Class I IP65 IK08

Available in any
of these RAL colors




Voltage : 240V A.C with integrated driver
Diffuser : Glass
Transformer : Electronic
Cable : Potted 1 m 3x1 H03 VV-F

Satrun 1




Power	Lampholder	Code No
ELECTRONIC FLUO. DEL 23W	E27	525101

Satrun 2



Power	Lampholder	Code No
ELECTRONIC FLUO. DEL 23W	E27	525201

Satrun 3



Power	Lampholder	Code No
ELECTRONIC FLUO. DEL 23W	E27	525301

 Spots



EMFA

 DARA Spots



EMFA

DARA

LED SPOTS

Class I IP65 IK08

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

The Dara Spot series has an LED source to deliver the desired light effect to facades, columns, bridges, monuments, signs, and trees. The series is made of die cast aluminium and painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment (grey, anthracite, black, white, green and beige). The spots can be mounted on surfaces, in the ground or concrete with a picket, or on a pole with the addition of a simple adaptor. Once installed, the special joint system allows for 100° horizontal and 180° vertical adjustment.

The LEDs used come in 3 different tones of white (2700K, 3000K, 4000K). Several lenses from 10 to 30 degrees are available to choose from to achieve the desired light effect.

Body

Die cast aluminium

Paint

Electrostatic powder

Pipe

Aluminium Profile

Gaskets



Silicone

Diffusers

Tempered Glass

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management


All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

DARA

LED SPOTS

Class I IP65 IK08


Available in any
of these RAL colors



COB LEDs


Voltage : 12-24 VDC External driver
Diffuser : Clear Glass 4 mm (Frosted Glass on request)
CRI : >80 or >90
Cable : Potted 1m 3x1 H03 VV-F

DARA 2




Height	Power	Kelvin	Real Lumen Output	Lens	Code No	
					Single	Twin
350mm	6W	2700/3000K	570 lm	10°, 20°, 30°	553001	554001
350mm	6W	4000 K	590 lm	10°, 20°, 30°	553002	554002
500mm	6W	2700/3000K	570 lm	10°, 20°, 30°	553101	554101
500mm	6W	4000 K	590 lm	10°, 20°, 30°	553102	554102
700mm	6W	2700/3000K	570 lm	10°, 20°, 30°	553201	554201
700mm	6W	4000 K	590 lm	10°, 20°, 30°	553202	554202

DARA 3



Height	Power	Kelvin	Real Lumen Output	Lens	Code No	
					Single	Twin
350mm	11W	2700/3000K	1045 lm	10°, 20°, 30°	555001	556001
350mm	11W	4000 K	1070 lm	10°, 20°, 30°	555002	556002
500mm	11W	2700/3000K	1045 lm	10°, 20°, 30°	555101	556101
500mm	11W	4000 K	1070 lm	10°, 20°, 30°	555102	556102
700mm	11W	2700/3000K	1045 lm	10°, 20°, 30°	555201	556201
700mm	11W	4000 K	1070 lm	10°, 20°, 30°	555202	556202


DARA 4



Height	Power	Kelvin	Real Lumen Output	Lens	Code No	
					Single	Twin
350mm	16W	2700/3000K	1520 lm	10°, 20°, 30°	557001	558001
350mm	16W	4000 K	1590 lm	10°, 20°, 30°	557002	558002
500mm	16W	2700/3000K	1520 lm	10°, 20°, 30°	557101	558101
500mm	16W	4000 K	1590 lm	10°, 20°, 30°	557102	558102
700mm	16W	2700/3000K	1520 lm	10°, 20°, 30°	557201	558201
700mm	16W	4000 K	1590 lm	10°, 20°, 30°	557202	558202



Picket
Code No: 953552




Honeycomb
Code No: 953551

SQUARE MINI

LED SPOT

Class I IP67 IK08

Available in any
of these RAL colors



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.

Body

Die cast aluminium

Paint

Electrostatic powder

Gaskets

Silicone

Diffusers

Tempered Glass



Power LED or COB LEDs

Voltage : 240 VAC with integrated driver (12-24 VDC on request)


Diffuser : Clear Glass 4 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red




Power	Kelvin	Real Lumen Output	Lens	Code No
1W	2700 K	95 lm	10°, 25°, 40°	438004
1W	3000 K	95 lm	10°, 25°, 40°	438001
1W	4000 K	97 lm	10°, 25°, 40°	438002
1W	6000 K	99 lm	10°, 25°, 40°	438003
3W	2700 K	285 lm	10°, 25°, 40°	438014
3W	3000 K	285 lm	10°, 25°, 40°	438011
3W	4000 K	290 lm	10°, 25°, 40°	438012
3W	6000 K	296 lm	10°, 25°, 40°	438013



Power	Kelvin	Real Lumen Output	Lens	Code No
6W	2700 K	570 lm	10°, 25°, 40°	438024
6W	3000 K	570 lm	10°, 25°, 40°	438021
6W	4000 K	580 lm	10°, 25°, 40°	438022
6W	6000 K	592 lm	10°, 25°, 40°	438023


12V - 24V (240V A.C with external driver)




Visor
Code No: 953712



Cylinder Visor
Code No: 953713



Honeycomb
Code No: 953714




Picket
Code No: 953711

SQUARE

LED SPOT WITH TIR LENS

Class I IP67 IK10

Available in any
of these RAL colors



The Square Spot series consists of a range of LED, metal halide, fluorescent and halogen sources to deliver the desired light effect to facades, columns, bridges, monuments, signs, and trees. The series is made of die cast aluminium and painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment (grey, anthracite, black, white, green and beige). The spots can be mounted on surfaces, in the ground or concrete with a picket, or on a pole with the addition of a simple adaptor. Two adaptors are available for two sizes of poles. Once installed, the special joint system allows for 100° horizontal and 180° vertical adjustment. The gearboxes are either filled with cast resin and have a pre-potted cable for IP67. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 10 to 30 degrees are available to choose from to achieve the desired the light effect.



Body

Die cast aluminium

Paint

Electrostatic powder

Gaskets

Silicone

Diffusers

Tempered Glass

Power LED or COB LEDs

Voltage : 240 VAC with integrated driver (12-24 VDC on request)


Diffuser : Clear Glass 4 mm (Frosted Glass on request)

CRI : >80 or >90


Cable : Potted 1m 3x1 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red




Power	Kelvin	Real Lumen Output	Lens	Code No
6W	2700 K	570 lm	10°,25°,40°	434103
6W	3000 K	570 lm	10°,25°,40°	434101
6W	4000 K	580 lm	10°,25°,40°	434102
6W	6000 K	592 lm	10°,25°,40°	434104
12W	2700 K	1140 lm	10°,25°,40°	434113
12W	3000 K	1140 lm	10°,25°,40°	434111
12W	4000 K	1185 lm	10°,25°,40°	434112
12W	6000 K	1192 lm	10°,25°,40°	434114



Visor
Code No: 953911



Cylinder Visor
Code No: 953912



Honeycomb
Code No: 953931




Picket
Code No: 953901



BELKIS

LED SPOT CLASS I IP 67 IK10

Available in any
of these RAL colors



The Belkis Spot series consists of a range of LED, metal halide, fluorescent and halogen sources to deliver the desired light effect to facades, columns, bridges, monuments, signs, and trees. The series is made of die cast aluminium and painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment (grey, anthracite, black, white, green and beige). The spots can be mounted on surfaces, in the ground or concrete with a picket, or on a pole with the addition of a simple adaptor. Two adaptors are available for two sizes of poles. Once installed, the special joint system allows for 100° horizontal and 180° vertical adjustment. The gearboxes are either filled with cast resin and have a pre-potted cable for IP67, or have a stainless steel cover and cable glands for IP55. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Body

Die cast aluminium

Paint

Electrostatic powder

Gearbox Cover

Stainless steel

Gaskets

Silicone


Diffusers

Tempered Glass



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted to the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

BELKIS MINI

LED SPOT CLASS I IP 67 IK10

Available in any
of these RAL colors




POWER LED or COB LED


- Voltage** : 240V A.C with integrated driver
(12 V-24V AC or DC on request)
- Lens** : 10°, 25°, 40°
- Diffuser** : Clear Glass 8 mm (Frosted Glass on request)
- Cable** : Potted 2 m 3x0,75 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	297104
1W LED	3000 K	95 lm	10°, 25°, 40°	297101
1W LED	4000 K	97 lm	10°, 25°, 40°	297102
1W LED	6000 K	99 lm	10°, 25°, 40°	297103
3W LED	2700 K	285 lm	10°, 25°, 40°	297114
3W LED	3000 K	285 lm	10°, 25°, 40°	297111
3W LED	4000 K	290 lm	10°, 25°, 40°	297112
3W LED	6000 K	296 lm	10°, 25°, 40°	297113




Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	297124
6W LED	3000 K	570 lm	10°, 25°, 40°	297121
6W LED	4000 K	581 lm	10°, 25°, 40°	297122
6W LED	6000 K	592 lm	10°, 25°, 40°	297123

12V - 24V (240V A.C with external driver)



Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	297134
1W LED	3000 K	95 lm	10°, 25°, 40°	297131
1W LED	4000 K	97 lm	10°, 25°, 40°	297132
1W LED	6000 K	112 lm	10°, 25°, 40°	297133
3W LED	2700 K	285 lm	10°, 25°, 40°	297144
3W LED	3000 K	285 lm	10°, 25°, 40°	297141
3W LED	4000 K	290 lm	10°, 25°, 40°	297142
3W LED	6000 K	296 lm	10°, 25°, 40°	297143




Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	297154
6W LED	3000 K	570 lm	10°, 25°, 40°	297151
6W LED	4000 K	581 lm	10°, 25°, 40°	297152
6W LED	6000 K	592 lm	10°, 25°, 40°	297153

12V - 24V (240V A.C with external driver)




**For
Belkis Mini**
Picket
Code No: 953711



Visor
Code No: 953712




Cylinder Visor
Code No: 953713



Honeycomb
Code No: 953714




Clamp
Code No: 953715



BELKIS 1

LED SPOT CLASS I IP 67 IK10

Available in any
of these RAL colors



POWER LED or COB LED

Voltage : 240V A.C with integrated driver
(12 V-24V AC or DC on request)


Lens : 10°, 25°, 40°

Diffuser : Clear Glass 8 mm (Frosted Glass on request)


Cable : Potted 2 m 3x0,75 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red



Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	330212
1W LED	3000 K	95 lm	10°, 25°, 40°	330211
1W LED	4000 K	97 lm	10°, 25°, 40°	330216
1W LED	6000 K	99 lm	10°, 25°, 40°	330217
3W LED	2700 K	285 lm	10°, 25°, 40°	330224
3W LED	3000 K	285 lm	10°, 25°, 40°	330221
3W LED	4500 K	290 lm	10°, 25°, 40°	330222
3W LED	6000 K	296 lm	10°, 25°, 40°	330223




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	330202
1W LED	3000 K	95 lm	10°, 25°, 40°	330201
1W LED	4000 K	97 lm	10°, 25°, 40°	330206
1W LED	6000 K	99 lm	10°, 25°, 40°	330207
3W LED	2700 K	285 lm	10°, 25°, 40°	330254
3W LED	3000 K	285 lm	10°, 25°, 40°	330251
3W LED	4500 K	290 lm	10°, 25°, 40°	330252
3W LED	6000 K	296 lm	10°, 25°, 40°	330253



Power	Lampholder	Reflector	Code No
20W HALOGEN	Gu4	10°, 38°	330121

12V - 24V (240V A.C with external driver)



Power	Lampholder	Reflector	Code No
20W HALOGEN	Gu4	10°, 38°	330101

12V - 24V (240V A.C with external driver)

For
Belkis 1




Picket
Code No: 953805



Visor
Code No: 953531




Cylinder Visor
Code No: 953581



Honeycomb
Code No: 953521




Clamp
Code No: 953715



BELKIS 2

LED SPOT CLASS I IP 67 IK10

Available in any
of these RAL colors




POWER LED or COB LED

- Voltage** : 240V A.C with integrated driver
(12 V-24V AC or DC on request)
- Lens** : 10°, 25°, 40°
- Diffuser** : Clear Glass 8 mm (Frosted Glass on request)
- Cable** : Potted 2 m 3x0,75 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

Power LEDs Driver in Base



Power	Kelvin	Real Lumen Output	Lens	Code No
3W LED	2700 K	285 lm	10°, 25°, 40°	331212
3W LED	3000 K	285 lm	10°, 25°, 40°	331211
3W LED	4000 K	290 lm	10°, 25°, 40°	331216
3W LED	6000 K	296 lm	10°, 25°, 40°	331217
9W LED	2700 K	855 lm	10°, 25°, 40°	331234
9W LED	3000 K	855 lm	10°, 25°, 40°	331231
9W LED	4000 K	872 lm	10°, 25°, 40°	331232
9W LED	6000 K	890 lm	10°, 25°, 40°	331233
9W LED	RGB		25°, 40°	331221


Power LEDs Driver in Head



Power	Kelvin	Real Lumen Output	Lens	Code No
3W LED	2700 K	285 lm	10°, 25°, 40°	331202
3W LED	3000 K	285 lm	10°, 25°, 40°	331201
3W LED	4000 K	290 lm	10°, 25°, 40°	331206
3W LED	6000 K	296 lm	10°, 25°, 40°	331207


12V - 24V (240V A.C with external driver)

COB LED Driver in Base



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 20°, 30°	331243
6W LED	3000 K	570 lm	10°, 20°, 30°	121001
6W LED	4000 K	581 lm	10°, 20°, 30°	121002
6W LED	6000 K	592 lm	10°, 20°, 30°	331244
11W LED	2700 K	1045 lm	10°, 20°, 30°	331253
11W LED	3000 K	1045 lm	10°, 20°, 30°	121011
11W LED	4000 K	1065 lm	10°, 20°, 30°	121012
11W LED	6000 K	1087 lm	10°, 20°, 30°	331254

COB LED Driver in Head



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 20°, 30°	331263
6W LED	3000 K	570 lm	10°, 20°, 30°	121001
6W LED	4000 K	581 lm	10°, 20°, 30°	121002
6W LED	6000 K	592 lm	10°, 20°, 30°	331264

For
Belkis 2




Picket
Code No: 953825



Visor
Code No: 953532



Cylinder Visor
Code No: 953582



Honeycomb
Code No: 953522





Clamp
Code No: 953715



BELKIS 2

HALOGEN SPOTS CLASS I IP 67 IK10

Available in any
of these RAL colors




HALOGEN

Lampholder : Gu 10

Reflector : -


Diffuser : 8 mm Glass

BELKIS 2 WITH SIDE ARM




Power	Lampholder	Reflector	Code No
35W,50W HALOGEN	Gu 10	25°, 50°	331121
12V - 24V (240V A.C with external driver)			

BELKIS 2 WITH CENTRAL ARM



Power	Lampholder	Reflector	Code No
35W,50W HALOGEN	Gu 10	25°, 50°	331141
12V - 24V (240V A.C with external driver)			

HIGH SPOT HALOGEN 240V 35W/50W (25° or 50°) or LED LAMP



Power	Lampholder	Reflector	Code No	
			Single	Twin
35W,50W HALOGEN	Gu 10	25°, 50°	331501	331601
240V A.C				

**For
Belkis 2**




Picket
Code No: 953825



Visor
Code No: 953532



Cylinder Visor
Code No: 953582



Honeycomb
Code No: 953522




Clamp
Code No: 953715



BELKIS 3

LED SPOT CLASS I IP 67 IK10

Available in any
of these RAL colors




POWER LED or COB LED

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)


Lens : 10°, 25°, 40° / (Mirror TIR Lens Options)

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

Cable : Potted 5 m 3x0,75 H03 VV-F




Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°,25°,40°	331312
6W LED	3000 K	570 lm	10°,25°,40°	331311
6W LED	4000 K	581 lm	10°,25°,40°	331316
6W LED	6000 K	592 lm	10°,25°,40°	331317
18W LED	2700 K	1710 lm	10°,25°,40°	331334
18W LED	3000 K	1710 lm	10°,25°,40°	331331
18W LED	4000 K	1744 lm	10°,25°,40°	331332
18W LED	6000 K	1779 lm	10°,25°,40°	331333
18W LED	RGB		10°,25°,40°	331321



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°,25°,40°	331302
6W LED	3000 K	570 lm	10°,25°,40°	331301
6W LED	4500 K	581 lm	10°,25°,40°	331306
6W LED	6000 K	593 lm	10°,25°,40°	331307

TIR LENS



Power	Kelvin	Real Lumen Output	Lens	Code No
12W LED	2700K	1140 lm	10°,20°,30°	331343
12W LED	3000 K	1140 lm	10°,20°,30°	121101
12W LED	4000 K	1162 lm	10°,20°,30°	121102
18W LED	2700K	1710 lm	10°,20°,30°	331353
18W LED	3000 K	1710 lm	10°,20°,30°	121111
18W LED	4000 K	1744 lm	10°,20°,30°	121112



For Belkis 3
Picket
Code No: 953805



Visor
Code No: 953531



Cylinder Visor
Code No: 953583



Honeycomb
Code No: 953523




Clamp
Code No: 953715



BELKIS 4

LED SPOT CLASS I IP 67 IK10

Available in any
of these RAL colors



POWER LED or COB LED


Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Lens : 10°, 25°, 40°

Diffuser : Clear Glass 8 mm (Frosted Glass on request)


Cable : Potted 5 m 3x0,75 H03 VV-F

DRIVER IN BASE




Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	331412
9W LED	3000 K	855 lm	10°, 25°, 40°	331411
9W LED	4500 K	872 lm	10°, 25°, 40°	331416
9W LED	6000 K	890 lm	10°, 25°, 40°	331417
27W LED	2700 K	2560 lm	10°, 25°, 40°	331424
27W LED	3000 K	2560 lm	10°, 25°, 40°	331421
27W LED	4000 K	2610 lm	10°, 25°, 40°	331422
27W LED	6000 K	2670 lm	10°, 25°, 40°	331423

DRIVER IN HEAD



Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	331402
9W LED	3000 K	855 lm	10°, 25°, 40°	331401
9W LED	4000 K	872 lm	10°, 25°, 40°	331406
9W LED	6000 K	890 lm	10°, 25°, 40°	331407
12V - 24V (240V A.C with external driver)				

TIR LENS



Power	Kelvin	Real Lumen Output	Lens	Code No
25W LED	2700 K	2375 lm	10°, 20°, 30°	331701
25W LED	3000 K	2375 lm	10°, 20°, 30°	331702
25W LED	4000 K	2422 lm	10°, 20°, 30°	331703
32W LED	2700 K	3040 lm	10°, 20°, 30°	331711
32W LED	3000 K	3040 lm	10°, 20°, 30°	331712
32W LED	4000 K	3100 lm	10°, 20°, 30°	331713

**For
Belkis 4**




Picket
Code No: 953805



Visor
Code No: 953531




Cylinder Visor
Code No: 953584



Honeycomb
Code No: 953524




Clamp
Code No: 953715



BELKIS 5

LED SPOT CLASS I IP 67 IK10


Available in any
of these RAL colors



POWER LED or COB LED


- Voltage** : 240V A.C with integrated driver
(24V AC or DC on request)
- Lens** : 10°, 25°, 40°
- Diffuser** : Clear Glass 8 mm (Frosted Glass on request)
- Cable** : Potted 5 m 3x0,75 H03 VV-F

DRIVER IN BASE




Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	425632
9W LED	3000 K	855 lm	10°, 25°, 40°	425631
9W LED	4500 K	872 lm	10°, 25°, 40°	425636
9W LED	6000 K	890 lm	10°, 25°, 40°	425637
27W LED	2700 K	2560 lm	10°, 25°, 40°	425652
27W LED	3000 K	2560 lm	10°, 25°, 40°	425651
27W LED	4500 K	2670 lm	10°, 25°, 40°	425653
27W LED	RGB		10°, 25°, 40°	425641

DRIVER IN HEAD



Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	425612
9W LED	3000 K	855 lm	10°, 25°, 40°	425611
9W LED	4500 K	872 lm	10°, 25°, 40°	425616
9W LED	6000 K	890 lm	10°, 25°, 40°	425617

For
Belkis 5



Picket
Code No: 953805



Visor
Code No: 953531



Cylinder Visor
Code No: 953585



Honeycomb
Code No: 953525




Clamp
Code No: 953715

BELKIS 5

HALOGEN SPOT CLASS I IP 67 IK10

Available in any
of these RAL colors




HALOGEN

Lampholder : E27

Reflector : -


Diffuser : 8 mm Clear Glass

WITH SIDE ARM




Power	Lampholder	Reflector	Code No
PAR 30 75W	E27	10°, 30°	332121
12V - 24V (240V A.C with external driver)			

WITH CENTRAL ARM



Power	Lampholder	Reflector	Code No
PAR 30 75W	E27	10°, 30°	332131
12V - 24V (240V A.C with external driver)			


For
Belkis 5



Picket
Code No: 953805



Visor
Code No: 953531




Cylinder Visor
Code No: 953585



Honeycomb
Code No: 953525




Clamp
Code No: 953715



BELKIS 5

SPOTS CLASS I IP 67 IK10

Available in any
of these RAL colors



Compact Fluoro



Metal Halide



With Gearbox

HALOGEN


Lampholder : Gx 53, PGJ 5, G 8.5

Diffuser : 8 mm Clear Glass

Gear : Electronic (in lamp)


Cable : Potted 5 m 3x0,75
H05 VV-F

SIDE ARM




Power	Lampholder	Code No
11W COMPACT FLUO AR111	Gx 53	332141
12V - 24V (240V A.C with external driver)		

CENTRAL METAL HALIDE




Power	Lampholder	Reflector	Code No
METAL HALIDE 20W	PGJ 5	25°	332151
12V - 24V (240V A.C with external driver)			

WITH GEARBOX



Power	Lampholder	Reflector	Code No
35W METAL HALIDE HALOGEN	PGJ 5	9°, 17°, 25°	332181
70W METAL HALIDE HALOGEN	PGJ 5	9°, 17°, 25°	332191
35W METAL HALIDE CDMR-111 HALOGEN	PGJ 5	9°, 17°, 25°	332201
70W METAL HALIDE CDMR-111 HALOGEN	PGJ 5	9°, 17°, 25°	332211
12V - 24V (240V A.C with external driver)			

WITH GEARBOX



Power	Lampholder	Reflector	Code No
35W METAL HALIDE HALOGEN	G 8.5	9°, 17°, 25°	332221
70W METAL HALIDE HALOGEN	G 8.5	9°, 17°, 25°	332231
35W METAL HALIDE CDMR-111 HALOGEN	G 8.5	9°, 17°, 25°	332241
70W METAL HALIDE CDMR-111 HALOGEN	G 8.5	9°, 17°, 25°	332251
12V - 24V (240V A.C with external driver)			

**For
Belkis 5**




Picket
Code No: 953805



Visor
Code No: 953531



Cylinder Visor
Code No: 953585



Honeycomb
Code No: 953525




Clamp
Code No: 953715



BELKIS 6

SPOTS WITH GEARBOX CLASS I IP 67 IK10

Available in any
of these RAL colors




HALOGEN

Lampholder : G12


Reflector : 30°, 42°

Diffuser : Clear Glass

Gear : Electronic



Power	Lampholder	Reflector	Code No
35W METAL HALIDE HALOGEN	G12	30°, 42°	138201
70W METAL HALIDE HALOGEN	G12	30°, 42°	138211
12V - 24V (240V A.C with external driver)			



Power	Lampholder	Reflector	Code No
150W METAL HALIDE HALOGEN	G12	30°, 42°	138221
12V - 24V (240V A.C with external driver)			


**For
Belkis 6**




Picket
Code No: 953805



Visor
Code No: 953531



Cylinder Visor
Code No: 953586



Honeycomb
Code No: 953525




Clamp
Code No: 953715



RESPOT 3

SPOTS WITH RECESSED GEARBOX CLASS I IP 67 IK10

Available in any
of these RAL colors




HALOGEN


Lampholder : G12, Gx8.5

Reflector : 30°, 42°

Diffuser : Clear Glass



Power	Lampholder	Reflector	Code No
35W METAL HALIDE HALOGEN	G12	30°, 42°	137101
70W METAL HALIDE HALOGEN	G12	30°, 42°	137111
12V - 24V (240V A.C with external driver)			



Power	Lampholder	Code No
35W METAL HALIDE CDM-R111 HALOGEN	Gx8.5	137121
70W METAL HALIDE CDM-R111 HALOGEN	Gx8.5	137131
12V - 24V (240V A.C with external driver)		



**For
RESPOT 3**

Clamp
Code No: 953715



Visor
Code No: 953536

 Bollards



EMFA

BÉTON



LED BOLLARDS

Class I IP67 IK10

Exposed concrete is the preferred material of architects for cutting edge designs. Our BÉTON bollard is made of heavy duty concrete with an incredibly smooth finish. The BÉTON can blend into the architecture of a building and mature together with its surroundings. The simple form of the BÉTON is emphasized with the light that comes out from the solid structure..


Asymmetrical

Led	: Linear LEDs
Voltage	: 240 VAC with integrated driver (12-24 VDC on request)
Diffuser	: 4mm Tempered Glass
Beam Angle	: 45° / 60° / 90°
Mac Adam	: 3
CRI	: >80
L.O.R %	: %70



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.



Power	Kelvin	Real Lumen Output	Lens	Code No
6W	2700 K	570 lm	45°, 60°, 90°	190003
6W	3000 K	570 lm	45°, 60°, 90°	190001
6W	4500 K	581 lm	45°, 60°, 90°	190002
12W	2700 K	1162 lm	45°, 60°, 90°	190013
12W	3000 K	1162 lm	45°, 60°, 90°	190011
12W	4500 K	1140 lm	45°, 60°, 90°	190012




For
BETON

Anchor
Code No: 953591

KIBIRA

LED BOLLARDS IP65

Available in any
of these RAL colors



Cover

Die cast aluminium

Body

Die cast aluminium
die cast aluminium bottom and connection box.

Gaskets

Silicone

Diffusers

4 mm Tempered Glass (Aluminium Cover)

Screws

316L Stainless steel

Glands

2 x PG 13.5

Recessing Tube

Polyamide 6




POWER LED


Led : LEDs (1W or 3W)

Voltage : 240 VAC with External driver
(12-24 VDC on request)

Diffuser : >80




600mm




Power	Kelvin	Code No		
		Single	Triple	Quinet
1W	2700 K	191003	192003	193003
1W	3000 K	191001	192001	193001
1W	4000 K	191002	192002	193002
3W	2700 K	191013	192013	193013
3W	3000 K	191011	192011	193011
3W	4000 K	191012	192012	193012

800mm




Power	Kelvin	Code No		
		Single	Triple	Quinet
1W	2700 K	191103	192103	193103
1W	3000 K	191101	192101	193101
1W	4000 K	191102	192102	193102
3W	2700 K	191113	192113	193113
3W	3000 K	191111	192111	193111
3W	4000 K	191112	192112	193112

1000mm



Power	Kelvin	Code No		
		Single	Triple	Quinet
1W	2700 K	191203	192203	193203
1W	3000 K	191201	192201	193201
1W	4000 K	191202	192202	193202
3W	2700 K	191213	192213	193213
3W	3000 K	191211	192211	193211
3W	4000 K	191212	192212	193212




For KIBIRA **Recessing Tube**
Internal Driver
Code No: 953631



KIZIKOS

LED BOLLARDS IP65

Available in any
of these RAL colors



Head

Die cast aluminium

Diffusers

Acrylic

Pipe

Stainless steel

Paint


Electrostatic powder

POWER LED


Led : LEDs (1W or 3W)

Voltage : 240 VAC with External driver
(12-24 VDC on request)

Diffuser : >80




600mm




Power	Kelvin	Code No
1W	2700 K	194003
1W	3000 K	194001
1W	4000 K	194002
3W	2700 K	194013
3W	3000 K	194011
3W	4000 K	194012

800mm



Power	Kelvin	Code No
1W	2700 K	194103
1W	3000 K	194101
1W	4000 K	194102
3W	2700 K	194113
3W	3000 K	194111
3W	4000 K	194112

1000mm



Power	Kelvin	Code No
1W	2700 K	194203
1W	3000 K	194201
1W	4000 K	194202
3W	2700 K	194213
3W	3000 K	194211
3W	4000 K	194212



ODEON

BOLLARD

Class I IP67 IK10

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

EMFA's Odean Bollard combines a die-cast aluminium head housing an LED unit with an extrusion aluminium pipe. The bollard is designed to light pathways, landscapes and open spaces. The unit comes with 5 different options of heads depending on much light is required and into which direction: with one head, two adjacent heads, two opposite heads, three heads, or four heads. The head and pipe are connected by a hidden screw within the pipe. One head contains 20 medium-power LEDs consuming 6W and providing over 500lm light output. An optional galvanized steel anchorage kit is available for mounting into concrete. An alternative option is sleeve anchors for mounting onto existing concrete or a picket to mount into the earth.

Head

Die cast aluminium

Diffusers


Frosted polyamide 6.6

Pipe

Extrusion aluminium

Paint

Electrostatic powder



“Customization” is EMFA's standard


EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.


LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.






POWER LED or COB LED


- Led** : Medium power LEDs
Voltage : 240 VAC with integrated driver
 (12-24 VDC on request)
Diffuser : Polyamide 6.6




Mono




Power	Kelvin	Code No
6W	2700 K	178103
6W	3000 K	178101
6W	4000 K	178102




Duo 1-way



Power	Kelvin	Code No
12W	2700 K	178113
12W	3000 K	178111
12W	4000 K	178112




Duo 2-way



Power	Kelvin	Code No
12W	2700 K	178123
12W	3000 K	178121
12W	4000 K	178122




Trio



Power	Kelvin	Code No
18W	2700 K	178133
18W	3000 K	178131
18W	4000 K	178132



Muilti



Power	Kelvin	Code No
24W	2700 K	178143
24W	3000 K	178141
24W	4000 K	178142




LEON

LED BOLLARD

Class I IP65

Available in any
of these RAL colors



EMFA's Leon Bollard combines a die-cast aluminium head housing an LED unit with an extrusion aluminium pipe. The bollard is designed to light pathways, landscapes and open spaces. The Leon bollard gives light only in the downward direction. This avoids any kind of glare and light pollution. The head and pipe are connected by a hidden screw within the pipe. The head contains LEDs that can be powered up to 12W. An optional galvanized steel anchorage kit is available for mounting into concrete. An alternative option is sleeve anchors for mounting onto existing concrete or a picket to mount into the earth.

Head

Die cast aluminium

Diffusers

Frosted polyamide 6.6

Pipe

Extrusion aluminium

Paint

Electrostatic powder

CIRCULAR LED


Led : Circular LEDs (6W or 12W)

Voltage : 240 VAC with integrated driver
(12-24 VDC on request)

CRI : >80




350mm




Power	Kelvin	Lumen Output	Code No
6W	2700 K	570 lm	177003
6W	3000 K	570 lm	177001
6W	4000 K	581 lm	177002
12W	2700 K	1140 lm	177013
12W	3000 K	1140 lm	177011
12W	4000 K	1162 lm	177012

500mm




Power	Kelvin	Lumen Output	Code No
6W	2700 K	570 lm	177103
6W	3000 K	570 lm	177101
6W	4000 K	581 lm	177102
12W	2700 K	1140 lm	177113
12W	3000 K	1140 lm	177111
12W	4000 K	1162 lm	177112

700mm



Power	Kelvin	Lumen Output	Code No
6W	2700 K	570 lm	177203
6W	3000 K	570 lm	177201
6W	4000 K	581 lm	177202
12W	2700 K	1140 lm	177213
12W	3000 K	1140 lm	177211
12W	4000 K	1162 lm	177212






LEON 2

LED BOLLARD Fixed & Adjustable Class I IP65

Available in any
of these RAL colors



Head

Die cast aluminium

Diffusers

Frosted polyamide 6.6

Pipe

316L Stainless Steel

Paint

Electrostatic powder

CIRCULAR LED

Led : Circular LEDs (6W or 12W)

Voltage : 12-24V External Driver
(12-24 VDC on request)

CRI : >80



Fixed




Adjustable


350mm



Fixed



Adjustable



Power	Kelvin	Lumen Output	Fixed	Adjustable
6W	2700 K	720 lm	270003	270103
6W	3000 K	720 lm	270001	270101
6W	4000 K	790 lm	270002	270102
12W	2700 K	1380 lm	270013	270113
12W	3000 K	1380 lm	270011	270111
12W	4000 K	1380lm	270012	270112


500mm



Fixed



Adjustable




Power	Kelvin	Lumen Output	Fixed	Adjustable
6W	2700 K	720 lm	271003	271103
6W	3000 K	720 lm	271001	271101
6W	4000 K	790 lm	271002	271102
12W	2700 K	1380 lm	271013	271113
12W	3000 K	1380 lm	271011	271111
12W	4000 K	1380lm	271012	271112


700mm




Fixed



Adjustable



Power	Kelvin	Lumen Output	Fixed	Adjustable
6W	2700 K	720 lm	272003	272103
6W	3000 K	720 lm	272001	272101
6W	4000 K	790 lm	272002	272102
12W	2700 K	1380 lm	272013	272113
12W	3000 K	1380 lm	272011	272111
12W	4000 K	1380lm	272012	272112



For LEON 2
Recessing Tube
Internal Driver
Code No: 953641




Picket
External Driver
Code No: 953642



LEON 3

LED ACRYLIC BOLLARD Fixed & Adjustable Class I IP65

Available in any
of these RAL colors



Head

Die cast aluminium

Diffusers

Frosted polyamide 6.6

Pipe

316L Stainless Steel

Paint

Electrostatic powder

CIRCULAR LED

Led : Circular LEDs (6W or 12W)

Voltage : 12-24V External Driver
(12-24 VDC on request)

CRI : >80




Fixed



Adjustable


350mm



Fixed




Adjustable



Power	Kelvin	Lumen Output	Fixed	Adjustable
6W	2700 K	720 lm	275003	275103
6W	3000 K	720 lm	275001	275101
6W	4000 K	790 lm	275002	275102


500mm



Fixed




Adjustable



Power	Kelvin	Lumen Output	Fixed	Adjustable
6W	2700 K	720 lm	276003	276103
6W	3000 K	720 lm	276001	276101
6W	4000 K	790 lm	276002	276102


700mm




Fixed



Adjustable



Power	Kelvin	Lumen Output	Fixed	Adjustable
6W	2700 K	720 lm	277003	277103
6W	3000 K	720 lm	277001	277101
6W	4000 K	790 lm	277002	277102



For
LEON 3

Recessing Tube
Internal Driver
Code No: 953641




Picket
External Driver
Code No: 953642

DION

WALL AND GROUND BOLLARDS

Class I IP65 IK10

Available in any
of these RAL colors



EMFA's Dion series combines a die-cast aluminium head with an extrusion aluminium pipe to provide a sturdy, outdoor bollard. The bollards are designed to light pathways, landscapes and open spaces. The unit comes with 5 different heads for various light outputs and applications. A screwless bayonet lock system allows for easy dismantling of the head. The unit comes in 4 sizes: 300mm, 450mm, 700mm, and 1100mm, as well as with 3 lamp options: LED, Fluorescent, Metal Halide. In combination with the fluorescent lamp, an optional LED pilot lamp is available to light the bollard when the primary light source is off to continue marking a path while saving energy. An optional galvanized steel anchorage kit is available for mounting into concrete. An alternative option is sleeve anchors for mounting onto existing concrete.

Head

Die cast aluminium
With Screwless lock system
(Electrical lock on request)

Outer Asymmetrical Grill

Die cast aluminium

Diffuser

Clear polycarbonate

Pipe

Extrusion aluminium

Paint

Electrostatic powder



Accessories:


2 x Leds Pilot Lamps

Lit when main Light Source is turned off.
Available in:

Code No 956101 - Blue
Code No 956102 - Red
Code No 956103 - Yellow
Code No 956104 - Green

Code Number should be indicated along with
bollard code number

Anchor



DION 1



DION 2



DION 3



DION 4




DION 5





DION LED BOLLARDS IP65


Available in any
of these RAL colors



LINEAR LED, HALOGEN or FLUO


Led : Medium power LEDs
Voltage : 240 VAC with integrated driver
(12-24 VDC on request)
Diffuser : Polyamide 6.6

DION 1




Power	30 cm	45 cm	70 cm	110 cm
FLUO 10W	143101			
ELECTRONIC FLUO 23W		143201	143301	143401
FLUO 26W		143211	143311	143411
METAL HALIDE 35W		143221	143321	143421
LINEAR LED 12W		143231	143341	143331

DION 2




Power	30 cm	45 cm	70 cm	110 cm
FLUO 10W	144101			
ELECTRONIC FLUO 23W		144201	144301	144401
FLUO 26W		144211	144311	144411
METAL HALIDE 35W		144221	144321	144421
LINEAR LED 12W		144231	144341	144331

DION 3




Power	30 cm	45 cm	70 cm	110 cm
FLUO 10W	145101			
ELECTRONIC FLUO 23W		145201	145301	145401
FLUO 26W		145211	145311	145411
METAL HALIDE 35W		145221	145321	145421
LINEAR LED 12W		145231	145341	145331

DION 4




Power	30 cm	45 cm	70 cm	110 cm
FLUO 10W	146101			
ELECTRONIC FLUO 23W		146201	146301	146401
FLUO 26W		146211	146311	146411
LINEAR LED 12W		146231	146341	146331

DION 5



Power	30 cm	45 cm	70 cm	110 cm
FLUO 10W	147101			
ELECTRONIC FLUO 23W		147201	147301	147401
FLUO 26W		147211	147311	147411
LINEAR LED 12W		147221	147341	147331



For
DION **Anchor**
Code No: 955201



MILET

BOLLARD

Class I IP65 IK08

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

The Milet Indirect series consists of an on-wall fixture and a bollard using LED, halogen or fluorescent. The fixtures are made of a combination of a die cast aluminium head and an aluminium pipe painted with electrostatic powder paint. The wall fixture allows for a custom made sign showing room numbers or names. For the LED versions, a specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. For the halogen and fluorescent versions, an IP connection box is provided to allow for a secure connection of the on-site cable.

Cover

Die cast aluminium

Paint

Black or grey electrostatic powder

Pipe

Extrusion aluminium

Connection

IP connection box

Gaskets

Silicone

Diffusers

Polycarbonate

DOM LED, HALOGEN or FLUO

Voltage : 240V A.C with integrated driver (24V AC or DC on request)

Lampholder : G9, Gx53


Lens : 40°

Diffuser : Polycarbonate

Cable : Potted 5 m 3x0,75 H03 VV-F




DOM LED




Power	Lens	Kelvin	300mm	550mm
11W	40°	3000K	291121	291221

HALOGEN



Power	Lens	Lampholder	300mm	550mm
40W	40°	G9	291101	291201

ELECTRONIC CICALAR FLUO




Power	Lampholder	Lens	300mm	550mm
6W	Gx53	40°	291111	291211

BELLA

LED BOLLARDS

Class I IP65 IK08

Available in any
of these RAL colors



Head

Die cast aluminium

Diffuser

Tempered Glass 4 mm

Pipe

Extrusion aluminium

Base

Polyamide (black color)

Paint

Electrostatic powder

LINEAR LEDs


Voltage : 240V AC with integrated driver
(12V DC or 24V DC on request)

Diffuser : Clear Glass 4 mm

Cable : Potted 5 m 3x0,75 H03 VV-F




ONE WAY ASYMMETRICAL




Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	380 lm	149103
3W	3000 K	387 lm	149101
3W	5000 K	416 lm	149102

TWO WAY ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	380 lm	149113
3W	3000 K	387 lm	149111
3W	5000 K	416 lm	149112

TWO WAY ASYMMETRICAL + SYMMETRICAL




Power	Kelvin	Real Lumen Output	Code No
3W	2700 K	380 lm	149123
3W	3000 K	387 lm	149121
3W	5000 K	416 lm	149122

ANI 1

ALUM LED BOLLARDS

Class I IP55 IK08

Available in any of these RAL colors



EMFA's Ani Bollard combines a die-cast aluminium head housing an LED unit with an extrusion aluminium pipe. The bollard is designed to light pathways, landscapes and open spaces. The Ani bollard gives light only in the downward direction. This avoids any kind of glare and light pollution. The head and pipe are connected by a hidden screw within the pipe. The head contains LEDs that can be powered up to 12W. An optional galvanized steel anchorage kit is available for mounting into concrete. An alternative option is sleeve anchors for mounting onto existing concrete or a picket to mount into the earth.

Profile

Aluminium

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

4 mm Tempered Glass

Screws

316L Stainless steel

Glands

PG 11

LINEAR LEDs

Led : Linear LEDs

Voltage : 240 VAC with integrated driver
(12-24 VDC on request)


Diffuser : 4mm Tempered Glass

Beam Angle : 45° / 60° / 90°


Mac Adam : 3

CRI : >80


L.O.R % : %70



Clear Glass




SYMMETRICAL



Power	Kelvin	Real Lumen Output	Beam Angle	450 mm	700 mm	1100 mm
6W	2700 K	570 lm	45° / 60° / 90°	452003	452103	452203
6W	3000 K	570 lm	45° / 60° / 90°	452001	452101	452201
6W	4000 K	581 lm	45° / 60° / 90°	452002	452102	452202
12W	2700 K	1140 lm	45° / 60° / 90°	452013	452113	452213
12W	3000 K	1140 lm	45° / 60° / 90°	452011	452111	452211
12W	4000 K	1162 lm	45° / 60° / 90°	452012	452112	452212

ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Beam Angle	450 mm	700 mm	1100 mm
6W	2700 K	570 lm	45° / 60° / 90°	452503	452603	452703
6W	3000 K	570 lm	45° / 60° / 90°	452501	452601	452701
6W	4000 K	581 lm	45° / 60° / 90°	452502	452602	452702
12W	2700 K	1140 lm	45° / 60° / 90°	452513	452613	452713
12W	3000 K	1140 lm	45° / 60° / 90°	452511	452611	452711
12W	4000 K	1162 lm	45° / 60° / 90°	452512	452612	452712



ANI 4

ALUM LED BOLLARDS

Class I IP55 IK08

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

Profile

Aluminium

Body

Die cast aluminium

Gaskets

Silicone

Diffusers


4 mm Tempered Glass

Screws

316L Stainless steel

Glands

PG 11



Asym. Glass



Trenched Glass



Milky Glass



Clear Glass



LINEAR LEDs

Led : Linear LEDs

Voltage : 240 VAC with integrated driver
(12-24 VDC on request)


Diffuser : 4mm Tempered Glass

Beam Angle : 45° / 60° / 90°


Mac Adam : 3

CRI : >80

L.O.R % : %70




SYMMETRICAL



Power	Kelvin	Real Lumen Output	Beam Angle	450 mm	700 mm	1100 mm
24W	2700 K	2280 lm	45° / 60° / 90°	459003	459103	459203
24W	3000 K	2280 lm	45° / 60° / 90°	459001	459101	459201
24W	4000 K	2320 lm	45° / 60° / 90°	459002	459102	459202
36W	2700 K	3420 lm	45° / 60° / 90°	459013	459113	459213
36W	3000 K	3420 lm	45° / 60° / 90°	459011	459111	459211
36W	4000 K	3520 lm	45° / 60° / 90°	459012	459112	459212

ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Beam Angle	450 mm	700 mm	1100 mm
24W	2700 K	2280 lm	45° / 60° / 90°	459503	459603	459703
24W	3000 K	2280 lm	45° / 60° / 90°	459501	459601	459701
24W	4000 K	2320 lm	45° / 60° / 90°	459502	459602	459702
36W	2700 K	3420 lm	45° / 60° / 90°	459513	459613	459713
36W	3000 K	3420 lm	45° / 60° / 90°	459511	459611	459711
36W	4000 K	3520 lm	45° / 60° / 90°	459512	459612	459712




L TYPE

LED BOLLARDS

Class I IP65

Available in any
of these RAL colors



3W or 6W COB LED

Head

Die cast aluminium

Diffuser

Tempered Glass 4 mm

Pipe

Extrusion aluminium

Base

Die cast aluminium

Paint

Electrostatic powder

COB LED


Voltage : 240V AC with integrated driver
(12V DC or 24V DC on request)

Diffuser : Clear Glass 4 mm

Cable : Potted 5 m 3x0,75 H03 VV-F



COB LED BOLLARDS



Power	Kelvin	Real Lumen Output	40 cm	80 cm
3W COB LED	2700 K	380 lm	125003	125201
3W COB LED	3000 K	387 lm	125001	125202
3W COB LED	5000 K	416 lm	125002	125203
6W COB LED	2700 K	570 lm	125011	125103
6W COB LED	3000 K	570 lm	125012	125101
6W COB LED	5000 K	612 lm	125013	125102

LARA

ACRYLIC BOLLARDS
Class I IP55

Available in any
of these RAL colors

7004

7016



9005

9016

6002

1015

FLUO
LARA (35/60cm)
Lampholder : G24 q-1
Reflector : -
Diffuser : Acrylic Pipe
Transformer : Electronic




Power	Lampholder	35 cm	60 cm
COMPACT FLUO 13W	G24 q-1	294101	294201

POLARIS

ALUMINIUM BOLLARDS Class I IP43 IK10

Available in any
of these RAL colors



FLUO

Bottom Base

Polyamide (black color)

Outer Grill

Die cast aluminium

Pipe

Extrusion aluminium


Paint

Electrostatic powder


Diffuser

Polycarbonate or

Glass (incandescent and mercury lamps)




POLARIS 1




Power	Lampholder	45 cm	70 cm	1100 cm
60W	E27	124101	124201	124301
80W	E27	124111	124211	124311
23W	E27	124121	124221	124321
26W	G24 d-3	124131	124231	124331

POLARIS 2




Power	Lampholder	45 cm	70 cm	1100 cm
23W	E27	126101	126201	126301
26W	G24 d-3	126111	126211	126311

For
POLARIS 1 Anchor



Code No: 953611

For
POLARIS 2 Anchor



Code No: 953621



BELKIS

BOLLARDS (600 mm)
Class I IP55

Available in any
of these RAL colors

7004

7016

9005

9016

6002

1015

FLUO

Lampholder : G24 q-1


Reflector : -

Diffuser : Acrylic Pipe

Transformer : Electronic




600mm




Power	Lampholder	Code No
13W COMPACT FLUO	G24 q-1	292201

1100mm



Power	Lampholder	Code No
26W COMPACT FLUO	G24 d-3	292301





Bottom Base

Polyamide (black color)

Inner Grill

Polycarbonate

Pipe

Extrusion aluminium

Paint

Electrostatic powder

Diffuser

Polycarbonate

Anchor


LINEAR LED

Voltage : 240V AC with integrated driver
(24V AC or DC on request)

Cable : Potted 5 m 3x0,75 H03 VV-F




GOREME 1



Power	Kelvin	Real Lumen Output	45 cm	70 cm	110 cm
12W	2700 K	1140 lm	127003	127103	127203
12W	3000 K	1140 lm	127001	127101	127201
12W	4000 K	1162 lm	127002	127102	127202
24W	2700 K	2280 lm	127013	127113	127213
24W	3000 K	2280 lm	127011	127111	127211
24W	4000 K	2320 lm	127012	127112	127212

GOREME 2




Power	Kelvin	Real Lumen Output	45 cm	70 cm	110 cm
12W	2700 K	1140 lm	127503	127603	127703
12W	3000 K	1140 lm	127501	127601	127701
12W	4000 K	1162 lm	127502	127602	127702
24W	2700 K	2280 lm	127513	127613	127713
24W	3000 K	2280 lm	127511	127611	127711
24W	4000 K	2320 lm	127512	127612	127712



BOW

GARDEN FIXTURE Class I IP44 IK10

Available in any
of these RAL colors



Body

Glass reinforced
polyester

Diffuser

Acrylic

Reflector

Anodized aluminium

Bracket

Stainless Steel




LINEAR LED or FLUO

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)


Cable : Potted 5 m 3x0,75 H03 VV-F

LINEAR LED



Power	Kelvin	Lumen Output	Code No
2x3W	2700 K	570 lm	129122
2x3W	3000 K	570 lm	129121

FLUO




Power	Lampholder	Code No
13W	G24 d-1	129101
18W	G24 d-2	129111



RAMBO

VANDALPROOF BOLLARD Class I IP65 IK10

Available in any
of these RAL colors



Head

Die cast aluminium

Pipe

Steel

Paint


Electrostatic powder paint

Diffuser

Polycarbonate

Anchor


Die cast iron




LINEAR LED, HALOGEN or FLUO

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Cable : Potted 5 m 3x0,75 H03 VV-F



Power	Lampholder	Code No
INCANDESCENT 100W	27	128101
MERCURY 80W	27	128111
ELECTRONIC FLUO 23W	27	128121
FLUO 26W	27	128131




Power	Kelvin	Lumen Output	Code No
LINEAR LED 12W	2700 K	1400 lm	128142
LINEAR LED 12W	3000 K	1400 lm	128141



MUSHROOM

GARDEN FIXTURE Class I IP67 IK10

Available in any
of these RAL colors



HALOGEN

Top Cover

Aluminium

Inner Body

Die cast aluminium


Diffuser

Tempered Glass

Gaskets


Silicone

Lampholder : Gu1



Power	Lampholder	Code No
HALOGEN 50W	Gu10	129501

For
Mushroom



Picket
Code No: 953501



 Stainless Steel
Underwater



EMFA

ATLANTIS

UNDERWATER LED FIXTURES

Class III IP68 IK10

The Atlantis Underwater series is specially designed to light pools, fountains and water features with high power LED light. The series is made of 316L stainless steel to withstand salt water and chlorine. Standard finish is polished stainless steel to avoid collection of dirt and algae, but a brushed finish is also possible. The series comes as recessed, surface mount or spots. The spots are heavy duty with stainless steel brackets for sturdy fixing. The bodies are filled with cast resin and a specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The low voltage electronic LED driver is housed in the base of the fixture. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber or RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired light effect.

Frame

316L Stainless Steel

Body

316L Stainless Steel

Recessing Tube

Aluminium

Gaskets

Silicone

Diffusers


Tempered Glass

Screws

Stainless Steel


Mounting Brackets

316L Stainless Steel



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



ATLANTIS 5




ATLANTIS 2



MIRA ATLANTIS RECESSED



ATLANTIS 2



INOX 1




MIRA ATLANTIS SURFACE MOUNTED

LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.



ATLANTIS UNDERWATER RECESSED LED FIXTURES

Class III IP68 IK10




Power LEDs

Voltage : 12V AC or DC (24V AC or DC on request)
Lens : 10°, 25°, 40°
Diffuser : 8 mm Clear Glass (Frosted Glass on request)
Cable : Potted 5 m 2x0,75 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

ATLANTIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	421102	421112
1W LED	3000 K	95 lm	10°, 25°, 40°	421101	421111
1W LED	4500 K	97 lm	10°, 25°, 40°	421106	421116
1W LED	6000 K	99 lm	10°, 25°, 40°	421107	421117
3W LED	2700 K	285 lm	10°, 25°, 40°	421204	421214
3W LED	3000 K	285 lm	10°, 25°, 40°	421201	421211
3W LED	4500 K	290 lm	10°, 25°, 40°	421202	421212
3W LED	6000 K	296 lm	10°, 25°, 40°	421203	421213

ATLANTIS 2



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	421122	421132
3W LED	3000 K	285 lm	10°, 25°, 40°	421121	421131
3W LED	4500 K	290 lm	10°, 25°, 40°	421126	421136
3W LED	6000 K	296 lm	10°, 25°, 40°	421127	421137
9W LED	2700 K	855 lm	10°, 25°, 40°	421304	421314
9W LED	3000 K	855 lm	10°, 25°, 40°	421301	421311
9W LED	4500 K	872 lm	10°, 25°, 40°	421302	421312
9W LED	6000 K	890 lm	10°, 25°, 40°	421303	421313
9W LED	RGB		10°, 25°, 40°	421141	421151

ATLANTIS 5



Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	405322	405332
9W LED	3000 K	855 lm	10°, 25°, 40°	405321	405331
9W LED	4500 K	872 lm	10°, 25°, 40°	405326	405336
9W LED	6000 K	890 lm	10°, 25°, 40°	405327	405337
27W LED	2700 K	2560 lm	10°, 25°, 40°	421824	421834
27W LED	3000 K	2560 lm	10°, 25°, 40°	421821	421831
27W LED	4500 K	2610 lm	10°, 25°, 40°	421822	421832
27W LED	6000 K	2670 lm	10°, 25°, 40°	421823	421833
27W LED	RGB		10°, 25°, 40°	405341	405351

ATLANTIS 27

SWIMMING POOL LED FIXTURE Class III IP68 IK10

Body

316L Stainless Steel Pipe

Frame

4 mm Polished Stainless Steel

Screws

316L Stainless Steel

Diffuser

8 mm Clear Glass

Gasket

Silicone

Remote Gear Box

240 VAC Class I

Control by DMX, remote control or push button




Voltage : 12V AC or DC (24V AC or DC on request)

Lens : 10°, 25°, 40°

Diffuser : 8 mm Clear Glass (Frosted Glass on request)


Cable : Potted 10 m 4x0,75 H03 VV-F



CODE NO 953702

SLIM IP 65 CONTROL BOX (For Max. 1 RGBox)


GLASS REINFORCED POLYESTER BODY



CODE NO 953703

WIDE IP 65 CONTROL BOX (For Max. 3 RGBoxes)

GLASS REINFORCED POLYESTER BODY



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	405472
6W LED	3000 K	570 lm	10°, 25°, 40°	405471
6W LED	4500 K	581 lm	10°, 25°, 40°	405476
6W LED	6000 K	593 lm	10°, 25°, 40°	405477
9W LED	2700 K	855 lm	10°, 25°, 40°	405482
9W LED	3000 K	855 lm	10°, 25°, 40°	405481
9W LED	4500 K	872 lm	10°, 25°, 40°	405486
9W LED	6000 K	890 lm	10°, 25°, 40°	405487
18W LED	2700 K	1710 lm	10°, 25°, 40°	421704
18W LED	3000 K	1710 lm	10°, 25°, 40°	421701
18W LED	4500 K	1744 lm	10°, 25°, 40°	421702
18W LED	6000 K	1779 lm	10°, 25°, 40°	421703
27W LED	2700 K	2560 lm	10°, 25°, 40°	421714
27W LED	3000 K	2560 lm	10°, 25°, 40°	421711
27W LED	4500 K	2610 lm	10°, 25°, 40°	421712
27W LED	6000 K	2670 lm	10°, 25°, 40°	421713
27W LED	RGB		10°, 25°, 40°	425311



ATLANTIS UNDERWATER SURFACE MOUNTED LED FIXTURES

Class III IP68 IK10

ATLANTIS 1



ATLANTIS 2



POWER LED

Voltage : 12V AC or DC (24V AC or DC on request)

Lens : 10°, 25°, 40°

Diffuser : 8 mm Clear Glass (Frosted Glass on request)

Cable : Potted 5 m 2x0,75 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red


ATLANTIS 5



ATLANTIS 5




ATLANTIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	405362
1W LED	3000 K	95 lm	10°, 25°, 40°	405361
1W LED	4500 K	97 lm	10°, 25°, 40°	405366
1W LED	6000 K	99 lm	10°, 25°, 40°	405367
3W LED	2700 K	285 lm	10°, 25°, 40°	421324
3W LED	3000 K	285 lm	10°, 25°, 40°	421321
3W LED	4500 K	290 lm	10°, 25°, 40°	421322
3W LED	6000 K	296 lm	10°, 25°, 40°	421323

ATLANTIS 2



Power	Kelvin	Real Lumen Output	Lens	Code No
3W LED	2700 K	285 lm	10°, 25°, 40°	405372
3W LED	3000 K	285 lm	10°, 25°, 40°	405371
3W LED	4500 K	255 lm	10°, 25°, 40°	405376
3W LED	6000 K	296 lm	10°, 25°, 40°	405377
9W LED	2700 K	855 lm	10°, 25°, 40°	421334
9W LED	3000 K	855 lm	10°, 25°, 40°	421331
9W LED	4500 K	872 lm	10°, 25°, 40°	421332
9W LED	6000 K	890 lm	10°, 25°, 40°	421333
9W LED	RGB		10°, 25°, 40°	405201

ATLANTIS 5



Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	405392
9W LED	3000 K	855 lm	10°, 25°, 40°	405391
9W LED	4500 K	872 lm	10°, 25°, 40°	405396
9W LED	6000 K	890 lm	10°, 25°, 40°	405397
27W LED	2700 K	2560 lm	10°, 25°, 40°	421854
27W LED	3000 K	2560 lm	10°, 25°, 40°	421851
27W LED	4500 K	2610 lm	10°, 25°, 40°	421852
27W LED	6000 K	2670 lm	10°, 25°, 40°	421853
27W LED	RGB		10°, 25°, 40°	405411

ATLANTIS

UNDERWATER LED SPOT

Class III IP68 IK10

ATLANTIS 1



ATLANTIS 2



POWER LED

Voltage : 12V AC or DC (24V AC or DC on request)

Lens : 10°, 25°, 40°


Diffuser : 8 mm Clear Glass (Frosted Glass on request)

Cable : Potted 5 m 2x0,75 H03 VV-F

ATLANTIS 5




ATLANTIS 5



Single color LED options upon request are ;


Blue Amber Green Red

ATLANTIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	405422
1W LED	3000 K	95 lm	10°, 25°, 40°	405421
1W LED	4500 K	97 lm	10°, 25°, 40°	405426
1W LED	6000 K	99 lm	10°, 25°, 40°	405427
3W LED	2700 K	285 lm	10°, 25°, 40°	405244
3W LED	3000 K	285 lm	10°, 25°, 40°	405241
3W LED	4500 K	290 lm	10°, 25°, 40°	405242
3W LED	6000 K	296 lm	10°, 25°, 40°	405243

ATLANTIS 2



Power	Kelvin	Real Lumen Output	Lens	Code No
3W LED	2700 K	285 lm	10°, 25°, 40°	405254
3W LED	3000 K	285 lm	10°, 25°, 40°	405251
3W LED	4500 K	290 lm	10°, 25°, 40°	405252
3W LED	6000 K	396 lm	10°, 25°, 40°	405253
9W LED	2700 K	855 lm	10°, 25°, 40°	421344
9W LED	3000 K	855 lm	10°, 25°, 40°	421341
9W LED	4500 K	872 lm	10°, 25°, 40°	421342
9W LED	6000 K	890 lm	10°, 25°, 40°	421343
9W LED	RGB	RGB	10°, 25°, 40°	405431

ATLANTIS 5



Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	405452
9W LED	3000 K	855 lm	10°, 25°, 40°	405451
9W LED	4500 K	872 lm	10°, 25°, 40°	405456
9W LED	6000 K	890 lm	10°, 25°, 40°	405457
27W LED	2700 K	2560 lm	10°, 25°, 40°	421874
27W LED	3000 K	2560 lm	10°, 25°, 40°	421871
27W LED	4500 K	2610 lm	10°, 25°, 40°	421872
27W LED	6000 K	2670 lm	10°, 25°, 40°	421873
27W LED	RGB	RGB	10°, 25°, 40°	405461

INOX 1 UNDERWATER RECESSED

Class III IP68

EMFA's Inox 1 Underwater spot is completely made of solid 316L stainless steel to withstand salt water and chlorine. The spot is specially designed to light fountains and water features. A special factory sealed cable is used to avoid any ingress of water. Standard finish is polished stainless steel to avoid collection of dirt and algae, but a brushed finish is also possible.

Body

316L marine grade stainless steel

Frame

316L marine grade stainless steel

Diffuser

Tempered Glass

Gaskets

Silicone

Screws

316L marine grade stainless steel

Gland

316L Inox Recessing Tube

HALOGEN


Lampholder : Gu 5.3

Reflector : -


Diffuser : 8 mm Tempered Glass

Transformer is not included.

Remote transformer should be used.




STEP MOUNTED




Power	Lampholder	Code No	
		Round	Square
50W HALOGEN	Gu 5.3	134211	134201

FLUSH MOUNTED



Power	Lampholder	Code No
50W HALOGEN	Gu 5.3	134221

SPOT



Power	Lampholder	Code No
50W HALOGEN	Gu 5.3	134101

MIRA ATLANTIS

UNDERWATER RECESSED LED FIXTURES

Class III IP68 IK10

The Mira Atlantis Underwater series brings together the rectangular LED fixture called Mira with the underwater feature of the Atlantis. Engineered completely from marine grade stainless steel, 316L, this range is designed to light pools, fountains and water features with efficient LED lighting. Standard finish is polished stainless steel to avoid collection of dirt and algae, but a brushed finish is also available on request. The series comes as recessed or surface mount. The surface mounted version has heavy-duty stainless steel adjustable brackets for sturdy fixing. The bodies are filled with cast resin and a specially developed potted power cable is used to effectively bond with the cast resin and stop any water ingress. The low voltage electronic LED driver is housed in the base of the fixture. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber or RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired underwater the light effect.

Cover

316L Stainless steel

Outer Body

316L Stainless steel

Body

Die cast aluminium

Diffusers

12 mm Tempered Glass

Gaskets

Silicone

Screws



316L Stainless steel

Recessing Box

Stainless steel

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50 °C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

MIRA ATLANTIS

UNDERWATER RECESSED LED FIXTURES

Class III IP68 IK10



POWER LED


Voltage : 24V AC or DC

Lens : 10°, 25°, 40°

Diffuser : Clear Glass 12 mm (Frosted Glass on request)


Cable : Potted 5 m 2x0,75 H03 VV-F

MIRA ATLANTIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No
12W	2700 K	1140 lm	10°, 25°, 40°	429004
12W	3000 K	1140 lm	10°, 25°, 40°	429001
12W	4500 K	1162 lm	10°, 25°, 40°	429002
12W	6000 K	1185 lm	10°, 25°, 40°	429003
12W	RGB		10°, 25°, 40°	429011

MIRA ATLANTIS 2 15°+15°+0° ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Lens	Code No
12W LED	2700 K	1140 lm	10°, 25°, 40°	429044
12W LED	3000 K	1140 lm	10°, 25°, 40°	429041
12W LED	4500 K	1162 lm	10°, 25°, 40°	429042
12W LED	6000 K	1185 lm	10°, 25°, 40°	429043
12W LED	RGB		10°, 25°, 40°	429051

MIRA ATLANTIS 2 15°+15°+0° ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Lens	Code No
36W LED	2700 K	3420 lm	10°, 25°, 40°	429064
36W LED	3000 K	3420 lm	10°, 25°, 40°	429061
36W LED	4500 K	3520 lm	10°, 25°, 40°	429062
36W LED	6000 K	3930 lm	10°, 25°, 40°	429063
36W LED	RGB		10°, 25°, 40°	429071

MIRA ATLANTIS

UNDERWATER SURFACE MOUNTED LED FIXTURES


Class III IP68 IK10



POWER LED


Voltage : 24V AC or DC
Lens : 10°, 25°, 40°
Diffuser : Clear Glass 12 mm (Frosted Glass on request)
Cable : Potted 5 m 2x0,75 H03 VV-F

MIRA ATLANTIS 1 SURFACE MOUNTED




Power	Kelvin	Real Lumen Output	Lens	Code No
12W LED	2700 K	1140 lm	10°, 25°, 40°	429024
12W LED	3000 K	1140 lm	10°, 25°, 40°	429021
12W LED	4500 K	1162 lm	10°, 25°, 40°	429022
12W LED	6000 K	1185 lm	10°, 25°, 40°	429023
12W LED	RGB		10°, 25°, 40°	429031

MIRA ATLANTIS 2 SURFACE MOUNTED



Power	Kelvin	Real Lumen Output	Lens	Code No
36W LED	2700 K	3420 lm	10°, 25°, 40°	429084
36W LED	3000 K	3420 lm	10°, 25°, 40°	429081
36W LED	4500 K	3520 lm	10°, 25°, 40°	429082
36W LED	6000 K	3930 lm	10°, 25°, 40°	429083
36W LED	RGB		10°, 25°, 40°	429091



 Stainless Steel
Outdoor



EMFA

ATLANTIS

NEARWATER LED FIXTURES

Class III IP67 IK10

The Atlantis Near Water series is specially designed to light objects around pools, fountains, and water features or near the sea with high power LED light. The series is made of solid 316L stainless steel and can therefore withstand these rough environments. Standard finish is polished stainless steel to avoid collection of dirt and algae, but a brushed finish is also possible. The series comes as recessed, surface mount or spots. The spots are heavy duty with stainless steel brackets for sturdy fixing. A specially developed power cable ensures for a long lifetime in extreme conditions without any ingress of water. The low voltage electronic LED driver is housed in the base of the fixture. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber or RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Frame

316L Stainless Steel

Body

316L Stainless Steel

Recessing Tube

Aluminium

Gaskets

Silicone

Diffusers

Tempered Glass

Screws


Stainless Steel

Mounting Brackets

316L Stainless Steel

“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 finishes of stainless steel, 8 LED colors, 2 wattages, and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.




LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted to the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.



ATLANTIS

NEARWATER LED FIXTURES


Class III IP67 IK10



POWER LED


Voltage : 12V AC or DC (24V AC or DC on request)
Lens : 10°, 25°, 40°
Diffuser : 8 mm Clear Glass (Frosted Glass on request)
Cable : Potted 5 m 2x0,75 H03 VV-F

ATLANTIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No	
				Round	Square
1W LED	2700 K	95 lm	10°, 25°, 40°	412102	412112
1W LED	3000 K	95 lm	10°, 25°, 40°	412101	412111
1W LED	4500 K	97 lm	10°, 25°, 40°	412106	412116
1W LED	6000 K	99 lm	10°, 25°, 40°	412107	412117
3W LED	2700 K	285 lm	10°, 25°, 40°	412124	412134
3W LED	3000 K	285 lm	10°, 25°, 40°	412121	412131
3W LED	4500 K	290 lm	10°, 25°, 40°	412122	412132
3W LED	6000 K	296 lm	10°, 25°, 40°	412123	412133

ATLANTIS 2



Power	Kelvin	Lumen Output	Lens	Code No	
				Round	Square
3W LED	2700 K	285 lm	10°, 25°, 40°	412122	412132
3W LED	3000 K	285 lm	10°, 25°, 40°	412121	412131
3W LED	4500 K	255 lm	10°, 25°, 40°	412126	412136
3W LED	6000 K	306 lm	10°, 25°, 40°	412127	412137
9W LED	2700 K	855 lm	10°, 25°, 40°	412134	412136
9W LED	3000 K	855 lm	10°, 25°, 40°	412135	412136
9W LED	4500 K	872 lm	10°, 25°, 40°	412132	412136
9W LED	6000 K	890 lm	10°, 25°, 40°	412133	412136
9W LED	RGB	RGB	10°, 25°, 40°	412141	412151

ATLANTIS 5



Power	Kelvin	Lumen Output	Lens	Code No	
				Round	Square
9W LED	2700 K	855 lm	10°, 25°, 40°	412182	412192
9W LED	3000 K	855 lm	10°, 25°, 40°	412181	412191
9W LED	4500 K	872 lm	10°, 25°, 40°	412186	412196
9W LED	6000 K	890 lm	10°, 25°, 40°	412187	412197
27W LED	2700 K	2560 lm	10°, 25°, 40°	412194	412194
27W LED	3000 K	2560 lm	10°, 25°, 40°	412191	412191
27W LED	4500 K	2610 lm	10°, 25°, 40°	412192	412192
27W LED	6000 K	2670 lm	10°, 25°, 40°	412193	412193
27W LED	RGB	RGB	10°, 25°, 40°	412201	412211

ATLANTIS

NEARWATER SURFACE MOUNTED LED FIXTURES

Class III IP67 IK10




POWER LED

Voltage : 12V AC or DC (24V AC or DC on request)
Lens : 10°, 25°, 40°
Diffuser : 8 mm Clear Glass (Frosted Glass on request)
Cable : Potted 5 m 2x0,75 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

ATLANTIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	412222
1W LED	3000 K	95 lm	10°, 25°, 40°	412221
1W LED	4500 K	97 lm	10°, 25°, 40°	412226
1W LED	6000 K	99 lm	10°, 25°, 40°	412227
3W LED	2700 K	285 lm	10°, 25°, 40°	421244
3W LED	3000 K	285 lm	10°, 25°, 40°	421241
3W LED	4500 K	290 lm	10°, 25°, 40°	421242
3W LED	6000 K	296 lm	10°, 25°, 40°	421243

ATLANTIS 2




Power	Kelvin	Lumen Output	Lens	Code No
3W LED	2700 K	285 lm	10°, 25°, 40°	412232
3W LED	3000 K	285 lm	10°, 25°, 40°	412231
3W LED	4500 K	290 lm	10°, 25°, 40°	412236
3W LED	6000 K	296 lm	10°, 25°, 40°	412237
9W LED	2700 K	855 lm	10°, 25°, 40°	421374
9W LED	3000 K	855 lm	10°, 25°, 40°	421371
9W LED	4500 K	872 lm	10°, 25°, 40°	421372
9W LED	6000 K	890 lm	10°, 25°, 40°	421373
9W LED	RGB			412241

ATLANTIS 5



Power	Kelvin	Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	412252
6W LED	3000 K	570 lm	10°, 25°, 40°	412251
6W LED	4500 K	581 lm	10°, 25°, 40°	412256
6W LED	6000 K	593 lm	10°, 25°, 40°	412257
18W LED	2700 K	1710 lm	10°, 25°, 40°	421934
18W LED	3000 K	1710 lm	10°, 25°, 40°	421931
18W LED	4500 K	1744 lm	10°, 25°, 40°	421932
18W LED	6000 K	1779 lm	10°, 25°, 40°	421933

ATLANTIS 5



Power	Lens	Code No
9W LED 40V DC	RGB 25°, 40°	412271

ATLANTIS

NEARWATER SURFACE MOUNTED LED FIXTURES Class III IP67 IK10




POWER LED

- Voltage** : 12V AC or DC (24V AC or DC on request)
Lens : 10°, 25°, 40°
Diffuser : 8 mm Clear Glass (Frosted Glass on request)
Cable : Potted 5 m 2x0,75 H03 VV-F


Single color LED options upon request are ;
Blue Amber Green Red

ATLANTIS 1



Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	412282
1W LED	3000 K	95 lm	10°, 25°, 40°	412281
1W LED	4500 K	97 lm	10°, 25°, 40°	412286
1W LED	6000 K	99 lm	10°, 25°, 40°	412287
3W LED	2700 K	285 lm	10°, 25°, 40°	421254
3W LED	3000 K	285 lm	10°, 25°, 40°	421251
3W LED	4500 K	290 lm	10°, 25°, 40°	421252
3W LED	6000 K	296 lm	10°, 25°, 40°	421253

ATLANTIS 1




Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	10°, 25°, 40°	421264
1W LED	3000 K	95 lm	10°, 25°, 40°	421261
1W LED	4500 K	97 lm	10°, 25°, 40°	421262
1W LED	6000 K	99 lm	10°, 25°, 40°	421263
3W LED	2700 K	285 lm	10°, 25°, 40°	421374
3W LED	3000 K	285 lm	10°, 25°, 40°	421371
3W LED	4500 K	290 lm	10°, 25°, 40°	421372
3W LED	6000 K	296 lm	10°, 25°, 40°	421373

ATLANTIS

NEARWATER LED SPOT

Class III IP67 IK10



POWER LED

Voltage : 12V AC or DC (24V AC or DC on request)

Lens : 10°, 25°, 40°


Diffuser : 8 mm Clear Glass (Frosted Glass on request)

Cable : Potted 5 m 2x0,75 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

ATLANTIS 2 NEAR WATER LED SPOT




Power	Kelvin	Real Lumen Output	Lens	Code No
3W LED	2700 K	285 lm	10°, 25°, 40°	412292
3W LED	3000 K	285 lm	10°, 25°, 40°	412291
3W LED	4500 K	290 lm	10°, 25°, 40°	412296
3W LED	6000 K	296 lm	10°, 25°, 40°	412297
9W LED	2700 K	872 lm	10°, 25°, 40°	421384
9W LED	3000 K	872 lm	10°, 25°, 40°	421381
9W LED	4500 K	872 lm	10°, 25°, 40°	421382
9W LED	6000 K	890 lm	10°, 25°, 40°	421383
9W LED	RGB	Red, Green, Blue	10°, 25°, 40°	412301

ATLANTIS 1 NEAR WATER LED SPOT



Power	Kelvin	Real Lumen Output	Lens	Code No
3W LED	2700 K	285 lm	10°, 25°, 40°	421394
3W LED	3000 K	285 lm	10°, 25°, 40°	421391
3W LED	4500 K	290 lm	10°, 25°, 40°	421392
3W LED	6000 K	296 lm	10°, 25°, 40°	421393
9W LED	2700 K	872 lm	10°, 25°, 40°	421404
9W LED	3000 K	872 lm	10°, 25°, 40°	421401
9W LED	4500 K	872 lm	10°, 25°, 40°	421402
9W LED	6000 K	890 lm	10°, 25°, 40°	421403
9W LED	RGB	Red, Green, Blue	10°, 25°, 40°	412411

ATLANTIS 3



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	421504
6W LED	3000 K	570 lm	10°, 25°, 40°	421501
6W LED	4500 K	510 lm	10°, 25°, 40°	421502
6W LED	6000 K	593 lm	10°, 25°, 40°	421503
18W LED	2700 K	1710 lm	10°, 25°, 40°	421514
18W LED	3000 K	1710 lm	10°, 25°, 40°	421511
18W LED	4500 K	1744 lm	10°, 25°, 40°	421512
18W LED	6000 K	1779 lm	10°, 25°, 40°	421513

ATLANTIS

NEARWATER LED SPOT

Class III IP67 IK10




POWER LED

Voltage : 12V AC or DC (24V AC or DC on request)
Lens : 10°, 25°, 40°
Diffuser : 8 mm Clear Glass (Frosted Glass on request)
Cable : Potted 5 m 2x0,75 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

ATLANTIS 4




Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	421604
6W LED	3000 K	570 lm	10°, 25°, 40°	421601
6W LED	4500 K	581 lm	10°, 25°, 40°	421602
6W LED	6000 K	593 lm	10°, 25°, 40°	421603
18W LED	2700 K	765 lm	10°, 25°, 40°	421614
18W LED	3000 K	1710 lm	10°, 25°, 40°	421611
18W LED	4500 K	1744 lm	10°, 25°, 40°	421612
18W LED	6000 K	1779 lm	10°, 25°, 40°	421613

ATLANTIS 5 NEAR WATER LED SPOT



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	412312
6W LED	3000 K	570 lm	10°, 25°, 40°	412311
6W LED	4500 K	581 lm	10°, 25°, 40°	412316
6W LED	6000 K	593 lm	10°, 25°, 40°	412317
18W LED	2700 K	765 lm	10°, 25°, 40°	421964
18W LED	3000 K	1710 lm	10°, 25°, 40°	421961
18W LED	4500 K	1744 lm	10°, 25°, 40°	421962
18W LED	6000 K	1779 lm	10°, 25°, 40°	421963

ATLANTIS 5 NEAR WATER LED SPOT




Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	412322
9W LED	3000 K	855 lm	10°, 25°, 40°	412321
9W LED	4500 K	872 lm	10°, 25°, 40°	412326
9W LED	6000 K	890 lm	10°, 25°, 40°	412327
27W LED	2700 K	2560 lm	10°, 25°, 40°	421954
27W LED	3000 K	2560 lm	10°, 25°, 40°	421951
27W LED	4500 K	2610 lm	10°, 25°, 40°	421952
27W LED	6000 K	2670 lm	10°, 25°, 40°	421953
27W LED	RGB		10°, 25°, 40°	412331

ATLANTIS

NEARWATER LED SPOT

Class III IP67 IK10




POWER LED

Voltage : 12V AC or DC (24V AC or DC on request)
Lens : 10°, 25°, 40°
Diffuser : 8 mm Clear Glass (Frosted Glass on request)
Cable : Potted 5 m 2x0,75 H03 VV-F

Single color LED options upon request are ;


Blue Amber Green Red

ATLANTIS 5 NEAR WATER LED SPOT



Power	Kelvin	Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°, 25°, 40°	412342
6W LED	3000 K	570 lm	10°, 25°, 40°	412341
6W LED	4500 K	581 lm	10°, 25°, 40°	412346
6W LED	6000 K	593 lm	10°, 25°, 40°	412347
18W LED	2700 K	765 lm	10°, 25°, 40°	421974
18W LED	3000 K	1710 lm	10°, 25°, 40°	421971
18W LED	4500 K	1744 lm	10°, 25°, 40°	421972
18W LED	6000 K	1779 lm	10°, 25°, 40°	421973

ATLANTIS 5 NEAR WATER LED SPOT



Power	Kelvin	Real Lumen Output	Lens	Code No
9W LED	2700 K	855 lm	10°, 25°, 40°	412352
9W LED	3000 K	855 lm	10°, 25°, 40°	412351
9W LED	4500 K	872 lm	10°, 25°, 40°	412356
9W LED	6000 K	890 lm	10°, 25°, 40°	412357
27W LED	2700 K	2560 lm	10°, 25°, 40°	421984
27W LED	3000 K	2560 lm	10°, 25°, 40°	421981
27W LED	4500 K	2610 lm	10°, 25°, 40°	421982
27W LED	6000 K	2670 lm	10°, 25°, 40°	421983
27W LED	RGB		10°, 25°, 40°	412361

ATLANTIS


MARINE BOLLARD Class I IP65 IK08



HALOGEN or LINEAR LED


Head : 316L Stainless Steel
Diffuser : Clear Polycarbonate
Pipe : 316L Stainless Steel
Isolation Belt : Polycarbonate
Finish : Polished or Brushed

POLISHED




Power	45 cm	70 cm	1100 cm
LINEAR LED 4W	409001	409101	409201

POLISHED




Power	Lampholder	45 cm	70 cm	110 cm
ELECTRONIC FLUO 23W	E27	409011	409111	409211
FLUO 26W	G24 q-3	409021	409121	409221

BRUSHED




Power	45 cm	70 cm	110 cm
LINEAR LED 4W	410001	410101	410201

BRUSHED



Power	Lampholder	45 cm	70 cm	110 cm
ELECTRONIC FLUO 23W	E27	410001	410111	410211
FLUO 26W	G24 q-3	410011	410121	410221



For
ATLANTIS

Anchor
Code No: 955201



INOX

LED APPLIQUES

Class I IP65 IK08

The Inox Applique series consists of a range of LED, metal halide and halogen sources to deliver the desired light effect to facades and columns. The series is made of die cast aluminium and extrusion aluminium painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.

Pipe

316L Stainless Steel

Body

316L Stainless Steel

Cover

316L Stainless Steel

Finish

Polished

Diffusers


Tempered Glass

Gaskets

Silicone


Connection

IP connection box



“Customization” is EMFA’s standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors and 5 or more lenses and reflectors are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.


Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA’s laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

INOX

ONE WAY LED APPLIQUES

Class I IP65 IK08




CREE COB LED

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Lens : 24° / 36° / 60°


Cable : Potted 5 m 3x0,75 H03 VV-F

INOX 1




Power	Kelvin	Lens	Code No
6W LED	2700 K	24°,36°,60°	135003
6W LED	3000 K	24°,36°,60°	135001
6W LED	4000 K	24°,36°,60°	135002
20W LED	2700 K	24°,36°,60°	135013
20W LED	3000 K	24°,36°,60°	135011
20W LED	4000 K	24°,36°,60°	135012

INOX 2



Power	Kelvin	Lens	Code No
6W LED	2700 K	24°,36°,60°	135023
6W LED	3000 K	24°,36°,60°	135021
6W LED	4000 K	24°,36°,60°	135022
20W LED	2700 K	24°,36°,60°	135033
20W LED	3000 K	24°,36°,60°	135031
20W LED	4000 K	24°,36°,60°	135032

INOX 3



Power	Kelvin	Lens	Code No
6W LED	2700 K	24°,36°,60°	135043
6W LED	3000 K	24°,36°,60°	135041
6W LED	4000 K	24°,36°,60°	135042
20W LED	2700 K	24°,36°,60°	135053
20W LED	3000 K	24°,36°,60°	135051
20W LED	4000 K	24°,36°,60°	135052

INOX


ONE WAY LED APPLIQUES

Class I IP65 IK08




CREE COB LED
Voltage : 240V A.C with integrated driver
 (24V AC or DC on request)
Lens : 24° / 36° / 60°
Cable : Potted 5 m 3x0,75 H03 VV-F

INOX 1



Power	Kelvin	Lens	Code No
6W LED	4000 K	24°,36°,60°	135203
6W LED	3000 K	24°,36°,60°	135201
6W LED	4000 K	24°,36°,60°	135202
20W LED	3000 K	24°,36°,60°	135213
20W LED	3000 K	24°,36°,60°	135211
20W LED	4000 K	24°,36°,60°	135212


INOX 2



Power	Kelvin	Lens	Code No
6W LED	4000 K	24°,36°,60°	135223
6W LED	3000 K	24°,36°,60°	135221
6W LED	4000 K	24°,36°,60°	135222
20W LED	3000 K	24°,36°,60°	135233
20W LED	3000 K	24°,36°,60°	135231
20W LED	4000 K	24°,36°,60°	135232

INOX TWO WAY LED APPLIQUES

Class I IP65 IK08




CREE COB LED

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)

Lens : 24° / 36° / 60°


Cable : Potted 5 m 3x0,75 H03 VV-F

INOX 1




Power	Kelvin	Lens	Code No
6W LED	2700 K	24°,36°,60°	135103
6W LED	3000 K	24°,36°,60°	135101
6W LED	4000 K	24°,36°,60°	135102
20W LED	2700 K	24°,36°,60°	135113
20W LED	3000 K	24°,36°,60°	135111
20W LED	4000 K	24°,36°,60°	135112

INOX 2



Power	Kelvin	Lens	Code No
4W LED	2700 K	24°,36°,60°	135123
4W LED	3000 K	24°,36°,60°	135121
4W LED	4000 K	24°,36°,60°	135122
15W LED	2700 K	24°,36°,60°	135133
15W LED	3000 K	24°,36°,60°	135131
15W LED	4000 K	24°,36°,60°	135132

INOX 3



Power	Kelvin	Lens	Code No
4W LED	2700 K	24°,36°,60°	135143
4W LED	3000 K	24°,36°,60°	135141
4W LED	4000 K	24°,36°,60°	135142
15W LED	2700 K	24°,36°,60°	135153
15W LED	3000 K	24°,36°,60°	135151
15W LED	4000 K	24°,36°,60°	135152

INOX


TWO WAY LED APPLIQUES

Class I IP65 IK08




CREE COB LED
Voltage : 240V A.C with integrated driver
 (24V AC or DC on request)
Lens : 24° / 36° / 60°
Cable : Potted 5 m 3x0,75 H03 VV-F

INOX 1



Power	Kelvin	Lens	Polished	Brushed
4W or 15W LED	2700 K	24°,36°,60°	135303	135313
4W or 15W LED	3000 K	24°,36°,60°	135301	135311
4W or 15W LED	4000 K	24°,36°,60°	135302	135312

INOX 2



Power	Kelvin	Lens	Polished	Brushed
4W or 15W LED	3000 K	24°,36°,60°	135323	135333
4W or 15W LED	3000 K	24°,36°,60°	135321	135331
4W or 15W LED	4000 K	24°,36°,60°	135322	135332

INOX

SURFACE MOUNTED CEILING FIXTURES

Class I IP65 IK08

The Inox surface series consists of a range of LED, metal halide and halogen sources to deliver the desired light effect to facades and columns. The series is made of die cast aluminium and extrusion aluminium painted with electrostatic powder paint. 6 standard RAL colors can be chosen from to adapt the spots to their environment. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 6 to 40 degrees are available to choose from to achieve the desired the light effect.




Body : 316L Stainless Steel
Cover : 316L Stainless Steel
Diffuser : Tempered Glass
Pipe : 316L Stainless Steel
Isolation Belt : Polycarbonate
Finish : Polished
Gaskets : Silicone
Connection : IP connection box

CREE COB LED


Voltage : 240V A.C with integrated driver
 (24V AC or DC on request)
Lens : 24° / 36° / 60°
Cable : Potted 5 m 3x0,75 H03 VV-F

INOX 1




Power	Kelvin	Lens	Polished	Brushed
15W or 20W LED	2700 K	24°, 36°, 60°	136003	136013
15W or 20W LED	3000 K	24°, 36°, 60°	136001	136011
15W or 20W LED	4000 K	24°, 36°, 60°	136002	136012

INOX 2



Power	Kelvin	Lens	Polished	Brushed
15W or 20W LED	2700 K	24°, 36°, 60°	136023	136033
15W or 20W LED	3000 K	24°, 36°, 60°	136021	136031
15W or 20W LED	4000 K	24°, 36°, 60°	136022	136032

Downlights



EMFA

PINARA

LINEAR LED DOWNLIGHT

Class II IP20

Available in any
of these RAL colors



The PINARA LED downlight is specially designed to deliver high output LED light with very clean beam angles to corridors, hotel rooms, museums and general lighting of public spaces. The Nichia LEDs in the PINARA are very efficient and have a high CRI (90). The unique lens that is used in this fixture creates very sharp beams that minimize the spill of uncontrolled light from the fixture. This reduces the glare of the fixture and gives more control to the architects and designers.

Body

Polycarbonate

Heatsink

Aluminium extrusion profile

Diffuser

With clear or frosted tempered glass, without glass

Springs

Steel

Cable

0.5 m exiting top of fixture

Gear



Non-Dimmable electronic LED driver (1-10V Dimmable and DALI drivers available on request)

Application

Symmetrical and asymmetrical lighting for general lighting such as museums, hospitals, hotel rooms, dormitories, corridors, shops, and balconies.

"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 2 standard paint colors, 2 white tones, 2 wattages are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.




LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.



PINARA

LINEAR LED DOWNLIGHT

Class II IP20

Available in any
of these RAL colors



POWER LED

Led : 350 - 500 - 700 mA (Nichia)


Gear : 240V Non-Dimmable Driver
(1-10V Dimmable Driver and
DALI Driver available on request)

Diffuser

Clear or frosted tempered Glass


Cable : 0.5 m 2x0,75 mm H03 VV-F

PINARA 1 CLEAR OR FROSTED TEMPERED GLASS




Power	Kelvin	Real Lumen Output	Code No
10W LED	2700 K	950 lm	392001
10W LED	3000 K	950 lm	392002
10W LED	4000 K	968 lm	392003
15W LED	2700 K	1425 lm	392011
15W LED	3000 K	1425 lm	392012
15W LED	4000 K	1453 lm	392013
21W LED	2700 K	1995 lm	392021
21W LED	3000 K	1995 lm	392022
21W LED	4000 K	2053 lm	392023

PINARA 2 SYMMETRICAL



Power	Kelvin	Real Lumen Output	Code No
10W LED	2700 K	950 lm	392101
10W LED	3000 K	950 lm	392102
10W LED	4000 K	968 lm	392103
15W LED	2700 K	1425 lm	392111
15W LED	3000 K	1425 lm	392112
15W LED	4000 K	1453 lm	392113
21W LED	2700 K	1995 lm	392121
21W LED	3000 K	1995 lm	392122
21W LED	4000 K	2053 lm	392123

PINARA 2 ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Code No
10W LED	2700 K	950 lm	392201
10W LED	3000 K	950 lm	392202
10W LED	4000 K	968 lm	392203
15W LED	2700 K	1425 lm	392211
15W LED	3000 K	1425 lm	392212
15W LED	4000 K	1453 lm	392213
21W LED	2700 K	1995 lm	392221
21W LED	3000 K	1995 lm	392222
21W LED	4000 K	2053 lm	392223

PINARA

LINEAR LED DOWNLIGHT

Class II IP20

Available in any
of these RAL colors



POWER LED

Led : 350 - 500 - 700 mA (Nichia)

Diffuser


Clear or frosted tempered Glass

Gear : 240V Non-Dimmable Driver
(1-10V Dimmable Driver and

DALI Driver available on request)


Cable : 0.5 m 2x0,75 mm H03 VV-F

PINARA SYMMETRICAL TRIMLESS



Power	Kelvin	Real Lumen Output	Code No
10W LED	2700 K	950 lm	393001
10W LED	3000 K	950 lm	393002
10W LED	4000 K	968 lm	393003
15W LED	2700 K	1425 lm	393011
15W LED	3000 K	1425 lm	393012
15W LED	4000 K	1453 lm	393013
21W LED	2700 K	1995 lm	393021
21W LED	3000 K	1995 lm	393022
21W LED	4000 K	2053 lm	393023

PINARA ASYMMETRICAL TRIMLESS



Power	Kelvin	Real Lumen Output	Code No
10W LED	2700 K	950 lm	393101
10W LED	3000 K	950 lm	393102
10W LED	4000 K	968 lm	393103
15W LED	2700 K	1425 lm	393111
15W LED	3000 K	1425 lm	393112
15W LED	4000 K	1453 lm	393113
21W LED	2700 K	1995 lm	393121
21W LED	3000 K	1995 lm	393122
21W LED	4000 K	2053 lm	393123

HARPUT

LED DOWNLIGHT

Class II IP65/20


Available in any
of these RAL colors



The Harput LED downlight is specially designed to deliver high output LED light with very clean beam angles to corridors, hotel rooms, museums and general lighting of public spaces. The LEDs used in the HARPUT are very efficient and have a high CRI (90). The unique lens that is used in this fixture creates very sharp beams that minimize the spill of uncontrolled light from the fixture. This reduces the glare of the fixture and gives more control to the architects and designers

Body : Aluminium
Heatsink : Aluminium
Diffuser : With clear or frosted tempered glass
Springs : Steel
Cable : 0.5 m exiting top of fixture
Gear : 240V Non-Dimmable electronic LED driver
 (1-10V Dimmable and DALI drivers
 available on request)


MINI



Fixed

Adjustable


HARPUT 2



Fixed

Adjustable


HARPUT 3



Fixed

Adjustable

HARPUT 4



Fixed


Adjustable

Application

Symmetrical and asymmetrical lighting for general lighting such as museums, hospitals, hotel rooms, dormitories, corridors, shops, and balconies.



BEAM ANGLE



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum

lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management


All fixtures are designed to withstand ambient temperatures of at least 50 mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.

HARPOT MINI

LED DOWNLIGHT

Class II IP20

Available in any
of these RAL colors



1W or 3W COB LED

Led : 6W or 12W COB LED


Reflector : 15°, 24°, 38° or 60°

Gear : 240V

(1-10V Dimmable Driver & DALI Driver available on request)


Cable : 0,5 m 2x0,75 mm H03 VV-F

FIXED




Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	230003
1W LED	3000 K	95 lm	230001
1W LED	4000 K	97 lm	230002
3W LED	2700 K	285 lm	230013
3W LED	3000 K	285 lm	230011
3W LED	4000 K	387 lm	230012

ADJUSTABLE




Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	230103
1W LED	3000 K	95 lm	230101
1W LED	4000 K	97 lm	230102
3W LED	2700 K	285 lm	230113
3W LED	3000 K	285 lm	230111
3W LED	4000 K	387 lm	230112

FIXED TRIMLESS



Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	234003
1W LED	3000 K	95 lm	234001
1W LED	4000 K	97 lm	234002
3W LED	2700 K	285 lm	234013
3W LED	3000 K	285 lm	234011
3W LED	4000 K	387 lm	234012

ADJUSTABLE TRIMLESS




Power	Kelvin	Real Lumen Output	Code No
1W LED	2700 K	95 lm	234103
1W LED	3000 K	95 lm	234101
1W LED	4000 K	97 lm	234102
3W LED	2700 K	285 lm	234113
3W LED	3000 K	285 lm	234111
3W LED	4000 K	387 lm	234112

HARPUR 2 LED DOWNLIGHT

Class II IP65

Available in any
of these RAL colors



6W or 12W COB LED

Led : 6W or 12W COB LED


Reflector : 15°, 24°, 38° or 60°

Gear : 240V

(1-10V Dimmable Driver & DALI Driver available on request)


Cable : 0,5 m 2x0,75 mm H03 VV-F

FIXED




Power	Kelvin	Real Lumen Output	Code No
6W LED	2700 K	570 lm	231003
6W LED	3000 K	570 lm	231001
6W LED	4000 K	581 lm	231002
12W LED	2700 K	1140 lm	231013
12W LED	3000 K	1140 lm	231011
12W LED	4000 K	1162 lm	231012

ADJUSTABLE




Power	Kelvin	Real Lumen Output	Code No
6W LED	2700 K	570 lm	231103
6W LED	3000 K	570 lm	231101
6W LED	4000 K	581 lm	231102
12W LED	2700 K	1140 lm	231113
12W LED	3000 K	1140 lm	231111
12W LED	4000 K	1162 lm	231112

FIXED TRIMLESS



Power	Kelvin	Real Lumen Output	Code No
6W LED	2700 K	570 lm	235003
6W LED	3000 K	570 lm	235001
6W LED	4000 K	581 lm	235002
12W LED	2700 K	1140 lm	235013
12W LED	3000 K	1140 lm	235011
12W LED	4000 K	1162 lm	235012

ADJUSTABLE TRIMLESS



Power	Kelvin	Real Lumen Output	Code No
6W LED	2700 K	570 lm	235103
6W LED	3000 K	570 lm	235101
6W LED	4000 K	581 lm	235102
12W LED	2700 K	1140 lm	235113
12W LED	3000 K	1140 lm	235111
12W LED	4000 K	1162 lm	235112

HARPUT 3 LED DOWNLIGHT

Class II IP65

Available in any
of these RAL colors



6W or 12W COB LED

Led : 6W or 12W COB LED


Reflector : 15°, 24°, 38° or 60°

Gear : 240V

(1-10V Dimmable Driver & DALI Driver available on request)


Cable : 0,5 m 2x0,75 mm H03 VV-F

FIXED




Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	232003
12W LED	3000 K	1140 lm	232001
12W LED	4000 K	1162 lm	232002
20W LED	2700 K	1900 lm	232013
20W LED	3000 K	1900 lm	232011
20W LED	4000 K	1936 lm	232012

ADJUSTABLE





Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	232103
12W LED	3000 K	1140 lm	232101
12W LED	4000 K	1162 lm	232102
20W LED	2700 K	1900 lm	232113
20W LED	3000 K	1900 lm	232111
20W LED	4000 K	1936 lm	232112

FIXED TRIMLESS



Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	236003
12W LED	3000 K	1140 lm	236001
12W LED	4000 K	1162 lm	236002
20W LED	2700 K	1900 lm	236013
20W LED	3000 K	1900 lm	236011
20W LED	4000 K	1936 lm	236012

ADJUSTABLE TRIMLESS




Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	236103
12W LED	3000 K	1140 lm	236101
12W LED	4000 K	1162 lm	236102
20W LED	2700 K	1900 lm	236113
20W LED	3000 K	1900 lm	236111
20W LED	4000 K	1936 lm	236112

HARPUR 4 LED DOWNLIGHT

Class II IP65

Available in any
of these RAL colors



6W or 12W COB LED

Led : 6W or 12W COB LED


Reflector : 15°, 24°, 38° or 60°

Gear : 240V

(1-10V Dimmable Driver & DALI Driver available on request)


Cable : 0,5 m 2x0,75 mm H03 VV-F

FIXED





Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	232003
12W LED	3000 K	1140 lm	232001
12W LED	4000 K	1162 lm	232002
20W LED	2700 K	1900 lm	232013
20W LED	3000 K	1900 lm	232011
20W LED	4000 K	1936 lm	232012

ADJUSTABLE





Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	232103
12W LED	3000 K	1140 lm	232101
12W LED	4000 K	1162 lm	232102
20W LED	2700 K	1900 lm	232113
20W LED	3000 K	1900 lm	232111
20W LED	4000 K	1936 lm	232112

FIXED TRIMLESS



Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	237003
12W LED	3000 K	1140 lm	237001
12W LED	4000 K	1162 lm	237002
20W LED	2700 K	1900 lm	237013
20W LED	3000 K	1900 lm	237011
20W LED	4000 K	1936 lm	237012

ADJUSTABLE TRIMLESS




Power	Kelvin	Real Lumen Output	Code No
12W LED	2700 K	1140 lm	237103
12W LED	3000 K	1140 lm	237101
12W LED	4000 K	1162 lm	237102
20W LED	2700 K	1900 lm	237113
20W LED	3000 K	1900 lm	237111
20W LED	4000 K	1936 lm	237112

PENTATHLON

LED DOWNLIGHT

Class II IP20

Available in any
of these RAL colors



The PENTATHLON Dark Reflector LED Downlight is specially designed to provide low glare lighting in high ceiling areas. The Nichia COB chip gives out a high efficiency and high CRI (90) light. The lens that is used in the PENTATHLON allows the light to reach the ground with minimal loss from deep inside the fixture. The depth of the fixture and the clean beam of the lens is what provides the low glare of this fixture.

Body

Die cast aluminium

Paint

Electrostatic powder paint RAL 9016 (available in other RAL colors)

Springs

Steel for mounting in ceilings of 1-25mm thickness

Gear

Non-Dimmable electronic LED driver

(1-10V Dimmable and DALI drivers available on request)

Cable

0.5m exiting from top of fixture

COB LED

Led : 350mA 13W / 500mA 18W LED (Nichia)

Reflector : 24° or 38°


Gear : 240V Non-Dimmable Driver

(1-10V Dimmable Driver & DALI Driver available on request)

Cable : 0,5 m 2x0,75 mm H03 VV-F




SYMMETRICAL



Power	Kelvin	Real Lumen Output	Lens	Code No
13W LED	2700 K	1235 lm	24°,38°	118203
13W LED	3000 K	1235 lm	24°,38°	118201
13W LED	4000 K	1259 lm	24°,38°	118202
18W LED	2700 K	1710 lm	24°,38°	118403
18W LED	3000 K	1710 lm	24°,38°	118401
18W LED	4000 K	1779 lm	24°,38°	118402

ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Lens	Code No
13W LED	2700 K	1235 lm	24°,38°	118223
13W LED	3000 K	1235 lm	24°,38°	118221
13W LED	4000 K	1259 lm	24°,38°	118222
18W LED	2700 K	1710 lm	24°,38°	118213
18W LED	3000 K	1710 lm	24°,38°	118211
18W LED	4000 K	1779 lm	24°,38°	118212


PENTATHLON

TRIMLESS LED DOWNLIGHT Class II IP20

Available in any
of these RAL colors



SYMMETRICAL



ASYMMETRICAL

COB LED

Led : 350mA 13W / 500mA 18W LED (Nichia)


Reflector : 24° or 38°

Gear : 240V Non-Dimmable Driver

(1-10V Dimmable Driver & DALI Driver available on request)


Cable : 0,5 m 2x0,75 mm H03 VV-F

TRIMLESS SYMMETRICAL



Power	Kelvin		Lens	Code No
13W LED	2700 K	1235 lm	24°, 38°	118303
13W LED	3000 K	1235 lm	24°, 38°	118301
13W LED	4000 K	1259 lm	24°, 38°	118302
18W LED	2700 K	1710 lm	24°, 38°	118333
18W LED	3000 K	1710 lm	24°, 38°	118331
18W LED	4000 K	1779 lm	24°, 38°	118332

TRIMLESS ASYMMETRICAL



Power	Kelvin	Real Lumen Output	Lens	Code No
13W LED	2700 K	1235 lm	24°, 38°	118323
13W LED	3000 K	1235 lm	24°, 38°	118321
13W LED	4000 K	1259 lm	24°, 38°	118322
18W LED	2700 K	1710 lm	24°, 38°	118343
18W LED	3000 K	1710 lm	24°, 38°	118341
18W LED	4000 K	1744 lm	24°, 38°	118342



SATURN

LED DOWNLIGHT

Class II IP20

Available in any
of these RAL colors



The Saturn LED Downlight is specially designed to provide highest energy efficiency in general lighting applications. Using latest LED technology in combination with special plastic moulding and paint application allows for around 90lm/W lighting output. The highly efficient diffuser provides a completely homogenous light output.

Body

Die cast aluminium

Paint

Electrostatic powder paint RAL 9016 (available in other RAL colors)

Springs

Steel for mounting in ceilings of 1-25mm thickness

Gear

Non-Dimmable electronic LED driver (1-10V Dimmable and DALI drivers available on request)

Cable

0.5m exiting from top of fixture

COB LED


Led : 180mA 6W / 250mA 8W COB LED

Reflector : 10° / 38° / 60°


Gear : 240V Non-Dimmable Driver

(1-10V Dimmable Driver & DALI Driver available on request)

Cable : 0,5 m 2x0,75 mm H03 VV-F




FIXED



Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°38°,60°	528004
6W LED	3000 K	570 lm	10°38°,60°	528001
6W LED	4000 K	581 lm	10°38°,60°	528002
6W LED	6000 K	593 lm	10°38°,60°	528003
8W LED	2700 K	760 lm	10°38°,60°	528014
8W LED	3000 K	760 lm	10°38°,60°	528011
8W LED	4000 K	774 lm	10°38°,60°	528012
8W LED	6000 K	790 lm	10°38°,60°	528013

ADJUSTABLE




Power	Kelvin	Real Lumen Output	Lens	Code No
6W LED	2700 K	570 lm	10°38°,60°	528104
6W LED	3000 K	570 lm	10°38°,60°	528101
6W LED	4000 K	581 lm	10°38°,60°	528102
6W LED	6000 K	593 lm	10°38°,60°	528103
8W LED	2700 K	760 lm	10°38°,60°	528114
8W LED	3000 K	760 lm	10°38°,60°	528111
8W LED	4000 K	774 lm	10°38°,60°	528112
8W LED	6000 K	790 lm	10°38°,60°	528113

SATURN MINI

DEEP LED DOWNLIGHT

Class I IP20


Available in any
of these RAL colors



COB LED

- Voltage** : 240V A.C with integrated driver
(24V AC or DC on request)
- Diffuser** : Clear Glass with painted circumference
8 mm (Frosted Glass on request)
- Cable** : Potted 5 m 3x0,75 H03 VV-F

SATURN MINI



Power	Kelvin	Real Lumen Output	Lens	Code No
1W LED	2700 K	95 lm	25°,40°	529004
1W LED	3000 K	95 lm	25°,40°	529001
1W LED	4500 K	97 lm	25°,40°	529002
1W LED	6000 K	99 lm	25°,40°	529003
3W LED	2700 K	285 lm	25°,40°	529014
3W LED	3000 K	285 lm	25°,40°	529011
3W LED	4500 K	290 lm	25°,40°	529012
3W LED	6000 K	296 lm	25°,40°	529013


CUNDA

LED DOWNLIGHT Class II IP44

Available in any
of these RAL colors




CUNDA 1



Power	Kelvin	Real Lumen Output	Code No	
			DOT	HALO
7W LED	2700 K	665 lm	419203	419213
7W LED	3000 K	665 lm	419201	419214
7W LED	4000 K	677 lm	419202	419215
7W LED	3000 K	665 lm	419204	419211
7W LED	4000 K	677 lm	419205	419212

CUNDA 2



Power	Kelvin	Real Lumen Output	Code No	
			DOT	HALO
11W LED	2700 K	1045 lm	419303	419313
11W LED	3000 K	1045 lm	419301	419314
11W LED	4000 K	1065 lm	419302	419315
11W LED	3000 K	1045 lm	419304	419311
11W LED	4000 K	1065 lm	419305	419312

DOT LED DOWNLIGHT

Class II IP44

Available in any of these RAL colors

7004

7016

9005

9016

6002

1015

DOT



Power	Kelvin	Real Lumen Output	Code No
7W LED	2700 K	665 lm	112303
7W LED	3000 K	665 lm	112301
7W LED	4000 K	677 lm	112302
11W LED	2700 K	1045 lm	112313
11W LED	3000 K	1045 lm	112311
11W LED	4000 K	1065 lm	112312

HALO





Power	Kelvin	Real Lumen Output	Code No
7W LED	2700 K	665 lm	112403
7W LED	3000 K	665 lm	112401
7W LED	4000 K	677 lm	112402
11W LED	2700 K	1045 lm	112413
11W LED	3000 K	1045 lm	112411
11W LED	4000 K	1065 lm	112412

PATARA

LED DOWNLIGHT



Class II IP44

PATARA 1



Power	Kelvin	Real Lumen Output	HALO	DOT
7W LED	2700 K	665 lm	420303	420313
7W LED	3000 K	665 lm	420301	420314
7W LED	4000 K	677 lm	420302	420315
7W LED	3000 K	665 lm	420304	420311
7W LED	4000 K	677 lm	420305	420312

PATARA 2



Power	Kelvin	Real Lumen Output	HALO	DOT
7W LED	2700 K	665 lm	420403	420313
7W LED	3000 K	665 lm	420401	420414
7W LED	4000 K	677 lm	420402	420415
7W LED	3000 K	665 lm	420404	420411
7W LED	4000 K	677 lm	420405	420412

BELKIS MINI

LED DOWNLIGHT

Class I IP65

Cover

Die cast aluminium or Stainless steel

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

Tempered Glass


POWER LED

Voltage : 240V A.C with integrated driver
(24V AC or DC on request)



Lens : 25°, 40°

Diffuser : Clear Glass with painted circumference
8 mm (Frosted Glass on request)

Cable : Potted 5 m 3x0,75 H03 VV-F



BELKIS MINI



Power	Kelvin	Lens	Real Lumen Output	Code No
1W LED	2700 K	25°,40°	95 lm	297004
1W LED	3000 K	25°,40°	95 lm	297001
1W LED	4500 K	25°,40°	97 lm	297002
1W LED	6000 K	25°,40°	99 lm	297003
3W LED	2700 K	25°,40°	285 lm	297014
3W LED	3000 K	25°,40°	285 lm	297011
3W LED	4500 K	25°,40°	290 lm	297012
3W LED	6000 K	25°,40°	296 lm	297013

MARATHON LED DOWNLIGHT

Class II IP65 IK10

Available in any
of these RAL colors



Body

Die cast aluminium designed to be heat sink

Cover

Die cast aluminium RAL9002 (available in other RAL colors as well as chrome or gold on request)

Diffuser

Clear of frosted tempered Glass

Springs

Stainless steel for mounting in ceilings or 1-25 mm (with plastic covers for the Marathon 2 Downlight)

Cable

0.5 m exiting top of fixture

Gear

Non-Dimmable electronic LED driver (1-10V Dimmable and DALI drivers available on request)

COB LED (350-500mA)

Reflector : 10°, 23°, 38° Aluminium-Coated Polycarbonate Reflector

Diffuser : Clear Glass 8 mm (Frosted Glass on request)

Gear : 240V Non-Dimmable Driver


(1-10V Dimmable Driver & DALI Driver available on request)

Springs : Plastic covered Stainless Steel for mounting in ceilings of 1-25 mm

Cable : 0,5 m 2x0,75 mm H03 VV-F




MARATHON 2





Power	Kelvin	Lens	Real Lumen Output	Code No
11W LED	2700 K	10°, 23°, 38°	1045 lm	260101
11W LED	3000 K	10°, 23°, 38°	1045 lm	260102
11W LED	4000 K	10°, 23°, 38°	1065 lm	260103
18W LED	2700 K	10°, 23°, 38°	1710 lm	260113
18W LED	3000 K	10°, 23°, 38°	1710 lm	260111
18W LED	4000 K	10°, 23°, 38°	1779 lm	260112

MARATHON 2 GLASS



Power	Kelvin	Lens	Real Lumen Output	Code No
11W LED	2700 K	10°, 23°, 38°	1045 lm	263001
11W LED	3000 K	10°, 23°, 38°	1045 lm	263002
11W LED	4000 K	10°, 23°, 38°	1065 lm	263003
18W LED	2700 K	10°, 23°, 38°	1710 lm	263011
18W LED	3000 K	10°, 23°, 38°	1710 lm	263012
18W LED	4000 K	10°, 23°, 38°	1744 lm	263013

MARATHON 2 GLASS



Power	Kelvin	Lens	Real Lumen Output	Code No
11W LED	2700 K	10°, 23°, 38°	1045 lm	263201
11W LED	3000 K	10°, 23°, 38°	1045 lm	263202
11W LED	4000 K	10°, 23°, 38°	1065 lm	263203
18W LED	2700 K	10°, 23°, 38°	1710 lm	263211
18W LED	3000 K	10°, 23°, 38°	1710 lm	263212
18W LED	4000 K	10°, 23°, 38°	1744 lm	263213



MARATHON

TIR LENS LED DOWNLIGHT Class II IP65 IK10


Available in any
of these RAL colors



COB LED (350-700 mA)


- Lens** : 10°, 20°, 30° Mirror TIR Lens
- Diffuser** : Clear Glass 8 mm (Frosted Glass on request)
- Gear** : 240V Non-Dimmable Driver
(1-10V Dimmable Driver & DALI Driver available on request)
- Springs** : Stainless Steel for mounting in ceilings of 1-25 mm
- Cable** : 0,5 m 2x0,75 mm H03 VV-F

MARATHON 3



Power	Kelvin	Lens	Real Lumen Output	Code No
11W LED	2700 K	10°, 20°, 30°	1045 lm	261003
11W LED	3000 K	10°, 20°, 30°	1045 lm	261001
11W LED	4000 K	10°, 20°, 30°	1065 lm	261002
18W LED	2700 K	10°, 20°, 30°	1710 lm	261013
18W LED	3000 K	10°, 20°, 30°	1710 lm	261011
18W LED	4000 K	10°, 20°, 30°	1779 lm	261012

MARATHON 4



Power	Kelvin	Lens	Real Lumen Output	Code No
25W LED	2700 K	10°, 20°, 30°	1045 lm	262003
25W LED	3000 K	10°, 20°, 30°	1045 lm	262001
25W LED	4000 K	10°, 20°, 30°	1065 lm	262002
32W LED	2700 K	10°, 20°, 30°	1710 lm	262023
32W LED	3000 K	10°, 20°, 30°	1710 lm	262021
32W LED	4000 K	10°, 20°, 30°	1779 lm	262022



DECATHLON

LED DOWNLIGHT

Class III IP65 IK10

Available in any
of these RAL colors



The Decathlon LED Downlight is specially designed to deliver high output LED light to indoors and outdoors using CREE LEDs. This downlight is the choice for lighting applications where high luminous-flux output is required from a single, small point source. The Decathlon is slightly wider and deeper than the Marathon giving a different look to the fixture, but the same output. A combination of high color rendition of over 80, several different color temperatures and several degree reflectors and lenses allow the use in a wide range of applications such as museums, hospitals, hotel rooms, dormitories, corridors, shops, and balconies. The shallow fixture depths allow for installation into most ceilings and applications. Non-dimmable drivers come standard with the Downlights, but 1-10V dimmable and DALI drivers are available on request. An ample heat sink is provided for to allow for the lifetime of L70 = 50,000 hours.

Body

Die cast aluminium designed to be heat sink

Cover

Die cast aluminium RAL9002 (available in other RAL colors as well as chrome or gold on request)

Diffuser

Clear of frosted tempered Glass

Springs

Stainless steel for mounting in ceilings or 1-25 mm (with plastic covers for the Marathon 2 Downlight)

Cable

0.5 m exiting top of fixture

Gear

Non-Dimmable electronic LED driver (1-10V Dimmable and DALI drivers available on request)




LEDs


Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.



Directional Downlight



Application

These fixtures give a narrow to wide beam asymmetrical light output to walls, paintings, corridors and shop displays. The die cast aluminium body has a fixed built in tilt to allow for proper heat dissipation on the LEDs that can run up to 700mA.

DECATHLON

LED DOWNLIGHT

Class III IP65 IK10


Available in any
of these RAL colors



COB CREE LED (350-700mA)


- Reflector** : 10°, 23°, 38° Aluminium-Coated Polycarbonate Reflector
- Diffuser** : Clear Glass 8 mm (Frosted Glass on request)
- Gear** : 240V Non-Dimmable Driver(1-10V Dimmable Driver & DALI Driver available on request)
- Springs** : Plastic covered Stainless Steel for mounting in ceilings of 1-25 mm
- Cable** : 0,5 m 2x0,75 mm H03 VV-F

DECATHLON 2 SYMMETRICAL



Power	Kelvin	Lens	Real Lumen Output	Code No
11W 350mA	2700 K	10°, 23°, 38°	1045 lm	260201
11W 350mA	3000 K	10°, 23°, 38°	1045 lm	260202
11W 350mA	4000 K	10°, 23°, 38°	1065 lm	260203
18W 500mA	2700 K	10°, 23°, 38°	1710 lm	260211
18W 500mA	3000 K	10°, 23°, 38°	1710 lm	260212
18W 500mA	4000 K	10°, 23°, 38°	1779 lm	260213

DECATHLON 2 ASYMMETRICAL



Power	Kelvin	Lens	Real Lumen Output	Code No
11W 350mA	2700 K	10°, 23°, 38°	1045 lm	260231
11W 350mA	3000 K	10°, 23°, 38°	1045 lm	260232
11W 350mA	4000 K	10°, 23°, 38°	1065 lm	260233
18W 500mA	2700 K	10°, 23°, 38°	1710 lm	260241
18W 500mA	3000 K	10°, 23°, 38°	1710 lm	260242
18W 500mA	4000 K	10°, 23°, 38°	1779 lm	260243




DECATHLON

TIR LENS LED DOWNLIGHT

Class II IP65 IK10


Available in any
of these RAL colors



COB LED (350-700mA)


- Lens** : 10°, 20°, 30° Mirror TIR Lens
- Diffuser** : Clear Glass 8 mm (Frosted Glass on request)
- Gear** : 240V Non-Dimmable Driver(1-10V Dimmable Driver & DALI Driver available on request)
- Springs** : Plastic covered Stainless Steel for mounting in ceilings of 1-25 mm
- Cable** : 0,5 m 2x0,75 mm H03 VV-F

DECATHLON 3 SYMMETRICAL




Power	Kelvin	Lens	Code No
11W LED	2700 K	10°, 20°, 30°	1045 lm 266002
11W LED	3000 K	10°, 20°, 30°	1045 lm 266001
11W LED	4000 K	10°, 20°, 30°	1065 lm 266003
18W LED	2700 K	10°, 20°, 30°	1710 lm 266022
18W LED	3000 K	10°, 20°, 30°	1710 lm 266021
18W LED	4000 K	10°, 20°, 30°	1779 lm 266023

DECATHLON 3 ASYMMETRICAL




Power	Kelvin	Lens	Real Lumen Output	Code No
11W LED	2700 K	10°, 20°, 30°	1045 lm	266102
11W LED	3000 K	10°, 20°, 30°	1045 lm	266101
11W LED	4000 K	10°, 20°, 30°	1065 lm	266103
18W LED	2700 K	10°, 20°, 30°	1710 lm	266122
18W LED	3000 K	10°, 20°, 30°	1710 lm	266121
18W LED	4000 K	10°, 20°, 30°	1779 lm	266123

DECATHLON 4 SYMMETRICAL



Power	Kelvin	Lens	Real Lumen Output	Code No
25W LED	2700 K	10°, 20°, 30°	2375 lm	267002
25W LED	3000 K	10°, 20°, 30°	2375 lm	267001
25W LED	4000 K	10°, 20°, 30°	2422 lm	267003
32W LED	2700 K	10°, 20°, 30°	3040 lm	267022
32W LED	3000 K	10°, 20°, 30°	3040 lm	267021
32W LED	4000 K	10°, 20°, 30°	3100 lm	267023

DECATHLON 4 ASYMMETRICAL



Power	Kelvin	Lens	Real Lumen Output	Code No
25W LED	2700 K	10°, 20°, 30°	2375 lm	267102
25W LED	3000 K	10°, 20°, 30°	2375 lm	267101
25W LED	4000 K	10°, 20°, 30°	2422 lm	267103
32W LED	2700 K	10°, 20°, 30°	3040 lm	267122
32W LED	3000 K	10°, 20°, 30°	3040 lm	267121
32W LED	4000 K	10°, 20°, 30°	3100 lm	267123



TRIATHLON

LED DOWNLIGHT

Class II IP55 IK08

Available in any
of these RAL colors



The Triathlon LED Downlight is specially designed to provide highest energy efficiency in general lighting applications. Using latest LED technology in combination with special plastic moulding and paint application allows for around 90lm/W lighting output. The highly efficient diffuser provides a completely homogenous light output. The simple installation method allows for easy installation into ceilings from 1-25mm thickness. One can choose from three compact sizes, 120mm, 150mm, and 175mm to achieve the desired lighting level.

Body

Die cast aluminium

Paint

Electrostatic powder paint RAL 9016 (available in other RAL colors)

Diffuser

High efficiency frosted acrylic diffuser with 90° beam angle

Springs

Steel for mounting in ceilings of 1-25mm thickness

Gear

Non-Dimmable electronic LED driver (1-10V Dimmable and DALI drivers available on request)

Cable



0.5m exiting from top of fixture

Downlight



Application

Wide beam symmetrical lighting for general lighting such as museums, hospitals, hotel rooms, dormitories, corridors, shops, and balconies.




LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

Thermal Management

All fixtures are designed to withstand ambient temperatures of at least 50°C. The LEDs are mounted on metal core pcbs, which are mounted the aluminium body of the fixture so that the entire fixture acts as a heat sink. Extensive testing is performed in EMFA's laboratory to ensure these values are maintained so that the lifetime of the LED is not compromised.



TRIATHLON

LED DOWNLIGHT

Class II IP55 IK08


Available in any
of these RAL colors



Osram SMD LEDs; over 110lm/W


- Reflector** : 90°
- Diffuser** : High efficiency frosted acrylic diffuser with 90° beam angle
- Gear** : 240V Non-Dimmable Driver (1-10V Dimmable Driver & DALI Driver available on request)
- Springs** : Plastic covered Stainless Steel for mounting in ceilings of 1-25 mm
- Cable** : 0,5 m 2x0,75 mm H03 VV-F

TRIATHLON 3




Power	Kelvin	Lens	Real Lumen Output	Code No
6W LED	2700 K	90°	570 lm	268301
6W LED	3000 K	90°	570 lm	268302
8W LED	2700 K	90°	760 lm	268311
8W LED	3000 K	90°	760 lm	268312
10W LED	2700 K	90°	950 lm	268321
10W LED	3000 K	90°	950 lm	268322

TRIATHLON 4



Power	Kelvin	Lens	Real Lumen Output	Code No
11W LED	2700 K	90°	1045 lm	268401
11W LED	3000 K	90°	1045 lm	268402
16W LED	2700 K	90°	1520 lm	268411
16W LED	3000 K	90°	1520 lm	268412
20W LED	2700 K	90°	1900 lm	268421
20W LED	3000 K	90°	1900 lm	268422

TRIATHLON 5



Power	Kelvin	Lens	Real Lumen Output	Code No
16W LED	2700 K	90°	1520 lm	268501
16W LED	3000 K	90°	1520 lm	268502
24W LED	2700 K	90°	2280 lm	268511
24W LED	3000 K	90°	2280 lm	268512
31W LED	2700 K	90°	2945 lm	268521
31W LED	3000 K	90°	2945 lm	268522
40W LED	2700 K	90°	3800 lm	268531
40W LED	3000 K	90°	3800 lm	268532

TRIATHLON HALO

LED DOWNLIGHT

Class II IP55 IK08


Available in any
of these RAL colors



Osram SMD LEDs


- Reflector** : 90°
- Diffuser** : High efficiency frosted acrylic diffuser with 90° beam angle
- Gear** : 240V Non-Dimmable Driver (1-10V Dimmable Driver & DALI Driver available on request)
- Springs** : Plastic covered Stainless Steel for mounting in ceilings of 1-25 mm
- Cable** : 0,5 m 2x0,75 mm H03 VV-F

TRIATHLON HALO 3




Power	Kelvin	Lens	Real Lumen Output	Code No
6W 350mA	2700 K	90°	570 lm	269301
6W 350mA	3000 K	90°	570 lm	269302
8W 500mA	2700 K	90°	760 lm	269311
8W 500mA	3000 K	90°	760 lm	269312
10W 700mA	2700 K	90°	950 lm	269321
10W 700mA	3000 K	90°	950 lm	269322

TRIATHLON HALO 4



Power	Kelvin	Lens	Real Lumen Output	Code No
11W 350mA	2700 K	90°	1045 lm	269401
11W 350mA	3000 K	90°	1045 lm	269402
16W 500mA	2700 K	90°	1520 lm	269411
16W 500mA	3000 K	90°	1520 lm	269412
20W 700mA	2700 K	90°	1900 lm	269421
20W 700mA	3000 K	90°	1900 lm	269422

TRIATHLON HALO 5



Power	Kelvin	Lens	Real Lumen Output	Code No
16W 350mA	2700 K	90°	1520 lm	269501
16W 350mA	3000 K	90°	1520 lm	269502
24W 500mA	2700 K	90°	2280 lm	269511
24W 500mA	3000 K	90°	2280 lm	269512
31W 700mA	2700 K	90°	2945 lm	269521
31W 700mA	3000 K	90°	2945 lm	269522

RECESSED FIXTURES Downlights (For False Ceiling) Class III IP67 IK10



HALOGEN

Lampholder : Gu4/Gu5.3/E27



Reflector : -

Diffuser : 6 mm Tempered Glass
(8mm Tempered Glass for BELKIS 5)

Transformer is not included.


Remote transformer should be used.

BELKIS 1




Power	Reflector	Lampholder	Class	Round	Square
20W HALOGEN	10°, 38°	Gu4	I	321101	321201

BELKIS 2



Power	Reflector	Lampholder	Class	Round	Square
35/50W HALOGEN	10°, 38°	Gu5.3	III	323101	323201
35/50W HALOGEN	25°, 50°	Gu10	I	323121	323221

BELKIS 5




Power	Reflector	Lampholder	Class	Round	Square
75W HALOGEN	10°, 30°	E27	I	325111	325211



DYO RECESSED CEILING FIXTURES

Available in any
of these RAL colors



Single



Twin

HALOGEN or COB LED

Class : III/II

Lampholder : Gu10/Gu5.3



Reflector : -

Diffuser : -

Transformer is not included.


Remote transformer should be used.

DYO 70 16 S/70 18 S




Power	Glass	Lampholder	Class	Code No
50W Halogen	Without Glass	Gu 5.3	III	133101
50W Halogen	With Glass	Gu 5.3	III	133201
50W Halogen	Without Glass	Gu10	II	133111
50W Halogen	With Glass	Gu10	II	133211

DYO 70 16 Single




Power	Kelvin	Real Lumen Output	Code No
6W LED	2700 K	570 lm	133304
6W LED	3000 K	570 lm	133301
6W LED	4000 K	581 lm	133302
6W LED	6000 K	593 lm	133303
8W LED	2700 K	760 lm	133314
8W LED	3000 K	760 lm	133311
8W LED	4000 K	774 lm	133312
8W LED	6000 K	790 lm	133313

DYO 70 16 TWIN



Power	Kelvin	Real Lumen Output	Code No
6W LED	2700 K	570 lm	133404
6W LED	3000 K	570 lm	133401
6W LED	4000 K	581 lm	133402
6W LED	6000 K	593 lm	133403
8W LED	2700 K	760 lm	133414
8W LED	3000 K	760 lm	133411
8W LED	4000 K	774 lm	133412
8W LED	6000 K	790 lm	133413



CUNDA/PATARA

RECESSED INDOOR CRADLE FIXTURES

HALOGEN

Outer Frame

Steel

Cradle Frame

Die cast aluminium

Paint


Electrostatic powder

Class : III-I


Lampholder : G53/E27

Reflector : -

Diffuser : -




CUNDA ROUND



Power	Lampholder	Class	Code No
50W	G 53	III	419101
75W	E 27	I	419111

PATARA SINGLE 2 x HALOGEN RJ111 12V 50W



Power	Lampholder	Class	Single	Twin
HALOGEN RJ111 50W	G 53	III	420101	420201
PAR 30 HALOGEN	E 27	I	420111	420211

HALOGEN SPOT DOWNLIGHT

Available in any
of these RAL colors



Body

Aluminium

Frame

Steel

Holding Force

Magnetism, no screws
for easy assembly
and maintenance

Spring

Spiral Inox

Automatically adjustable to the
thickness of false ceiling

Special Feature

Adjustable lamp angle

HALOGEN

Class : III


Lampholder : Gu 4 / Gu5.3

Reflector : -

Diffuser : -

Transformer is not included.

Remote transformer should be used.



Power	Lampholder	Class	Code No
20W HALOGEN	Gu 4	III	113401
50W HALOGEN	Gu 5.3	III	113411



Body

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffusers

Tempered glass or acrylic

Gaskets

Silicone

Connection

IP connection box

OSRAM SMD LED, COB LED, MULTICHIP LED, DOM LED

Voltage : 240V A.C with integrated Driver
(24V AC or DC on request)

Diffuser : Acrylic / Clear Glass 8 mm (Frosted Glass on request)

Cable : Potted 5 m 3x0,75 mm H03 VV-F



Power LED



SQUARE DOM LED




MULTICHIP LED




SQUARE

SQUARE DOM LED




Power	Kelvin		Code No
11W LED	2700 K	1045 lm	289003
11W LED	3000 K	1045 lm	289001
11W LED	4000 K	1065 lm	289002

SQUARE




Power	Kelvin	Real Lumen Output	Code No
6W LED	2700 K	570 lm	289013
6W LED	3000 K	570 lm	289011
6W LED	4000 K	581 lm	289012

SQUARE POWER LED



Power	Kelvin	Lens	Real Lumen Output	Code No
6W LED	2700 K	10°, 25°, 40°	570 lm	289024
6W LED	3000 K	10°, 25°, 40°	570 lm	289021
6W LED	4000 K	10°, 25°, 40°	581 lm	289022
6W LED	6000 K	10°, 25°, 40°	593 lm	289023

SQUARE MULTICHIP LED



Power	Kelvin	Real Lumen Output	Code No
9W LED	2700 K	855 lm	289033
9W LED	3000 K	855 lm	289031
9W LED	4000 K	872 lm	289032

MARATHON 2 GLASS

SURFACE MOUNTED CEILING FIXTURES Class I IP65

Glass available in these
pastel colors



Body

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffusers

Tempered glass

Gaskets

Silicone

Connection

IP connection box

COB LED (350-500mA)

Reflector : 10°, 23°, 38° Aluminium-Coated Polycarbonate Reflector


Diffuser : Clear Glass 8 mm (Frosted Glass on request)

Gear : 240V Non-Dimmable Driver


(1-10V Dimmable Driver & DALI Driver available on request)

Springs : Plastic covered Stainless Steel for mounting in ceilings of 1-25 mm

Cable : 0,5 m 2x0,75 mm H03 VV-F



Power	Kelvin	Lens	Real Lumen Output	Code No
3W LED	2700 K	10°, 23°, 38°	285 lm	260301
3W LED	3000 K	10°, 23°, 38°	285 lm	260302
3W LED	4000 K	10°, 23°, 38°	290 lm	260303
11W LED	2700 K	10°, 23°, 38°	1045 lm	260333
11W LED	3000 K	10°, 23°, 38°	1045 lm	260331
11W LED	4000 K	10°, 23°, 38°	1065 lm	260332



Power	Kelvin	Lens	Real Lumen Output	Code No
3W LED	2700 K	10°, 23°, 38°	210 lm	260402
3W LED	3000 K	10°, 23°, 38°	210 lm	260401
3W LED	4000 K	10°, 23°, 38°	252 lm	260403
11W LED	2700 K	10°, 23°, 38°	252 lm	260433
11W LED	3000 K	10°, 23°, 38°	696 lm	260431
11W LED	4000 K	10°, 23°, 38°	835 lm	260432

DECATHLON 3

SURFACE MOUNTED CEILING FIXTURES Class I IP55

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffusers

Tempered glass

Gaskets

Silicone

Connection

IP connection box




POWER LED

Voltage : 240V A.C with integrated Driver
(24V AC or DC on request)


Lens : 10°, 25°, 40°

Diffuser : Clear Glass with painted circumference 8 mm
(Frosted Glass on request)

Cable : Potted 5 m 3x0,75 H03 VV-F




Power	Kelvin	Lens	Real Lumen Output	Code No
6W LED	2700 K	10°,25°,40°	510 lm	266204
6W LED	3000 K	10°,25°,40°	510 lm	266201
6W LED	4500 K	10°,25°,40°	510 lm	266202
6W LED	6000 K	10°,25°,40°	612 lm	266203
12W LED	2700 K	10°,25°,40°	510 lm	266304
12W LED	3000 K	10°,25°,40°	935 lm	266301
12W LED	4500 K	10°,25°,40°	935 lm	266302
12W LED	6000 K	10°,25°,40°	1070 lm	266303



BELKIS 2

SURFACE MOUNTED CEILING FIXTURES Class I IP65

Available in any
of these RAL colors



Body

Die cast aluminium

Paint

Electrostatic powder

Bracket

Die cast aluminium

Diffusers

Tempered glass

Gaskets

Silicone

Connection

IP connection box



COB LED

Voltage : 240V A.C with integrated Driver (24V AC or DC on request)


Lens : 10°, 25°, 40°

Diffuser : Clear Glass with painted circumference 8 mm (Frosted Glass on request)

Cable : Potted 5 m 3x0,75 H03 VV-F

Single color LED options upon request are ;

Blue Amber Green Red



Power	Kelvin	Lens	Real Lumen Output	Code No
3W LED	2700 K	10°, 25°, 40°	285lm	435004
3W LED	3000 K	10°, 25°, 40°	285 lm	435001
3W LED	4500 K	10°, 25°, 40°	290 lm	435002
3W LED	6000 K	10°, 25°, 40°	296 lm	435003
9W LED	2700 K	10°, 25°, 40°	855 lm	435014
9W LED	3000 K	10°, 25°, 40°	855 lm	435011
9W LED	4500 K	10°, 25°, 40°	872 lm	435012
9W LED	6000 K	10°, 25°, 40°	890 lm	435013






POWER LED or HALOGEN


- Voltage** : 240V A.C with integrated Driver (24V AC or DC on request)
Lens : 10°, 25°, 40°
Reflector : 25°, 30°, 40°, 42°, 50°
Diffuser : 4mm Frosted Glass for HALOGEN,
Clear Glass with painted circumference 8 mm
Lampholder : G9/Gu10/E27/G12
Cable : Potted 5 m 3x0,75 H03 VV-F

BELKIS 1




Power	Kelvin	Lens	Real Lumen Output	Code No
1W LED	2700 K	10°, 25°, 40°	95 lm	427004
1W LED	3000 K	10°, 25°, 40°	95 lm	427001
1W LED	4000 K	10°, 25°, 40°	97 lm	427002
1W LED	6000 K	10°, 25°, 40°	99 lm	427003
25W HALOGEN	G9	40°		335101

BELKIS 2




Power	Kelvin	Lens	Real Lumen Output	Code No
3W LED	2700 K	10°, 25°, 40°	285 lm	427104
3W LED	3000 K	10°, 25°, 40°	285 lm	427101
3W LED	4000 K	10°, 25°, 40°	285 lm	427102
3W LED	6000 K	10°, 25°, 40°	296 lm	427103
50W HALOGEN	Gu10	25°, 50°		336111

BELKIS 5 HALOGEN



Power	Kelvin	Lens	Real Lumen Output	Code No
6W LED	2700 K	10°, 25°, 40°	570 lm	427204
6W LED	3000 K	10°, 25°, 40°	570 lm	427201
6W LED	4500 K	10°, 25°, 40°	581 lm	427202
6W LED	6000 K	10°, 25°, 40°	593 lm	427203
9W LED	2700 K	10°, 25°, 40°	855 lm	427214
9W LED	3000 K	10°, 25°, 40°	855 lm	427211
9W LED	4500 K	10°, 25°, 40°	872 lm	427212
9W LED	6000 K	10°, 25°, 40°	890 lm	427213
75W HALOGEN	E27	30°		337121

BELKIS 5 METAL HALIDE




Power	Lampholder	Reflector	Code No
35W/70W	G12	30°, 42°	337131



HALOGEN


- Voltage** : 240V A.C with integrated Driver
(24V AC or DC on request)
- Diffuser** : Acrylic Pipe
- Cable** : Potted 5 m 3x0,75 H03 VV-F
- Transformer** : Electronic
- Lampholder** : G24 q-1/G23/G24 d-2/G12

BELKIS 1




Power	Lampholder	Code No
COMPACT FLUO 13W	G24 q-1	293101

BELKIS 2



Power	Lampholder	Code No
ELECTRONIC FLUO DEL 23W	E27	293111

BELKIS 4




Power	Code No
ELECTRONIC FLUO DEL 23W	293121

BELKIS

RECESSED CEILING FIXTURES

Class I IP44


Available in any
of these RAL colors



HALOGEN

- Voltage** : 240V A.C with integrated Driver
(24V AC or DC on request)
- Diffuser** : Acrylic Pipe
- Cable** : Potted 5 m 3x0,75 H03 VV-F
- Transformer** : Electronic
- Lampholder** : G23/G24 d-2/G24 d-3


BELKIS 1



Power	Lampholder	Code No
-------	------------	---------

COMPACT FLUO 9W	G23	296101
-----------------	-----	--------


BELKIS 2



Power	Lampholder	Code No
-------	------------	---------

COMPACT FLUO 18W	G24 d-2	296111
------------------	---------	--------


BELKIS 5



Power	Lampholder	Code No
-------	------------	---------

COMPACT FLUO 26W	G24 d-3	296121
------------------	---------	--------

BELKIS 5



Power	Lampholder	Code No
-------	------------	---------

METAL HALIDE 35W	G12	296131
------------------	-----	--------



HALOGEN

Voltage : 240V A.C with integrated Driver
(24V AC or DC on request)


Reflector : Symmetrical

Cable : Potted 5 m 3x0,75 H03 VV-F

Transformer : Included


Lampholder : Gu5.3/G9/Gu10/R7 s/G24 D-1/G24 d-2/G24 d-3

SQUARE




Power	Lampholder	Code No
50W HALOGEN	Gu 5.3	360101
25W HALOGEN	G9	360111
50W HALOGEN	Gu10	360121

ROUND



Power	Lampholder	Code No
50W HALOGEN	Gu 5.3	360201
25W HALOGEN	G9	360211
50W HALOGEN	Gu10	360221


FROSTED GLASS



Power	Lampholder	Code No
60W LINEAR HALOGEN	R7 s	363101
2 x 18W COMPACT FLUO HALOGEN	G24 d-2	379101
2 x 26W COMPACT FLUO HALOGEN	G24 d-3	380101
40W HALOGEN HALOGEN	G9	363111
10W COMPACT FLUO HALOGEN	G24 d-1	363121




 Pendants



VUVUZELA

PENDANT IP20

Available in any
of these RAL colors



Body

Black, gold or silver plated
304 stainless steel

Diffusers

Tempered Glass

Gaskets

Silicone

Mounting

Aluminium

Screws

316L stainless steel

POWER LED

Lamps : 4 x 700 mA (10W) LED

Lens : 40°

Transformer mounting : Remote


Transformer type : Electronic

Gear : 240v non-dimmable driver (1-10v dimmable driver & request)

Cable : 0.5m 2x0.75mm h03 w-f




RECESSED MOUNTED



Power	Kelvin	Lens	Lumen Output	Code No
10W LED	2700 K	40°	950 lm	117002
10W LED	3000 K	40°	950 lm	117001

SURFACE MOUNTED



Power	Kelvin	Lens	Lumen Output	Code No
10W LED	2700 K	40°	950 lm	117012
10W LED	3000 K	40°	950 lm	117011



KATENER

HIGH BAY LED FIXTURES IP65

Body

Die cast aluminium

Cover

Steel

Gaskets

Silicone


Screws

316L stainless steel


Voltage : 240 V A.C with integrated driver
(24V AC or DC on request)

Lens : Optical Lens 60° / 90° / 120°


Cable : Potted 5 m 3x0,75 H03 VV-F



Power	Lens	Kelvin	Real Lumen Output	Code No
100W	60°, 90°, 120°	2700 K	9500 lm	436003
100W	60°, 90°, 120°	4500 K	9688 lm	436001
100W	60°, 90°, 120°	6000 K	9880 lm	436002



Power	Lens	Kelvin	Real Lumen Output	Code No
150W	60°, 90°, 120°	2700 K	14250 lm	436013
150W	60°, 90°, 120°	4500 K	14532 lm	436011
150W	60°, 90°, 120°	6000 K	14820 lm	436012



Power	Lens	Kelvin	Real Lumen Output	Code No
200W	60°, 90°, 120°	2700 K	19000 lm	436023
200W	60°, 90°, 120°	4500 K	19376 lm	436021
200W	60°, 90°, 120°	6000 K	19760 lm	436022



ELEA PENDANT FIXTURES

Available in any
of these RAL colors



Body

Acrylic

Side Caps

Aluminium

Reflector

Aluminium

Wires

Adjustable Suspending Steel Wire

Diffusers

Acrylic

Gear

Electronic

Mounting Brackets

Aluminium

HALOGEN

Voltage : 240 VAC Class II


Diffuser : Acrylic

Lamp : Fluo. G5

Gear : Integrated in tube



ELEA




Power	Lampholder	Code No
FLUO 24W	G5	433101
3FLUO 5W	G5	433111

KARIA 2

PENDANT FIXTURES

Class I IP44 IK07

Available in any
of these RAL colors




HALOGEN

Voltage : 240V AC with integrated ballast
Diffuser : 4 mm Clear Glass
Lampholder : G5
Ballast : Electronic




KARIA 2



Power	Lampholder	Code No
T5 14W/24W	G5	431401

KARIA 3



Power	Lampholder	Code No
T5 21W/39W	G5	431501



TROY

PENDANT FIXTURES

Class I IP55

(with glass & gasket)

HALOGEN

Head

Glass reinforced polyamide 6

Gear box inside

Reflector


Opaque ABS or translucent acrylic



TROY




With Ring




Please use 150... as the first three digits of the code number

With Suspending Rod And Bracket




Please use 151... as the first three digits of the code number

With Adjustable Suspending Steel & Wire Spring Cable



Please use 153... as the first three digits of the code number

With Adjustable Suspending Steel Wire & Cable For Mounting On Pipe



Please use 154... as the first three digits of the code number

1 x ELEC. FL. DEL 23 23W

Lampholder : E27 Code No

Translucent xxx101

Opaque xxx501

2 x ELEC. FL. DEL 23 23W

Lampholder : E27 Code No

Translucent xxx111

Opaque xxx511

1 x COMPACT FLUOR. 26W

Lampholder : G24 d-3 Code No

Translucent xxx141

Opaque xxx541

2 x COMPACT FLUOR. 26W

Lampholder : G24 d-3 Code No

Translucent xxx151

Opaque xxx551

1 x COMPACT FLUOR. 42W

Lampholder : G24 q-4 Code No

Translucent xxx181

Opaque xxx581



 Pole Fixtures



MILET ANI

SIDE ALUM LED POLE

Class I IP65 IK08

EMFA's ANI pole mounted series have been designed for high efficiency and ease of installation incorporating the latest in LED technology and control systems. The special lens directs the light flow precisely and makes the whole luminaire system efficient. This compact and essential design is made of a combination of aluminium profile and die cast aluminium.

Pole

Aluminium profile

Body

Die cast aluminium

Gaskets

Silicone

Diffusers

4 mm Tempered Glass

Screws



316L Stainless Steel

Glands

PG 11

"Customization" is EMFA's standard


EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 8 LED colors, and 2 wattages, and available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.



Fuse Box



Anchor



LEDs

Only highest quality LEDs such as Cree or Toplite are used in production allowing for maximum lumen output and maximum lifetime. Most LEDs run on 350mA or 700mA depending on how much light output is required. The white color temperature binning is 200K at most, and always on the same x,y coordinates on the CIE diagram in accordance with Energy Star. This ensures consistent supply of the same color temperature over time. As LEDs are constantly developing and becoming more efficient, lumen output given in this catalogue are current as of March 2020. At 2700K, 3000K, and 4000K LED lumen output per led is 110lm; at 6000K the lumen output per led is 125lm. Total Lighting Output as printed in this catalogue is the actual light output of the entire fixture. The minimum CRI of the LEDs used is 85 with a majority of products over 90.

ANI 4

ALUM LED POLE
Class I IP65 IK08


Available in any
of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------



- Led** : Linear LEDs
Voltage : 240 VAC with integrated driver
(12-24 VDC on request)
Diffuser : 4mm Tempered Glass
Beam Angle : 45° / 60° / 90°
Mac Adam : 3
CRI : >80
L.O.R % : %70

SIDE



Power	Kelvin	Lens	Real Lumen Output	Code No		
				2000mm	4000mm	6000mm
24W	2700 K	10°,25°,40°	2280 lm	460003	460103	460203
24W	3000 K	10°,25°,40°	2280 lm	460001	460101	460201
24W	4000 K	10°,25°,40°	2320 lm	460002	460102	460202
36W	2700 K	10°,25°,40°	3420 lm	460013	460113	460213
36W	3000 K	10°,25°,40°	3420 lm	460011	460111	460211
36W	4000 K	10°,25°,40°	3520 lm	460012	460112	460212

ANI 4


ALUM LED POLE

Class I IP65 IK08

Available in any of these RAL colors


7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

L TYPE



Power	Kelvin	Lens	Real Lumen Output	Code No		
				2000mm	4000mm	6000mm
24W	2700 K	10°,25°,40°	2280 lm	461003	461103	461203
24W	3000 K	10°,25°,40°	2280 lm	461001	461101	461201
24W	4000 K	10°,25°,40°	2320 lm	461002	461102	461202
48W	2700 K	10°,25°,40°	3420 lm	461013	461113	461213
48W	3000 K	10°,25°,40°	3420 lm	461011	461111	461211
48W	4000 K	10°,25°,40°	3520 lm	461012	461112	461212

T TYPE



Power	Kelvin	Lens	Real Lumen Output	Code No		
				2000mm	4000mm	6000mm
2x24W	2700 K	10°,25°,40°	2280 lm	462003	462103	462203
2x24W	3000 K	10°,25°,40°	2280 lm	462001	462101	462201
2x24W	4000 K	10°,25°,40°	2320 lm	462002	462102	462202
2x48W	2700 K	10°,25°,40°	3420 lm	462013	462113	462213
2x48W	3000 K	10°,25°,40°	3420 lm	462011	462111	462211
2x48W	4000 K	10°,25°,40°	3520 lm	462012	462112	462212

BELKIS 5

ONE-WAY APPLIQUE ON POLE

Class I IP55

Available in any of these RAL colors

7004

7016

9005


9016

6002

1015

- Cover
- Die cast aluminium
- Paint
- Electrostatic powder
- Pipe
- Extrusion aluminium
- Connection
- IP connection box
- Gaskets
- Silicone
- Diffusers
- Tempered Clear Glass

- HALOGEN
- Lampholder : E27 / G24 d-2
- Reflector : 40
- Diffuser : Clear Glass



Power	Reflector	Lampholder	Code No
ELECTRONIC FLUO 23W	40°	E27	295101
ELECTRONIC FLUO 18W	40°	G24 d-2	295111

GOREME

ACRYLIC POLE
Class I IP65

Available in any
of these RAL colors

7004

7016

9005

9016

6002

1015

- Pipe

Steel

Body

Die cast aluminium

Cover

Die cast aluminium

Paint

Electrostatic powder

Diffuser


Acrylic Glass

Gaskets

Silicone

Connection

IP connection box



Power	Kelvin	Code No		
		2500mm	3000mm	3500mm
27W	2700 K	295303	295313	295323
27W	3000 K	295301	295311	295321
27W	4000 K	295302	295312	295322
48W	2700 K	295333	295343	295353
48W	3000 K	295331	295341	295351
48W	4000 K	295332	295342	295352

GOREME

ACRYLIC REFLECTOR POLE
Class I IP65

Available in any
of these RAL colors

7004

7016

9005

9016

6002

1015

- Pipe

Steel

Body

Die cast aluminium

Cover

Die cast aluminium

Paint

Electrostatic powder

Diffuser


Acrylic Glass

Gaskets

Silicone

Connection

IP connection box




Power	Kelvin	Code No		
		2500mm	3000mm	3500mm
27W	2700 K	295203	295213	295223
27W	3000 K	295201	295211	295221
27W	4000 K	295202	295212	295222
48W	2700 K	295233	295243	295253
48W	3000 K	295231	295241	295251
48W	4000 K	295232	295242	295252



LPA POLE MOUNTED Class I IP65

Available in any
of these RAL colors



Body

Die cast aluminium

Cover

Spinning aluminium

Paint

Electrostatic powder

Diffusers

Acrylic Glass

Gaskets

Silicone

Connection


IP connection box



Code No
A



Code No
B



Power	Real Lumen Output	Kelvin	Code No
26W	2465 lm	2700 K	437603
26W	2465 lm	3000 K	437601
26W	2835 lm	6000 K	437602
36W	3420 lm	2700 K	437613
36W	3420 lm	3000 K	437611
36W	3930 lm	6000 K	437612
E27 CFL 65W			437621

LPB POLE MOUNTED
Class I IP65

Available in any of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

Body

Die cast aluminium

Cover

Spinning aluminium

Paint

Electrostatic powder

Diffusers


Acrylic Glass

Gaskets

Silicone

Connection

IP connection box





Power	Real Lumen Output	Kelvin	Code No
30W	2850 lm	2700 K	437503
30W	2850 lm	3000 K	437501
30W	3135 lm	6000 K	437502
46W	4370 lm	2700 K	437313
46W	4370 lm	3000 K	437511
46W	4807 lm	6000 K	437512
60W	5700 lm	2700 K	437523
60W	5700 lm	3000 K	437521
60W	6270 lm	6000 K	437522
65W E27 CFL			437531

LPC POLE MOUNTED
Class I IP65

Available in any
of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

- Pipe
Steel
- Body
Die cast aluminium
- Cover
Spinning aluminium
- Paint
Electrostatic powder
- Diffusers
Acrylic Glass
- Gaskets
Silicone
- Connection
IP connection box




Power	Real Lumen Output	Kelvin	Code No
26W	2465 lm	2700 K	437403
26W	2465 lm	3000 K	437401
26W	2835 lm	6000 K	437402
36W	3420 lm	2700 K	437413
36W	3420 lm	3000 K	437411
36W	3930 lm	6000 K	437412
65W			437421

LPD

POLE MOUNTED

Class I IP65

Available in any
of these RAL colors



Pipe

Steel

Body

Die cast aluminium

Cover

Spinning aluminium

Paint

Electrostatic powder

Diffusers


Acrylic Glass

Gaskets

Silicone

Connection

IP connection box



Power	Real Lumen Output	Kelvin	Code No
35W	3325 lm	2700 K	437303
35W	3325 lm	3000 K	437301
35W	3657 lm	6000 K	437302
45W	4275 lm	2700 K	437313
45W	4275 lm	3000 K	437311
45W	4702 lm	6000 K	437312
60W	5700 lm	2700 K	437323
60W	5700 lm	3000 K	437321
60W	6270 lm	6000 K	437322
E27 CFL HALOGEN 65W			437331

LPE

POLE MOUNTED

Class I IP65

Available in any of these RAL colors

7004

7016


9005

9016

6002

1015

- Body**
Extruded aluminium pole
- Paint**
Electrostatic powder
- Diffusers**
Acrylic Glass
- Gaskets**
Silicone
- Connection**
IP connection box




Power	Real Lumen Output	Kelvin	Code No	
			One Way	Two Way
20W	1900 lm	2700 K	437203	437213
20W	1900 lm	3000 K	437201	437211
20W	2090 lm	6000 K	437202	437212
30W	2850 lm	2700 K	437223	437233
30W	2850 lm	3000 K	437221	437231
30W	3135 lm	6000 K	437222	437232
40W	3800 lm	2700 K	437243	437253
40W	5562 lm	3000 K	437241	437251
40W	4180 lm	6000 K	437242	437252

LPF


POLE MOUNTED

Class I IP65

Available in any
of these RAL colors



Pipe
Steel
Body
Die cast aluminium
Cover
White polymer plate
Paint
Electrostatic powder
Diffusers
Glass
Gaskets
Silicone
Connection
IP connection box



Power	Kelvin	Code No
30W	2700 K	437103
30W	3000 K	437101
30W	6000 K	437102
70W	2700 K	437112
70W	3000 K	437111
150W	2700 K	437122
150W	6000 K	437121




LPG POLE MOUNTED
Class I IP65

Available in any
of these RAL colors

7004	7016	9005	9016	6002	1015
------	------	------	------	------	------

- Pipe
- Steel
- Body
- Die cast aluminium
- Cover
- Spinning aluminium
- Paint
- Electrostatic powder
- Diffusers
- Acrylic Glass
- Gaskets
- Silicone
- Connection
- IP connection box



Power	Kelvin	Code No
30W	2700 K	437003
30W	3000 K	437001
30W	6000 K	437002
60W	2700 K	437013
60W	3000 K	437011
60W	6000 K	437012
90W	2700 K	437023
90W	3000 K	437021
90W	6000 K	437022
120W	2700 K	437033
120W	3000 K	437031
120W	6000 K	437032

 20mA
Led Fixtures



EMFA

BELKIS

RECESSED WALK OVER LED FIXTURES

Class II IP67

EMFA's 20mA LED fixtures are ideal for ambiance lighting outdoors and in where only touch of light is required. These fixtures apart from being used as orientation lights, can light steps and paths and highlight walls and columns acrylic are offered to fit the correct location. A choice of lighting or backlighting LEDs is offered to either a directional lighting effect or a lighting glow.

"Customization" is EMFA's standart

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standart paint colors, 5 LED colors and 2 LED types are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as small quantities.

BACKLIGHTING LEDS

Voltage : 240V A.C
(12V AC or DC, 24V AC or DC on request)


Diffuser : Clear Glass 6 mm

Standard with 5m 3x0,75 H03 VV-F cable


Available with springs for false ceiling.

Single color LED options upon request are ;

Blue Amber Green Red




BELKIS 1




Power	Code No Inox
9x20mA	418101

BELKIS 1



Power	Code No Inox
1x20mA	418111

BELKIS 2





Power	Code No Inox
18x20mA	418121

BELKIS

WALL RECESSED LED FIXTURES Class II IP67

Available in any
of these RAL colors



LIGHTING or BACKLIGHTING LEDS

Voltage : 240V A.C

(12V AC or DC, 24V AC or DC on request)

Diffuser : Clear Acrylic (Not for walk-over)

Cable : Potted 5 m 3x0,75 H03 VV-F


Standard with 5m 3x0,75 H03 VV-F cable

Available with springs for false ceiling.

Single color LED options upon request are ;


Blue Amber Green Red

BELKIS 0




Power	Code No	
	Alum	Inox
6x20mA LIGHTING LEDS	416201	416211
6x20mA LIGHTING LEDS	417101	417111

BELKIS 0





Power	Code No	
	Alum	Inox
9x20mA LIGHTING LEDS	416261	416271
9x20mA BACKLIGHTING LEDS	417191	417201

BELKIS 1



Power	Code No	
	Alum	Inox
1x20mA BACKLIGHTING LEDS	407501	417351

BELKIS 2






Power	Code No	
	Alum	Inox
12x20mA LIGHTING LEDS	416281	
4x20mA LIGHTING LEDS	416291	
4x20mA BACKLIGHTING LEDS	417561	
4x20mA BACKLIGHTING LEDS	417571	

BELKIS

WALL RECESSED LED FIXTURES

Class II IP67

Available in any
of these RAL colors



LIGHTING or BACKLIGHTING LEDS

Voltage : 240V A.C
(12V AC or DC, 24V AC or DC on request)

Diffuser : Clear Acrylic (Not for walk-over)

Cable : Potted 5 m 3x0,75 H03 VV-F


Standard with 5m 3x0,75 H03 VV-F cable

Available with springs for false ceiling.

Single color LED options upon request are ;


Blue Amber Green Red

BELKIS 1



Power	Code No
12x20mA LIGHTING LEDS	417801
12x20mA BACKLIGHTING LEDS	417641

BELKIS 1




Power	Lens	Code No
12x20mA LIGHTING LEDS	Asymmetrical	417771
4x20mA LIGHTING LEDS	Asymmetrical 30°	417691
4x20mA LIGHTING LEDS	Asymmetrical 120°	417811

BELKIS

SURFACE MOUNTED LED FIXTURES

Class II IP67

Available in any
of these RAL colors



LIGHTING or BACKLIGHTING LEDS

Voltage : 240V A.C
(12V AC or DC, 24V AC or DC on request)


Diffuser : Clear Acrylic

Standard with 5m 3x0,75 H03 VV-F cable

Single color LED options upon request are ;



Blue Amber Green Red

BELKIS 0




Power	Code No	
	Alum	Inox
6x20mA LIGHTINGS LEDS	416221	416231
6x20mA BACKLIGHTING LEDS	417141	417151

BELKIS 0




Power	Code No	
	Alum	Inox
9x20mA LIGHTINGS LEDS	417751	417761
9x20mA BACKLIGHTING LEDS	417271	417281

BELKIS 1



Power	Code No
12x20mA LIGHTINGS LEDS	418201
12x20mA BACKLIGHTING LEDS	418211

BELKIS 1 ASYMMETRICAL



Power	Lens	Code No
12x20mA LIGHTINGS LEDS	Asymmetrical	418251
4x20mA LIGHTINGS LEDS	Asymmetrical 30°	418311
4x20mA LIGHTINGS LEDS	Asymmetrical 120°	418321

DYO

WALL RECESSED LED FIXTURES

Class II IP67



Outer Frame & Body

Anodized aluminium

Recessing Box

Galvanized Steel

Voltage

: 240V A.C

(12V AC or DC, 24V AC or DC on request)

Diffuser

: Clear Poly Carbonate


Cable

: Standard with 5m 3x0,75 H03 VV-F cable

Single color LED options upon request are ;


Blue Amber Green Red

SYMMETRICAL INOX




Power	Lens	Code No
12x20mA BACKLIGHTING LEDS	120°	404501

ASYMMETRICAL INOX




Power	Lens	Code No
12x20mA LIGHTING LEDS	30°	404511
4x20mA LIGHTING LEDS	30°	404521

ASYMMETRICAL ANODIZED ALUMINIUM



Power	Code No
3x20mA LIGHTING LEDS	405101

ASYMMETRICAL ANODIZED ALUMINIUM



Power	Code No
4x20mA LIGHTING LEDS	405151