ASSOS 4 RECESSED DRIVE OVER FIXTURES Load 15 kN | Class I IP67 IK10

Available in any of these RAL colors









EMFA's Assos 4 series is specially designed to light facades, columns, monuments and trees. The fixture can be equipped with metal halide, halogen or fluorescent lamps. The fixture has 3 different options of cover: 316 stainless steel, die cast aluminium or bronze in combination with the die cast aluminium body which allows for IP67 and IK10 and a load of 15kN. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete. A louvre can be ordered separately to reduce the glare of the lamps. An anti-slip glass is available upon request.

Cover

Die cast aluminium / 316L Stainless Steel

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box. Gaskets


Silicone


Diffusers 15 mm Tempered Glass Screws 316L Stainless steel Glands

2 x PG 13.5 **Recessing Tube**

Polyamide 6











Lampholder : G x 8.5 Fixed or Adjustable ± 15°

Reflector

Diffuser : Clear Glass : 166°C Temp





Louvre To avoid glare. Can be applied to all lamp types except Halogen PAR 30 and 38

Code No 955105

Caution:

207271

The louvre and filter cannot be applied to the standard fixture. These options should be mentioned when ordering.



Anti-slip Glass

Please contact for this option.

METAL HALIDE CDMR 111 35W / 70W Code No

Inox (Stainless Steel)

