# ASSOS 6 RECESSED DRIVE OVER FIXTURES Load 15 kN | Class I IP67 IK10

EMFA's Assos 6 series is specially designed to light facades, columns, monuments and trees. The fixture can be equipped with metal halide, halogen or fluorescent lamps. The fixture is made of a combination of 316L stainless steel and die cast aluminium, which allows for IP67 and IK10 and a load of 15kN. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete. A louvre can be ordered separately to reduce the glare of the lamps. An anti-slip glass is available upon request.

Cover

316L Stainless steel

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Silicone

Diffusers


15 mm Tempered Glass (Aluminium Cover)

Screws

316L Stainless steel Glands

2 x PG 13.5 **Recessing Tube** Polyamide 6









#### METAL HALIDE




Lampholder : G x 8.5 Fixed or Adjustable ± 15°

Reflector

Diffuser : Clear Glass

Temp : 166°C

METAL HALIDE CDMR 111 35W / 70W Code No 212271 Inox (Stainless Steel)



### Accessories:



Louvre To avoid glare. Can be applied to all lamp types except Halogen PAR 30 and 38

Code No 955105

#### Caution:

The louvre and filter cannot be applied to the standard fixture. These options should be mentioned when ordering.



## Square Version:

All fixtures are available with a square cover with dimensions 220 x 220 mm. Please indicate square version when ordering.

