ASSOS 6 RECESSED DRIVE OVER FIXTURES Load 15 kN | Class I IP67 IK10

EMFA's Assos 6 series is specially designed to light facades, columns, monuments and trees. The fixture can be equipped with metal halide, halogen or fluorescent lamps. The fixture is made of a combination of 316L stainless steel and die cast aluminium, which allows for IP67 and IK10 and a load of 15kN. The fixture comes with a polyamide recessing tube for easy mounting in the ground or concrete. A louvre can be ordered separately to reduce the glare of the lamps. An anti-slip glass is available upon request.

Cover

316L Stainless steel

Die cast aluminium or aluminium profile with die cast aluminium bottom and connection box.

Gaskets Silicone

Diffusers

15 mm Tempered Glass (Aluminium Cover)


Screws

316L Stainless steel

Glands 2 x PG 13.5

Recessing Tube Polyamide 6









HALOGEN




Lampholder : E27 Adjustable ± 20°

Reflector

Diffuser : Clear Glass

Temp : 129°C



HALOGEN PAR 30 / 75W Inox (Stainless Steel) 221391

Code No



Accessories:

Caution: The louvre and filter cannot be applied to the standard fixture. These options should be mentioned when ordering.

Louvre To avoid glare.

and 38

Code No



Square Version:

All fixtures are available with a square cover with dimensions 220 x 220 mm. Please indicate square version when ordering.

Can be applied to all lamp types except Halogen PAR 30

955105

