BELKIS 1 RECESSED WALK OVER LED FIXTURES Class II IP67


EMFA's 20mA LED fixtures are ideal for ambiance lighting outdoors and in where only a touch of light is required. These fixtures apart from being used as orientation lights, can light steps and paths and highlight walls and columns. A material mix of die cast aluminium, marine grade stainless steel and acrylic are offered to fit the correct location. A choice of lighting or backlighting LEDs is offered to either give a directional lighting effect or a lighting glow.


"Customization" is EMFA's standard

EMFA offers many combinations for each fixture, as all fixtures are made in house. A combination of 6 standard paint colors, 5 LED colors and 2 LED types are available to make the fixture suitable for the required application. This is done without increasing lead-time and is available for large as well as small quantities.









: 240V A.C Voltage

(12V AC or DC, 24V AC or DC on request)

Diffuser : Clear Glass 6 mm

Standard with 5m 3x0,75 H03 VV-F cable Available with springs for false ceiling.


Ø 75
(a (000) (a (000) (a (000))





INOX

Code No 9 x 20 mA BACKLIGHTING LEDS nox 418101 Warm White









: 240V A.C Voltage

(12V AC or DC, 24V AC or DC on request)

Diffuser : Clear Glass 6 mm

Standard with 5m 3x0,75 H03 VV-F cable Available with springs for false ceiling.

1 x 20 mA BACKLIGHTING LEDS	Code No Inox
Warm White	418111









Recessing Box

BELKIS 1 WALL RECESSED LED FIXTURES Class II IP67







Voltage : 240V A.C

(12V AC or DC, 24V AC or DC on request)

Diffuser: Clear Acrylic (Not for walk-over) Standard with 5m 3x0,75 H03 VV-F cable Available with springs for false ceiling. ALUM



Ø 54



1 x 20 mA BACKLIGHTING LEDS	Code No	
	Alum	Inox
Warm White	407501	417351

Single color LED options upon request are ;






BELKIS 1 WALL RECESSED LED FIXTURES Class II IP67









Voltage : 240V A.C

(12V AC or DC, 24V AC or DC on request)

: Clear Acrylic (Not for walk-over) Diffuser Standard with 5m 3x0,75 H03 VV-F cable

Symmetrical


12 x 20 mA LIGHTING LEDS	Code No
A Warm White	417801


Symmetrical

12 x 20 mA BACKLIGHTING LEDS	Code No
△ Warm White	417641

Single color LED options upon request are; _ Blue _ Amber _ Green _ Red







Plastik Recessing Box

Recessing Box

ALUM

9 0000

ALUM

Voltage : 240V A.C

(12V AC or DC, 24V AC or DC on request)

Diffuser : Clear Acrylic

Standard with 5m 3x0,75 H03 VV-F cable

Symmetrical

12 x 20 mA LIGHTING LEDS Code No 417771 Warm White

Symmetrical Code No

4 x 20 mA BACKLIGHTING LEDS Asymmetrical 30° Asymmetrical 120° 417691 417811 Warm White

Single color LED options upon request are;



BELKIS 1 SURFACE MOUNTED LED FIXTURES Class II IP67

Available in any of these RAL colors




















0000 ALUM

Voltage : 240V A.C

(12V AC or DC, 24V AC or DC on request)

Diffuser : Clear Acrylic (Not for walk-over) Standard with 5m 3x0,75 H03 VV-F cable


Symmetrical


12 x 20 mA LIGHTING LEDS	Code No
A Warm White	418201

12 x 20 mA BACKLIGHTING LEDS Code No Warm White 418211

Single color LED options upon request are; ⚠ Blue 🔔 Amber 🔔 Green 🔔 Red







Voltage : 240V A.C

(12V AC or DC, 24V AC or DC on request)

Diffuser : Clear Acrylic

Standard with 5m 3x0,75 H03 VV-F cable

Asymmetrical

12 x 20 mA LIGHTING LEDS Code No Warm White 418251

Code No 4 x 20 mA LIGHTING LEDS Asymmetrical 30° Asymmetrical 120° 418311 Warm White 418321

Single color LED options upon request are; ▲ Blue 🔔 Amber 🔔 Green 🔔 Red

